

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	00477
NAME:	Benzoic acid
SYNONYMS:	Benzene carboxylic acid Carboxybenzene
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
SKIN IRRITATION (CATEGORY 2), H315

SERIOUS EYE DAMAGE (CATEGORY 1), H318

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE, INHALATION
(CATEGORY 1), LUNGS, H372

ACUTE AQUATIC TOXICITY (CATEGORY 3), H402

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE
SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H315 CAUSES SKIN IRRITATION
H318 CAUSES SERIOUS EYE DAMAGE.
H372 CAUSES DAMAGE TO ORGANS (LUNGS) THROUGH
PROLONGED OR REPEATED EXPOSURE IF INHALED.
H402 HARMFUL TO AQUATIC LIFE.

PRECAUTIONARY STATEMENT(S)

P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/
SPRAY
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS
PRODUCT.
P273 AVOID RELEASE TO THE ENVIRONMENT.
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE
PROTECTION/ FACE PROTECTION.
P302 + P352 IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER
P305 + P351 + P338 + IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL
P310 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND
EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A
POISON CENTER/DOCTOR.
P314 GET MEDICAL ADVICE/ ATTENTION IF YOU FEEL UNWELL
P332 + P313 IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/
ATTENTION
P362 TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE
REUSE
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
WASTE DISPOSAL PLANT.

**HAZARDS NOT
OTHERWISE
CLASSIFIED (HNOC)
OR NOT COVERED
BY GHS** NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: C₇H₆O₂

MW: 122.10

CAS-NO. 65-85-0

PURITY: 99.5 - 100.5% (Assay on anhydrous basis)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Benzoic acid		
	SKIN IRRIT. 2; EYE DAM. 1; STOT RE 1; AQUATIC ACUTE 3; H315, H318, H372, H402	90 - 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	WASH OFF WITH SOAP AND PLENTY OF WATER. TAKE VICTIM IMMEDIATELY TO HOSPITAL. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.CONTINUE RINSING EYES DURING TRANSPORT TO HOSPITAL.
IF SWALLOWED	NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND	NO DATA AVAILABLE

**SPECIAL TREATMENT
NEEDED**

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

**SUITABLE
EXTINGUISHING MEDIA** USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY
CHEMICAL OR CARBON DIOXIDE.

**SPECIAL HAZARDS
ARISING FROM THE
SUBSTANCE OR MIXTURE** NO DATA AVAILABLE

**ADVICE FOR
FIREFIGHTERS** WEAR SELF-CONTAINED BREATHING APPARATUS FOR
FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES** USE PERSONAL PROTECTIVE EQUIPMENT. AVOID
DUST FORMATION. AVOID BREATHING VAPOURS, MIST
OR GAS. ENSURE ADEQUATE VENTILATION.
EVACUATE PERSONNEL TO SAFE AREAS. AVOID
BREATHING DUST.

FOR PERSONAL PROTECTION SEE SECTION 8.

**ENVIRONMENTAL
PRECAUTIONS** PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE
TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.
DISCHARGE INTO THE ENVIRONMENT MUST BE
AVOIDED.

**METHODS AND
MATERIALS FOR
CONTAINMENT AND
CLEANING UP** PICK UP AND ARRANGE DISPOSAL WITHOUT
CREATING DUST. SWEEP UP AND SHOVEL. KEEP IN
SUITABLE, CLOSED CONTAINERS FOR DISPOSAL

**REFERENCE TO OTHER
SECTIONS** FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS.FURTHER PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE ADDITIONAL PROCESSING OCCURS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE.. Store at RT

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

DERIVED NO EFFECT LEVEL (DNEL)

APPLICATION AREA	EXPOSURE ROUTES	HEALTH EFFECT	VALUE
WORKERS	INHALATION	LONG-TERM LOCAL EFFECTS	0.1 MG/M3
WORKERS	INHALATION	LONG-TERM SYSTEMIC EFFECTS	3 MG/M3
WORKERS	SKIN CONTACT	LONG-TERM SYSTEMIC EFFECTS	62.5MG/KG BW/D

PREDICTED NO EFFECT CONCENTRATION (PNEC)

COMPARTMENT	VALUE
SOIL	0.151 MG/KG
MARINE WATER	0.034 MG/L
MARINE SEDIMENT	0.175 MG/KG
FRESH WATER SEDIM	1.75 MG/KG
SEWAGE TREATMENT PLANT	100 MG/L
AQUATIC INTERMITTENT RELEASE	0.331 MG/L

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION	FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).
SKIN PROTECTION	<p>HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.</p> <p>FULL CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:DERMATRIL (KCL 740 , SIZE M)</p> <p>SPLASH CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)</p> <p>IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.</p>
BODY PROTECTION	COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.
RESPIRATORY PROTECTION	WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	White crystalline powder
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	2.5 - 3.5 AT 20 C
MELTING POINT/FREEZING POINT	122 - 123 °C
INITIAL BOILING POINT AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	13 HPA (10 MMHG) AT 132 C
VAPOUR DENSITY	4.22 - (AIR = 1.0)
RELATIVE DENSITY	
WATER SOLUBILITY	2.9 G/L AT 25 C
PARTITION COEFFICIENT: N- OCTANOL/WATER	LOG POW: 1.88
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION

RELATIVE VAPOUR DENSITY	4.22 - (AIR = 1.0)
-------------------------	--------------------

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
-------------------	-------------------

CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
---------------------------	--

POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	NO DATA AVAILABLE
INCOMPATIBLE MATERIALS	STRONG OXIDIZING AGENTS, STRONG BASES, STRONG REDUCING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. CARBON OXIDES. OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	LD50 ORAL - RAT - FEMALE - 2,360 MG/KG (OECD TEST GUIDELINE 401) REMARKS: BEHAVIORAL:SOMNOLENCE (GENERAL DEPRESSED ACTIVITY). CYANOSIS LC50 INHALATION - RAT - 4 H - > 12.2 MG/L LD50 DERMAL - RABBIT - > 2,000 MG/KG NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	CLASSIFIED ACCORDING TO REGULATION (EU) 1272/2008, ANNEX VI (TABLE 3.1/3.2)
SERIOUS EYE DAMAGE/EYE IRRITATION	EYES - RABBIT RESULT: CORROSIVE (DIRECTIVE 67/548/EEC, ANNEX V, B.5.)
RESPIRATORY OR SKIN SENSITISATION	MAXIMISATION TEST - GUINEA PIG RESULT: DOES NOT CAUSE SKIN SENSITISATION. (OECD TEST GUIDELINE 406)
GERM CELL MUTAGENICITY	NO DATA AVAILABLE AMES TEST S. TYPHIMURIUM RESULT: NEGATIVE
CARCINOGENICITY	

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY OSHA.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE INHALATION - CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. - LUNGS

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION RTECS: DG0875000

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY

TOXICITY TO FISH LC50 - LEPOMIS MACROCHIRUS - 44.6 MG/L - 96 H
TOXICITY TO DAPHNIA AND IMMOBILIZATION EC50 - DAPHNIA MAGNA (WATER
OTHER AQUATIC FLEA) - 860 MG/L - 48 H
INVERTEBRATES

TOXICITY TO ALGAE STATIC TEST EC50 - PSEUDOKIRCHNERIELLA
SUBCAPITATA - > 33.1 MG/L - 72 H
(OECD TEST GUIDELINE 201)

PERSISTENCE AND DEGRADABILITY EXPECTED TO BE BIODEGRADABLE

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION LEUCISCUS IDUS (GOLDEN ORFE) - 3 D - 50 G/L

BIOCONCENTRATION FACTOR (BCF): 5.3

MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL HANDLING OR DISPOSAL. HARMFUL TO AQUATIC LIFE.
	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)	
PROPER SHIPPING NAME:	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLIDN.O.S (Benzoic acid)
UN NUMBER:	3077
CLASS:	9
PACKING GROUP:	III
REPORTABLE QUANTITY (RQ):	5000 LBS
POISON INHALATION HAZARD:	NO

IMDG
NOT DANGEROUS GOODS

IATA

NOT DANGEROUS GOODS

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS
ACUTE HEALTH HAZARD

CALIFORNIA PROP. 65 COMPONENTS
THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE HARM

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

AQUATIC ACUTE	ACUTE AQUATIC TOXICITY
EYE DAM.	SERIOUS EYE DAMAGE
H315	CAUSES SKIN IRRITATION
H318	CAUSES SERIOUS EYE DAMAGE
H372	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE IF INHALED
H402	HARMFUL TO AQUATIC LIFE
SKIN IRRIT.	SKIN IRRITATION
STOT RE	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

HMIS RATING

HEALTH HAZARD:	3
CHRONIC HEALTH HAZARD:	*
FLAMMABILITY:	1
PHYSICAL HAZARD	0

NFPA RATING

HEALTH HAZARD:	3
FIRE HAZARD:	1
REACTIVITY HAZARD:	0

MSDS LEGEND

MW: MOLECULAR WEIGHT
MF: MOLECULAR FORMULA
VOC: VOLATILE ORGANIC COMPOUNDS
ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL
HYGINISTS
CAS: CHEMICAL ABSTRACTS SERVICE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION:3.1.

REVISION DATE: 01/27/2017