Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 00757

NAME: Ethyl acetate

SYNONYMS: Acetic acid ethyl ester

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE LIQUIDS (CATEGORY 2), H225 EYE IRRITATION (CATEGORY 2A), H319

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), CENTRAL NERVOUS SYSTEM, H336

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.

H319 CAUSES SERIOUS EYE IRRITATION.

H336 MAY CAUSE DROWSINESS OR DIZZINESS.

PRECAUTIONARY STATEMENT(S)

PRECAUTIONARY STA	
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT
	SURFACES NO SMOKING.
P233	KEEP CONTAINER TIGHTLY CLOSED.
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/
	LIGHTING EQUIPMENT.
P242	USE ONLY NON-SPARKING TOOLS.
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC
	DISCHARGE.
P261	AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/
	SPRAY.
P264	WASH SKIN THOROUGHLY AFTER HANDLING.
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P280	WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE
	PROTECTION.
P303 + P361 + P353	IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY
	ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/
	SHOWER.
P304 + P340 + P312	IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT
	REST IN A POSITION COMFORTABLE FOR BREATHING. CALL
	A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL
	UNWELL.
P305 + P351 + P338	IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL
	MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND
	EASY TO DO. CONTINUE RINSING.
P337 + P313	IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/
	ATTENTION.
P370 + P378	IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR
	ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P403 + P233	STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER
	TIGHTLY CLOSED.
P403 + P235	STORE IN A WELL-VENTILATED PLACE. KEEP COOL.
P405	STORE LOCKED UP.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
	HILL OTTE DIGDOGLI DI LIVE

WASTE DISPOSAL PLANT.

HAZARDS NOT NONE
OTHERWISE
CLASSIFIED (HNOC)
OR NOT COVERED
BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: $C_4H_8O_2$

MW: 88.11

CAS-NO. 141-78-6

PURITY: $\geq 99.7\%$ (GC)

ETHYL ACETATE

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Ethyl acetate		
	FLAM. LIQ. 2; EYE IRRIT. 2A; STOT SE 3; H225, H319, H336 CONCENTRATION LIMITS: 20	<= 100 %
	%: STOT SE 3, H336	

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN, SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN WASH OFF WITH SOAP AND PLENTY OF WATER.

CONTACT CONSULT A PHYSICIAN.

IN CASE OF EYE RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

CONTACT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

IF SWALLOWED DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING

BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE

MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE SUITABLE EXTINGUISHING MEDIA DRY POWDER DRY SAND

UNSUITABLE EXTINGUISHING MEDIA DO NOT USE WATER JET.

SPECIAL HAZARDS
ARISING FROM THE
SUBSTANCE OR MIXTURE

CARBON OXIDES

ADVICE FOR FIREFIGHTERS WEAR SELF-CONTAINED BREATHING APPARATUS FOR

FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES

USE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN

ACCUMULATE IN LOW AREAS.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP CONTAIN SPILLAGE, AND THEN COLLECT WITH NON-COMBUSTIBLE ABSORBENT MATERIAL, (E.G. SAND, EARTH, DIATOMACEOUS EARTH, VERMICULITE) AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL/NATIONAL REGULATIONS (SEE SECTION 13).

REFERENCE TO OTHER SECTIONS

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

AVOID CONTACT WITH SKIN AND EYES. AVOID

INHALATION OF VAPOUR OR MIST.

USE EXPLOSION-PROOF EQUIPMENT.KEEP AWAY FROM

SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF

ELECTROSTATIC CHARGE.

FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT

UPRIGHT TO PREVENT LEAKAGE.

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS
			PARAMETERS	
Ethyl acetate	141-78-6	TWA	400 PPM	USA. ACGIH
				THRESHOLD LIMIT
				VALUES (TLV)
	REMARKS	UPPER RESPIRATORY TRACT IRRITATION		
		EYE IRRITATION		
		TWA	400 PPM	USA. NIOSH
			1,400 MG/M3	RECOMMENDED
				EXPOSURE LIMITS

,	TWA	400 PPM	USA. OCCUPATIONAL
		1,400 MG/M3	EXPOSURE LIMITS
			(OSHA) - TABLE Z-1
			LIMITS FOR AIR
			CONTAMINANTS
,	THE VALUE IN MG/M3 IS APPROXIMATE.		
-	PEL	400 PPM	CALIFORNIA
		1,400 MG/M3	PERMISSIBLE
			EXPOSURE LIMITS FOR
			CHEMICAL
			CONTAMINANTS

PREDICTED NO EFFECT CONCENTRATION (PNEC)

COMPARTMENT	VALUE
SOIL	0.24 MG/KG
MARINE WATER	0.026 MG/L
FRESH WATER	0.26 MG/L
MARINE SEDIMENT	0.125 MG/KG
FRESH WATER SEDIMENT	1.25 MG/KG

EXPOSURE CONTROLS

APPROPRIATEHANDLE IN ACCORDANCE WITH GOOD INDUSTRIALENGINEERINGHYGIENE AND SAFETY PRACTICE. WASH HANDSCONTROLSBEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT

FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

SPLASH CONTACT

MATERIAL: BUTYL-RUBBER

SPECIFIC USE SCENARIO.

MINIMUM LAYER THICKNESS: 0.3 MM BREAK THROUGH TIME: 113 MIN

MATERIAL TESTED:BUTOJECT (KCL 897, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY

BODY PROTECTION

IMPERVIOUS CLOTHING, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Clear, free or clear and colorless liquid

ODOUR NO DATA AVAILABLE
ODOUR THRESHOLD NO DATA AVAILABLE
PH NO DATA AVAILABLE

MELTING -84 °C

POINT/FREEZING POINT

INITIAL BOILING POINT 76.5 - 77.5 °C

AND BOILING RANGE

FLASH POINT -3 °C

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER UPPER EXPLOSION LIMIT: 11.5 %(V) FLAMMABILITY OR LOWER EXPLOSION LIMIT: 2.2 %(V)

EXPLOSIVE LIMITS

VAPOUR PRESSURE 97.3 HPA AT 20.0 C VAPOUR DENSITY NO DATA AVAILABLE RELATIVE DENSITY 0.902 g/mL at 25 °C

WATER SOLUBILITY SOLUBLE PARTITION COEFFICIENT: LOG POW: 0.73

N- OCTANOL/WATER

AUTO-IGNITION 427.0 C

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

SURFACE TENSION 24.0 MN/M AT 20.0 C

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

CONDITIONS TO AVOID HEAT, FLAMES AND SPARKS.

INCOMPATIBLE MATERIALS STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS OTHER DECOMPOSITION PRODUCTS - NO DATA

AVAILABLE

HAZARDOUS DECOMPOSITION PRODUCTS FORMED

UNDER FIRE CONDITIONS. - CARBON OXIDES

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY LD50 ORAL - RAT - 5,620 MG/KG

LC50 INHALATION - MOUSE - 2 H - 45,000 MG/M3

LD50 DERMAL - RABBIT - > 18,000 MG/KG

NO DATA AVAILABLE

SKIN - RABBIT

CORROSION/IRRITATION RESULT: MILD SKIN IRRITATION

(OECD TEST GUIDELINE 404)

SERIOUS EYE NO DATA AVAILABLE

DAMAGE/EYE IRRITATION

RESPIRATORY OR SKIN NO

SENSITISATION

NO DATA AVAILABLE

GERM CELL NO DATA AVAILABLE

MUTAGENICITY

CARCINOGENICITY

THIS PRODUCT IS OR CONTAINS A COMPONENT THAT IS NOT CLASSIFIABLE AS TO ITS CARCINOGENICITY BASED ON ITS IARC, ACGIH, NTP, OR EPA CLASSIFICATION.

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC. NO COMPONENT OF THIS PRODUCT PRESENT AT

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE

EXPOSURE

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - REPEATED

EXPOSURE

NO DATA AVAILABLE

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION RTECS: AH5425000

INHALATION OF HIGH CONCENTRATIONS MAY CAUSE: HEADACHE, DROWSINESS, DIZZINESS,

VOMITING, NARCOSIS, ANEMIA, CENTRAL NERVOUS

SYSTEM DEPRESSION

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE

NOT BEEN THOROUGHLY INVESTIGATED.

KIDNEY - IRREGULARITIES - BASED ON HUMAN

EVIDENCE

SECTION 12. **ECOLOGICAL INFORMATION**

TOXICITY

TOXICITY TO FISH LC50 - ONCORHYNCHUS MYKISS (RAINBOW TROUT)

- 350.00 - 600.00 MG/L - 96 H

LC50 - PIMEPHALES PROMELAS (FATHEAD MINNOW)

- 220.00 - 250.00 MG/L - 96 H

TOXICITY TO DAPHNIA AND

OTHER AQUATIC

EC50 - DAPHNIA MAGNA (WATER FLEA) - 2,300.00 -

3,090.00 MG/L - 24 H

INVERTEBRATES LC50 - DAPHNIA MAGNA (WATER FLEA) - 560 MG/L -

TOXICITY TO ALGAE EC50 - ALGAE - 4,300.00 MG/L - 24 H

EC50 - SELENASTRUM - 1,800.00 - 3,200.00 MG/L - 72 H

PERSISTENCE AND **DEGRADABILITY**

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS

CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT CONTACT A LICENSED PROFESSIONAL WASTE

DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.
OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS
TO A LICENSED DISPOSAL COMPANY. BURN IN A
CHEMICAL INCINERATOR EQUIPPED WITH AN
AFTERBURNER AND SCRUBBER BUT EXERT EXTRA
CARE IN IGNITING AS THIS MATERIAL IS HIGHLY

FLAMMABLE.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: ETHYL ACETATE

UN NUMBER: 1173 CLASS: 3 PACKING GROUP: II

REPORTABLE QUANTITY 5000 LBS

(RO):

POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: ETHYL ACETATE

UN NUMBER: 1173
CLASS: 3
PACKING GROUP: II
EMS-NO: F-E, S-D

IATA

PROPER SHIPPING NAME: ETHYL ACETATE

UN NUMBER: 1173 CLASS: 3 PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL

COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DEMINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS FIRE HAZARD, ACUTE HEALTH HAZARD, CHRONIC

HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Ethyl acetate 141-78-6 02-16-1993

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.

H319 CAUSES SERIOUS EYE IRRITATION.

H336 MAY CAUSE DROWSINESS OR DIZZINESS.

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.