

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	01464
NAME:	Stannous chloride dihydrate
SYNONYMS:	Tin(II) chloride dihydrate
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
CORROSIVE TO METALS (CATEGORY 1), H290

ACUTE TOXICITY, ORAL (CATEGORY 4), H302
 ACUTE TOXICITY, INHALATION (CATEGORY 4), H332
 SKIN CORROSION (CATEGORY 1B), H314
 SERIOUS EYE DAMAGE (CATEGORY 1), H318
 SKIN SENSITISATION (CATEGORY 1), H317
 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3),
 RESPIRATORY SYSTEM, H335
 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE, ORAL (CATEGORY 2),
 CARDIO-VASCULAR SYSTEM, H373
 SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 3), H402
 LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 3), H412

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
 PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H290	MAY BE CORROSIVE TO METALS.
H302 + H332	HARMFUL IF SWALLOWED OR IF INHALED.
H314	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H317	MAY CAUSE AN ALLERGIC SKIN REACTION.
H335	MAY CAUSE RESPIRATORY IRRITATION.
H373	MAY CAUSE DAMAGE TO ORGANS (CARDIO-VASCULAR SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE IF SWALLOWED.
H412	HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT(S)

P234	KEEP ONLY IN ORIGINAL CONTAINER.
P260	DO NOT BREATHE DUST.
P264	WASH SKIN THOROUGHLY AFTER HANDLING.
P270	DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P272	CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.
P273	AVOID RELEASE TO THE ENVIRONMENT.
P280	WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.
P301 + P312 + P330	IF SWALLOWED: CALL A POISON CENTER/ DOCTOR IF YOU FEEL UNWELL. RINSE MOUTH.
P301 + P330 + P331	IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING.
P303 + P361 + P353	IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER.
P304 + P340 + P310	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A

P305 + P351 + P338 + P310	POISON CENTER OR DOCTOR/ PHYSICIAN. IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A POISON CENTER OR DOCTOR/ PHYSICIAN.
P314 P333 + P313	GET MEDICAL ADVICE/ ATTENTION IF YOU FEEL UNWELL. IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ ATTENTION.
P363 P390 P403 + P233	WASH CONTAMINATED CLOTHING BEFORE REUSE. ABSORB SPILLAGE TO PREVENT MATERIAL DAMAGE. STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.
P405 P406	STORE LOCKED UP. STORE IN CORROSIVE RESISTANT CONTAINER WITH A RESISTANT INNER LINER.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.
HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS	NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:	SnCl ₂ ·2H ₂ O
MW:	225.63
CAS-NO.	10025-69-1
PURITY:	98 - 103% (Assay by titration)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Stannous chloride dihydrate	MET. CORR. 1; ACUTE TOX. 4; SKIN CORR. 1B; EYE DAM. 1; SKIN SENS. 1; STOT SE 3; STOT RE 2; AQUATIC ACUTE 3; AQUATIC CHRONIC 3; H290, H302, H332, H314, H318, H317, H335, H373, H402, H412	<= 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	FIRST AIDERS NEED TO PROTECT THEMSELVES. SHOW THIS MATERIAL SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.
IF INHALED	AFTER INHALATION: FRESH AIR. IMMEDIATELY CALL IN PHYSICIAN. IF BREATHING STOPS: IMMEDIATELY APPLY ARTIFICIAL RESPIRATION, IF NECESSARY ALSO OXYGEN.
IN CASE OF SKIN CONTACT	IN CASE OF SKIN CONTACT: TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER. CALL A PHYSICIAN IMMEDIATELY.
IN CASE OF EYE CONTACT	AFTER EYE CONTACT: RINSE OUT WITH PLENTY OF WATER. IMMEDIATELY CALL IN OPHTHALMOLOGIST. REMOVE CONTACT LENSES.
IF SWALLOWED	AFTER SWALLOWING: MAKE VICTIM DRINK WATER (TWO GLASSES AT MOST), AVOID VOMITING (RISK OF PERFORATION). CALL A PHYSICIAN IMMEDIATELY. DO NOT ATTEMPT TO NEUTRALISE.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	SUITABLE EXTINGUISHING MEDIA USE EXTINGUISHING MEASURES THAT ARE APPROPRIATE TO LOCAL CIRCUMSTANCES AND THE SURROUNDING ENVIRONMENT.
	UNSUITABLE EXTINGUISHING MEDIA FOR THIS SUBSTANCE/MIXTURE NO LIMITATIONS OF EXTINGUISHING AGENTS ARE GIVEN.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	HYDROGEN CHLORIDE GAS TIN/TIN OXIDES NOT COMBUSTIBLE. AMBIENT FIRE MAY LIBERATE HAZARDOUS VAPOURS.
ADVICE FOR FIREFIGHTERS	STAY IN DANGER AREA ONLY WITH SELF-CONTAINED BREATHING APPARATUS. PREVENT SKIN CONTACT BY KEEPING A SAFE DISTANCE OR BY WEARING SUITABLE PROTECTIVE CLOTHING.
FURTHER INFORMATION	SUPPRESS (KNOCK DOWN) GASES/VAPORS/MISTS WITH A WATER SPRAY JET. PREVENT FIRE EXTINGUISHING WATER FROM CONTAMINATING SURFACE WATER OR THE GROUND WATER SYSTEM.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	ADVICE FOR NON-EMERGENCY PERSONNEL: AVOID INHALATION OF DUSTS. AVOID SUBSTANCE CONTACT. ENSURE ADEQUATE VENTILATION. EVACUATE THE DANGER AREA, OBSERVE EMERGENCY PROCEDURES, CONSULT AN EXPERT. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS	DO NOT LET PRODUCT ENTER DRAINS.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	COVER DRAINS. COLLECT, BIND, AND PUMP OFF SPILLS. OBSERVE POSSIBLE MATERIAL RESTRICTIONS (SEE SECTIONS 7 AND 10). TAKE UP DRY. DISPOSE OF PROPERLY. CLEAN UP AFFECTED AREA. AVOID GENERATION OF DUSTS.
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	WORK UNDER HOOD. DO NOT INHALE SUBSTANCE/MIXTURE. IMMEDIATELY CHANGE CONTAMINATED CLOTHING. APPLY PREVENTIVE SKIN PROTECTION. WASH HANDS AND FACE AFTER WORKING WITH SUBSTANCE. FOR PRECAUTIONS SEE SECTION 2.2.
--------------------------------------	--

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

NO METAL CONTAINERS. TIGHTLY CLOSED. DRY. AIR AND MOISTURE SENSITIVE. STORE UNDER INERT GAS.

Store at RT

STORAGE CLASS (TRGS 510): 8B: NON-COMBUSTIBLE, CORROSIVE HAZARDOUS MATERIALS

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
STANNOUS CHLORIDE DEHYDRATE	10025-69-1	TWA	2 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		TWA	2 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		TWA	2 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		PEL	2 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS (TITLE 8, ARTICLE 107)

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

IMMEDIATELY CHANGE CONTAMINATED CLOTHING. APPLY PREVENTIVE SKIN PROTECTION. WASH HANDS AND FACE AFTER WORKING WITH SUBSTANCE.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU). TIGHTLY FITTING SAFETY GOGGLES

SKIN PROTECTION

THIS RECOMMENDATION APPLIES ONLY TO THE PRODUCT STATED IN THE SAFETY DATA SHEET, SUPPLIED BY US AND FOR THE DESIGNATED USE. WHEN DISSOLVING IN OR MIXING WITH OTHER SUBSTANCES AND UNDER CONDITIONS DEVIATING FROM THOSE STATED IN EN 16523-1 PLEASE CONTACT THE SUPPLIER OF CE-APPROVED GLOVES.

FULL CONTACT

MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:KCL 741 DERMATRIL L

THIS RECOMMENDATION APPLIES ONLY TO THE PRODUCT STATED IN THE SAFETY DATA SHEET, SUPPLIED BY US AND FOR THE DESIGNATED USE. WHEN DISSOLVING IN OR MIXING WITH OTHER SUBSTANCES AND UNDER CONDITIONS DEVIATING FROM THOSE STATED IN EN 16523-1 PLEASE CONTACT THE SUPPLIER OF CE-APPROVED GLOVES.

SPLASH CONTACT

MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:KCL 741 DERMATRIL L

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

RECOMMENDED FILTER TYPE: FILTER TYPE P2
THE ENTREPRENEUR HAS TO ENSURE THAT MAINTENANCE, CLEANING AND TESTING OF RESPIRATORY PROTECTIVE DEVICES ARE CARRIED OUT ACCORDING TO THE INSTRUCTIONS OF THE PRODUCER. THESE MEASURES HAVE TO BE PROPERLY DOCUMENTED. REQUIRED WHEN DUSTS ARE GENERATED.
OUR RECOMMENDATIONS ON FILTERING RESPIRATORY PROTECTION ARE BASED ON THE FOLLOWING STANDARDS: DIN EN 143, DIN 14387 AND OTHER ACCOMPANYING STANDARDS RELATING TO THE USED RESPIRATORY PROTECTION SYSTEM.

CONTROL OF ENVIRONMENTAL EXPOSURE

DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	White crystals
ODOUR	ODORLESS
ODOUR THRESHOLD	NOT APPLICABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	37 - 38 °C (approx.)
INITIAL BOILING POINT AND BOILING RANGE	652 °C (Lit.)
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	THE PRODUCT IS NOT FLAMMABLE.
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	2.71 (Lit.)
WATER SOLUBILITY	1,187 G/L AT 20 °C (68 °F) - SOLUBLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NOT APPLICABLE FOR INORGANIC SUBSTANCES
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE
OTHER SAFETY INFORMATION	NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	THE PRODUCT IS CHEMICALLY STABLE UNDER STANDARD AMBIENT CONDITIONS (ROOM TEMPERATURE).

**POSSIBILITY OF
HAZARDOUS
REACTIONS**

VIOLENT REACTIONS POSSIBLE WITH:
STRONG ACIDS
HYDROGEN PEROXIDE

RISK OF IGNITION OR FORMATION OF INFLAMMABLE
GASES OR VAPOURS WITH:
HALOGEN-HALOGEN COMPOUNDS
ETHYLENE OXIDE
CARBIDES

RISK OF EXPLOSION WITH:
HYDRAZINE AND DERIVATIVES
NITRATES
ALKALI METALS
STRONG OXIDIZING AGENTS

CONDITIONS TO AVOID

EXPOSURE TO MOISTURE MAY AFFECT PRODUCT
QUALITY. EXPOSURE TO AIR MAY AFFECT PRODUCT
QUALITY.

**INCOMPATIBLE
MATERIALS**

NO DATA AVAILABLE

**HAZARDOUS
DECOMPOSITION
PRODUCTS**

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY

LD50 ORAL - RAT - MALE - 1,910 MG/KG
(OECD TEST GUIDELINE 423)
REMARKS: (ANHYDROUS SUBSTANCE)

LC50 INHALATION - RAT - MALE AND FEMALE - 4 H - 2
MG/L - DUST/MIST
(OECD TEST GUIDELINE 436)
REMARKS: (ANHYDROUS SUBSTANCE)

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

**SKIN
CORROSION/IRRITATION**

SKIN RABBIT
RESULT: CORROSIVE - 4 H
(OECD TEST GUIDELINE 404)
REMARKS: (ANHYDROUS SUBSTANCE)

**SERIOUS EYE
DAMAGE/EYE IRRITATION**

REMARKS: CAUSES SERIOUS EYE DAMAGE.

**RESPIRATORY OR SKIN
SENSITISATION**

PATCH TEST: - HUMAN
RESULT: POSITIVE
REMARKS: (ECHA)
(ANHYDROUS SUBSTANCE)

**GERM CELL
MUTAGENICITY**

TEST TYPE: IN VITRO MAMMALIAN CELL GENE
MUTATION TEST
TEST SYSTEM: MOUSE LYMPHOMA TEST
METABOLIC ACTIVATION: WITH AND WITHOUT
METABOLIC ACTIVATION
METHOD: OECD TEST GUIDELINE 476
RESULT: NEGATIVE
REMARKS: (ANHYDROUS SUBSTANCE)

TEST TYPE: MUTAGENICITY (MAMMAL CELL TEST):
MICRONUCLEUS.
SPECIES: MOUSE
APPLICATION ROUTE: INTRAPERITONEAL INJECTION
RESULT: NEGATIVE
REMARKS: (NATIONAL TOXICOLOGY PROGRAM)
(ANHYDROUS SUBSTANCE)

CARCINOGENICITY

IARC:

NO INGREDIENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS PROBABLE, POSSIBLE OR
CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP:

NO INGREDIENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS A KNOWN OR ANTICIPATED
CARCINOGEN BY NTP.

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON
OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY

NO DATA AVAILABLE

**SPECIFIC TARGET ORGAN
TOXICITY - SINGLE
EXPOSURE**

MAY CAUSE RESPIRATORY IRRITATION.

**SPECIFIC TARGET ORGAN
TOXICITY - REPEATED
EXPOSURE**

ORAL - MAY CAUSE DAMAGE TO ORGANS THROUGH
PROLONGED OR REPEATED EXPOSURE. - CARDIO-
VASCULAR SYSTEM

ASPIRATION HAZARD

NO DATA AVAILABLE

**ADDITIONAL
INFORMATION**

RTECS: XP8850000

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL,
PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE
NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	
TOXICITY TO FISH	STATIC TEST LC50 - OTHER FISH - 10.19 MG/L - 96 H REMARKS: THE VALUE IS GIVEN IN ANALOGY TO THE FOLLOWING SUBSTANCES: TIN(II) CHLORIDE
TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES	EC50 - DAPHNIA - 22 - 55 MG/L - 48 H REMARKS: (ECHA) THE VALUE IS GIVEN IN ANALOGY TO THE FOLLOWING SUBSTANCES: TIN(II) CHLORIDE
TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES(CHRONIC TOXICITY)	STATIC TEST NOEC - DAPHNIA MAGNA (WATER FLEA) - 0.18 MG/L - 21 D (OECD TEST GUIDELINE 211) REMARKS: THE VALUE IS GIVEN IN ANALOGY TO THE FOLLOWING SUBSTANCES: TIN(II) CHLORIDE
PERSISTENCE AND DEGRADABILITY	THE METHODS FOR DETERMINING THE BIOLOGICAL DEGRADABILITY ARE NOT APPLICABLE TO INORGANIC SUBSTANCES.
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	HARMFUL EFFECT DUE TO PH SHIFT. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH THE NATIONAL AND LOCAL REGULATIONS. LEAVE CHEMICALS IN ORIGINAL CONTAINERS. NO MIXING WITH OTHER WASTE. HANDLE UNCLEANED CONTAINERS LIKE THE PRODUCT ITSELF.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.
(Stannous chloride dihydrate)
UN NUMBER: 3260
CLASS: 8
PACKING GROUP: II
REPORTABLE QUANTITY
(RQ):
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.
(Stannous chloride dihydrate)
UN NUMBER: 3260
CLASS: 8
PACKING GROUP: II
EMS-NO: F-A, S-B

IATA

PROPER SHIPPING NAME: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.
(Stannous chloride dihydrate)
UN NUMBER: 3260
CLASS: 8
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 302 EHS TPQ.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Stannous chloride dihydrate	10025-69-1	4/24/1993

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H290	MAY BE CORROSIVE TO METALS.
H302 + H332	HARMFUL IF SWALLOWED OR IF INHALED.
H314	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H317	MAY CAUSE AN ALLERGIC SKIN REACTION.
H335	MAY CAUSE RESPIRATORY IRRITATION.
H373	MAY CAUSE DAMAGE TO ORGANS (CARDIO-VASCULAR SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE IF SWALLOWED.
H412	HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION: 3.2.

REVISION DATE: 4/10/2024