# Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

# SAFETY DATA SHEET

# SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 02006

NAME: Pyridine, super dry

SYNONYMS:

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

# SECTION 2. HAZARDS IDENTIFICATION

### CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

FLAMMABLE LIQUIDS (CATEGORY 2), H225 ACUTE TOXICITY, ORAL (CATEGORY 4), H302 ACUTE TOXICITY, INHALATION (CATEGORY 4), H332 ACUTE TOXICITY, DERMAL (CATEGORY 4), H312 SKIN IRRITATION (CATEGORY 2), H315

# EYE IRRITATION (CATEGORY 2A), H319 ACUTE AOUATIC TOXICITY (CATEGORY 3), H402

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

# GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD DANGER

HAZARD	STATEMENT	(S)
--------	-----------	-----

H225	HIGHLY FLAMMABLE LIC	DUID AND VAPOUR

H302 + H312 + H332	HARMFUL IF SWALLOWED	. IN CONTACT WITH SKIN OR IF
11302 11312 11332	III II CE II S WILLES WED	, in a continue i will be been one in

INHALED

H315 CAUSES SKIN IRRITATION.

H319 CAUSES SERIOUS EYE IRRITATION. H402 HARMFUL TO AQUATIC LIFE.

PRECAUTIONARY STATEMENT(S)

P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT

SURFACES. - NO SMOKING.

P233 KEEP CONTAINER TIGHTLY CLOSED.

P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.

P241 USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/

LIGHTING/ EQUIPMENT.

P242 USE ONLY NON-SPARKING TOOLS.

P243 TAKE PRECAUTIONARY MEASURES AGAINST STATIC

DISCHARGE.

P261 AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/

SPRAY.

P264 WASH SKIN THOROUGHLY AFTER HANDLING.

P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS

PRODUCT.

P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P273 AVOID RELEASE TO THE ENVIRONMENT.

P280 WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE

PROTECTION.

P301 + P312 + P330 IF SWALLOWED: CALL A POISON CENTER OR DOCTOR/

PHYSICIAN IF YOU FEEL UNWELL. RINSE MOUTH.

P303 + P361 + P353 IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY

ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/

SHOWER.

P304 + P340 + P312 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT

REST IN A POSITION COMFORTABLE FOR BREATHING. CALL A POISON CENTER OR DOCTOR/ PHYSICIAN IF YOU FEEL

UNWELL.

P305 + P351 + P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING.

P332 + P313 IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/

ATTENTION

P337 + P313 IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/

ATTENTION.

P362 TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE

REUSE.

**NONE** 

P370 + P378IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR

ALCOHOL-RESISTANT FOAM FOR EXTINCTION.

STORE IN A WELL-VENTILATED PLACE. KEEP COOL. P403 + P235P501

DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT **OTHERWISE** 

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:  $C_6H_5N$ 

MW: 79.1

CAS-NO. 110-86-1

**PURITY**:  $\geq$  99.5% (GC)

### **HAZARDOUS COMPONENTS**

COMPONENT	CLASSIFICATION	CONCENTRATION
PYRIDINE		
	FLAM. LIQ. 2; ACUTE TOX. 4; SKIN IRRIT. 2; EYE IRRIT. 2A; AQUATIC ACUTE 3; H225, H302 + H312 + H332, H315, H319, H402	<= 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

# **SECTION 4. FIRST-AID MEASURES**

# **DESCRIPTION OF FIRST AID MEASURES**

**GENERAL ADVICE** CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN **CONTACT** 

WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

**CONTACT** 

LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

IF SWALLOWED

DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

**MOST IMPORTANT** SYMPTOMS AND

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

**EFFECTS, BOTH ACUTE** 

SECTION 2.2) AND/OR IN SECTION 11

AND DELAYED

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT **NEEDED** 

NO DATA AVAILABLE

### SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

**SUITABLE** USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY

**EXTINGUISHING MEDIA** CHEMICAL OR CARBON DIOXIDE.

SPECIAL HAZARDS ARISING FROM THE CARBON OXIDES, NITROGEN OXIDES (NOX)

SUBSTANCE OR MIXTURE

WEAR SELF-CONTAINED BREATHING APPARATUS FOR ADVICE FOR

**FIREFIGHTERS** FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, **PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES** 

USE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN

ACCUMULATE IN LOW AREAS.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET-BRUSHING AND PLACE IN CONTAINER FOR

DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE

SECTION 13).

REFERENCE TO OTHER SECTIONS

FOR DISPOSAL SEE SECTION 13.

### SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

PRECAUTIONS FOR SAFE AVOID CONTACT WITH SKIN AND EYES. AVOID

INHALATION OF VAPOUR OR MIST.

USE EXPLOSION-PROOF EQUIPMENT.KEEP AWAY FROM

SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF

ELECTROSTATIC CHARGE.

FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT

UPRIGHT TO PREVENT LEAKAGE.

HANDLE AND STORE UNDER INERT GAS.

STORAGE CLASS (TRGS 510): FLAMMABLE LIQUIDS

**SPECIFIC END USE(S)** 

APART FROM THE USES MENTIONED IN SECTION 1.2

NO OTHER SPECIFIC USES ARE STIPULATED

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# CONTROL PARAMETERS COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS
			PARAMETERS	
PYRIDINE	110-86-1	TWA	1.000000 PPM	USA. WORKPLACE ENVIRONMENTAL
				EXPOSURE LEVELS (WEEL)

REMARKS	LIVER DAMAGE KIDNEY DAMAGE SKIN IRRITATION CONFIRMED ANIMAL CARCINOGEN WITH UNKNOWN RELEVANCE TO HUMANS		
			USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		15.000000	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z- 1 LIMITS FOR AIR CONTAMINANTS
	THE VALUE IN MG/M3 IS APPROXIMATE.		

#### **EXPOSURE CONTROLS**

APPROPRIATEHANDLE IN ACCORDANCE WITH GOOD INDUSTRIALENGINEERINGHYGIENE AND SAFETY PRACTICE. WASH HANDSCONTROLSBEFORE BREAKS AND AT THE END OF WORKDAY.

# PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT

FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR EN 166(EU).

**SKIN PROTECTION** HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED

PRIOR TO USE. USE PROPER GLOVE REMOVAL

TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER

SURFACE) TO AVOID SKIN CONTACT WITH THIS

PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY

HANDS.

SPLASH CONTACT

MATERIAL: BUTYL-RUBBER

MINIMUM LAYER THICKNESS: 0.3 MM

BREAK THROUGH TIME: 219 MIN

MATERIAL TESTED:BUTOJECT (KCL 897, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD

NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR

ANY SPECIFIC USE SCENARIO.

**BODY PROTECTION** COMPLETE SUIT PROTECTING AGAINST CHEMICALS,

FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING., THE TYPE OF PROTECTIVE EQUIPMENT

MUST BE SELECTED ACCORDING TO THE

CONCENTRATION AND AMOUNT OF THE DANGEROUS

SUBSTANCE AT THE SPECIFIC WORKPLACE.

**RESPIRATORY** WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING **PROTECTION** RESPIRATORS ARE APPROPRIATE USE A FULL-FACE

RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTI- PURPOSE COMBINATION

(US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING

CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR

CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO

DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

# INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Colorless liquid ODOUR UNPLEASANT

ODOUR THRESHOLD NO DATA AVAILABLE
PH 8.5 AT 15.82 G/L AT 25 C

MELTING -42 °C

POINT/FREEZING POINT

INITIAL BOILING POINT 116 °C (Approx.)

AND BOILING RANGE

FLASH POINT 17°C

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER UPPER EXPLOSION LIMIT: 12.4 %(V) FLAMMABILITY OR LOWER EXPLOSION LIMIT: 1.8 %(V)

EXPLOSIVE LIMITS

VAPOUR PRESSURE 13.3 HPA (10.0 MMHG) AT 13.2 C, 26.7 HPA (20.0 MMHG) AT

25.0 C

VAPOUR DENSITY NO DATA AVAILABLE RELATIVE DENSITY 0.978 g/mL at 25 °C

WATER SOLUBILITY SOLUBLE PARTITION COEFFICIENT: LOG POW: 0.65

N- OCTANOL/WATER

AUTO-IGNITION 482.0 C

**TEMPERATURE** 

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

### **SECTION 10. STABILITY AND REACTIVITY**

**REACTIVITY** NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

**CONDITIONS TO AVOID** HEAT, FLAMES AND SPARKS.

INCOMPATIBLE STRONG OXIDIZING AGENTS, STRONG ACIDS

**MATERIALS** 

HAZARDOUS OTHER DECOMPOSITION PRODUCTS - NO DATA

**DECOMPOSITION** AVAILABLE

**PRODUCTS** IN THE EVENT OF FIRE: SEE SECTION 5

### SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

**ACUTE TOXICITY** 

LD50 ORAL - RAT - 891.0 MG/KG

REMARKS: SENSE ORGANS AND SPECIAL SENSES

(NOSE, EYE, EAR, AND TASTE):EYE:PTOSIS.

BEHAVIORAL:SOMNOLENCE(GENERAL DEPRESSED

ACTIVITY). BEHAVIORAL:COMA.

LC50 INHALATION - RAT - 1 H - 28,500 MG/M3 REMARKS: SENSE ORGANS AND SPECIAL SENSES (NOSE, EYE, EAR, AND TASTE):EYE:LACRIMATION. BEHAVIORAL:SOMNOLENCE (GENERAL DEPRESSED

ACTIVITY). LUNGS, THORAX, OR

RESPIRATION: DYSPNEA.

LD50 DERMAL - RABBIT - 1,121 MG/KG REMARKS: BEHAVIORAL: ATAXIA.

GASTROINTESTINAL: CHANGES IN STRUCTURE OR FUNCTION OF SALIVARY GLANDS. LIVER: OTHER

CHANGES.

**SKIN** 

**CORROSION/IRRITATION** 

SKIN - RABBIT

RESULT: MILD SKIN IRRITATION - 24 H

(DRAIZE TEST)

**SERIOUS EYE** 

DAMAGE/EYE IRRITATION

NO DATA AVAILABLE

**RESPIRATORY OR SKIN** 

**SENSITISATION** 

NO DATA AVAILABLE

GERM CELL **MUTAGENICITY**  NO DATA AVAILABLE

**CARCINOGENICITY** 

IARC:

3 - GROUP 3: NOT CLASSIFIABLE AS TO ITS CARCINOGENICITY TO HUMANS (PYRIDINE)

NTP:

NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS

IDENTIFIED AS A CARCINOGEN OR POTENTIAL

CARCINOGEN BY OSHA.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

**TOXICITY - SINGLE** 

**EXPOSURE** 

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN **TOXICITY - REPEATED** 

**EXPOSURE** 

NO DATA AVAILABLE

**ASPIRATION HAZARD** NO DATA AVAILABLE

ADDITIONAL RTECS: UR8400000

**INFORMATION** BURNING SENSATION, COUGH, WHEEZING,

LARYNGITIS, SHORTNESS OF BREATH, HEADACHE, NAUSEA, VOMITING, DIZZINESS, TACHYCARDIA, NERVOUSNESS, INSOMNIA, SKIN DISORDERS, LOSS OF

**APPETITE** 

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE

NOT BEEN THOROUGHLY INVESTIGATED.

# SECTION 12. ECOLOGICAL INFORMATION

**TOXICITY** 

TOXICITY TO FISH LC50 - PIMEPHALES PROMELAS (FATHEAD MINNOW)

- 93.80 MG/L - 96 H

LC50 - CYPRINUS CARPIO (CARP) - 26.00 MG/L - 96 H

TOXICITY TO DAPHNIA AND

OTHER AQUATIC INVERTEBRATES

EC50 - DAPHNIA MAGNA (WATER FLEA) - 940.00 MG/L

- 48 H

EC50 - DAPHNIA MAGNA (WATER FLEA) - 1,140.00

MG/L - 48 H

EC50 - DAPHNIA PULEX (WATER FLEA) - 520.00 MG/L -

48 H

TOXICITY TO ALGAE EC50 - SELENASTRUM - 100.00 - 180.00 MG/L - 72 H

PERSISTENCE AND DEGRADABILITY

BIODEGRADABILITY

RESULT: 97 % - READILY BIODEGRADABLE

BIOACCUMULATIVE

**POTENTIAL** 

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS AN ENVIRONMENTAL HAZARD CANNOT BE

EXCLUDED IN THE EVENT OF UNPROFESSIONAL

HANDLING OR DISPOSAL. HARMFUL TO AQUATIC LIFE.

### SECTION 13. DISPOSAL CONSIDERATIONS

### WASTE TREATMENT METHODS

PRODUCT BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH

AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA

CARE IN IGNITING AS THIS MATERIAL IS HIGHLY

FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE

SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

# **SECTION 14.** TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: PYRIDINE

UN NUMBER: 1282 CLASS: 3 PACKING GROUP: II

REPORTABLE QUANTITY 1000 LBS

(RQ):

POISON INHALATION NO

HAZARD:

**IMDG** 

PROPER SHIPPING NAME: PYRIDINE

UN NUMBER: 1282 CLASS: 3 PACKING GROUP: II

EMS-NO: F-E, S-D

**IATA** 

PROPER SHIPPING NAME: PYRIDINE

UN NUMBER: 1282 CLASS: 3 PACKING GROUP: II

### SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THE FOLLOWING COMPONENTS ARE SUBJECT TO

REPORTING LEVELS ESTABLISHED BY SARA TITLE III,

SECTION 313:

CAS-NO. REVISION DATE

Pyridine, super dry 110-86-1 7/1/2007

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Pyridine, super dry 110-86-1 7/1/2007

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Pyridine, super dry 110-86-1 7/1/2007

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Pyridine, super dry 110-86-1 7/1/2007

CALIFORNIA PROP. 65 COMPONENTS WARNING! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE

CANCER.

CAS-NO. REVISION DATE

Pyridine, super dry 110-86-1 9/28/2007

# **SECTION 16. OTHER INFORMATION**

# FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

ACUTE TOX. ACUTE TOXICITY

AQUATIC ACUTE ACUTE AQUATIC TOXICITY

EYE IRRIT. EYE IRRITATION

FLAM. LIQ. FLAMMABLE LIQUIDS

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.

H302 HARMFUL IF SWALLOWED.

H302 + H312 + H332 HARMFUL IF SWALLOWED, IN CONTACT WITH SKIN OR

IF INHALED

H312 HARMFUL IN CONTACT WITH SKIN.

H315 CAUSES SKIN IRRITATION.

**HMIS RATING** 

HEALTH HAZARD: 2

CHRONIC HEALTH

HAZARD:

FLAMMABILITY: 3 PHYSICAL HAZARD 0

NFPA RATING

HEALTH HAZARD: 2

FIRE HAZARD: 3
REACTIVITY HAZARD: 0

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

**HYGINISTS** 

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.