Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 22274

NAME: *N,N'*-Dimethylethylenediamine

SYNONYMS: 1,2-Bis(methylamino)ethane

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE LIQUIDS (CATEGORY 3), H226

SKIN CORROSION (CATEGORY 1B), H314 SERIOUS EYE DAMAGE (CATEGORY 1), H318 FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

DANGER SIGNAL WORD

HAZARD STATEMENT(S)

H226 FLAMMABLE LIQUID AND VAPOUR.

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

PRECAUTIONAL	RY STATEMENT(S)
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT
	SURFACES NO SMOKING.
P233	KEEP CONTAINER TIGHTLY CLOSED.
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/
	LIGHTING EQUIPMENT.
P242	USE ONLY NON-SPARKING TOOLS.
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC
	DISCHARGE.
P264	WASH SKIN THOROUGHLY AFTER HANDLING.
P280	WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE

WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE P280

PROTECTION/ FACE PROTECTION.

P301 + P330 + P331IF SWALLOWED: RINSE MOUTH, DO NOT INDUCE

VOMITING.

P303 + P361 + P353IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY

ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/

SHOWER.

P304 + P340 + P310IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT

> REST IN A POSITION COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A POISON CENTER OR DOCTOR/

PHYSICIAN.

P305 + P351 + P338 + F IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

P310 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A

POISON CENTER/DOCTOR.

P363 WASH CONTAMINATED CLOTHING BEFORE REUSE. IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR P370 + P378

ALCOHOL-RESISTANT FOAM TO EXTINGUISH.

P403 + P235STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT NONE

OTHERWISE

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: $C_4H_{12}N_2$

MW: 88.15

CAS-NO. 110-70-3

PURITY: $\geq 97\%$ (GC)

COMPONENT	CLASSIFICATION	CONCENTRATION				
<i>N,N'</i> -Dimethylethylenediamine						
	FLAM. LIQ. 3; SKIN CORR. 1B;	<= 100 %				
	EYE DAM. 1; H226, H314, H318					

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

CONTACT

TAKE OFF CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH OFF WITH SOAP AND PLENTY OF

WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE

CONTACT

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A

PHYSICIAN.CONTINUE RINSING EYES DURING

TRANSPORT TO HOSPITAL.

IF SWALLOWED DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING

BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND

EFFECTS, BOTH ACUTE

AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE SUITABLE EXTINGUISHING MEDIA

EXTINGUISHING MEDIA DRY POWDER DRY SAND

UNSUITABLE EXTINGUISHING MEDIA

DO NOT USE WATER JET.

SPECIAL HAZARDS ARISING FROM THE

SUBSTANCE OR MIXTURE

CARBON OXIDES COMBUSTIBLE.

ADVICE FOR WEAR SELF CONTAINED BREATHING APPARATUS FOR

FIREFIGHTERS FIRE FIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES USE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN

ACCUMULATE IN LOW AREAS.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP CONTAIN SPILLAGE, AND THEN COLLECT WITH NON-COMBUSTIBLE ABSORBENT MATERIAL, (E.G. SAND, EARTH, DIATOMACEOUS EARTH, VERMICULITE) AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL / NATIONAL REGULATIONS (SEE SECTION 13).

SECTION 7. HANDLING AND STORAGE

HANDLING

PRECAUTIONS FOR SAFE AVOID INHALATION OF VAPOUR OR MIST.

KEEP AWAY FROM SOURCES OF IGNITION - NO

SMOKING. TAKE MEASURES TO PREVENT THE BUILD

UP OF ELECTROSTATIC CHARGE. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT

UPRIGHT TO PREVENT LEAKAGE.

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2

NO OTHER SPECIFIC USES ARE STIPULATED.

EXPOSURE CONTROLS/PERSONAL PROTECTION SECTION 8.

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

TIGHTLY FITTING SAFETY GOGGLES. FACESHIELD (8-INCH MINIMUM). USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 30 MIN

MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Colorless clear liquid
ODOUR NO DATA AVAILABLE
ODOUR THRESHOLD NO DATA AVAILABLE
PH NO DATA AVAILABLE

MELTING

POINT/FREEZING POINT

INITIAL BOILING POINT 141 - 145 °C (Lit.)

AND BOILING RANGE

FLASH POINT 26 °C

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY 0.82 g/mL (Lit.)

WATER SOLUBILITY NO DATA AVAILABLE PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION NO DATA AVAILABLE

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

CONDITIONS TO AVOID HEAT, FLAMES AND SPARKS.

INCOMPATIBLE ACIDS, ACID CHLORIDES, ACID ANHYDRIDES, STRONG

MATERIALS OXIDIZING AGENTS, CARBON DIOXIDE (CO2)

HAZARDOUS DECOMPOSITION PRODUCTS HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - CARBON OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA

AVAILABLE

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY NO DATA AVAILABLE

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

LD50 INTRAPERITONEAL - MOUSE - 200 MG/KG

SKIN NO DATA AVAILABLE

CORROSION/IRRITATION

SERIOUS EYE CAUSES SERIOUS EYE DAMAGE.

DAMAGE/EYE IRRITATION

RESPIRATORY OR SKIN NO DATA AVAILABLE SENSITISATION

GERM CELL NO DATA AVAILABLE **MUTAGENICITY**

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE

EXPOSURE

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - REPEATED

EXPOSURE

NO DATA AVAILABLE

ASPIRATION HAZARD

NO DATA AVAILABLE

ADDITIONAL INFORMATION

RTECS: KV4250000

MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE

OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN., COUGH, SHORTNESS OF BREATH, HEADACHE, NAUSEA

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE

NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL

NO DATA AVAILABLE

RESULTS OF PBT AND

VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT

DECLUDED MOT COMPLICATED

REQUIRED/NOT CONDUCTED.

OTHER ADVERSE

EFFECTS

NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS

TO A LICENSED DISPOSAL COMPANY. BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS

MATERIAL.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: POLYAMINES, LIQUID, CORROSIVE, FLAMMABLE,

N.O.S. (*N*,*N*'-Dimethylethylenediamine)

UN NUMBER: 2734 CLASS: 8 (3) PACKING GROUP: II

REPORTABLE QUANTITY

(RQ):

POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: POLYAMINES, LIQUID, CORROSIVE, FLAMMABLE,

N.O.S. (*N*,*N*'-Dimethylethylenediamine)

UN NUMBER: 2734
CLASS: 8 (3)
PACKING GROUP: II
EMS-NO: F-E, S-C

IATA

PROPER SHIPPING NAME: POLYAMINES, LIQUID, CORROSIVE, FLAMMABLE,

N.O.S. (*N*,*N*'-Dimethylethylenediamine)

UN NUMBER: 2734 CLASS: 8 (3) PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL

COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS FIRE HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

N,N'-Dimethylenediamine 110-70-3

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

N,N'-Dimethylethylenediamine 110-70-3

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H226 FLAMMABLE LIQUID AND VAPOUR.

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL

INDUSTRIAL HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER

OSHA: OCCUPATIONAL SAFETY AND HEALTH

ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.1 REVISION DATE: 01/27/2017