

Chem-Impex International Inc.

Tel: (630) 766-2112

E-mail: sales@chemimpex.com

Shipping and Correspondence:

935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218

Web site: www.chemimpex.com

Manufacturing site:

825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	24551
NAME:	Sodium bis(trimethylsilyl)amide solution, 1.0 M in THF
SYNONYMS:	Hexamethyldisilazane sodium salt solution, 1.0 M in THF
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

FLAMMABLE LIQUIDS (CATEGORY 2), H225

SKIN CORROSION (CATEGORY 1B), H314

SERIOUS EYE DAMAGE (CATEGORY 1), H318

REPRODUCTIVE TOXICITY (CATEGORY 2), H361

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), CENTRAL
NERVOUS SYSTEM, H336

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (CATEGORY 2), CENTRAL NERVOUS SYSTEM, H373
ASPIRATION HAZARD (CATEGORY 1), H304
SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 2), H401
LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 3), H412

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H336 MAY CAUSE DROWSINESS OR DIZZINESS.
H361 SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.
H373 MAY CAUSE DAMAGE TO ORGANS (CENTRAL NERVOUS SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE.
H401 TOXIC TO AQUATIC LIFE.
H412 HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT(S)

P201 OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.
P202 DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.
P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.
P233 KEEP CONTAINER TIGHTLY CLOSED.
P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241 USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/ LIGHTING/ EQUIPMENT.
P242 USE ONLY NON-SPARKING TOOLS.
P243 TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.
P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P273 AVOID RELEASE TO THE ENVIRONMENT.
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.
P301 + P310 IF SWALLOWED: IMMEDIATELY CALL A POISON CENTER/DOCTOR.
P301 + P330 + P331 IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING.
P303 + P361 + P353 IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER.
P304 + P340 + P310 IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A POISON CENTER/DOCTOR.

P305 + P351 + P338 + P310 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A POISON CENTER/DOCTOR.

P308 + P313 IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ ATTENTION.

P363 WASH CONTAMINATED CLOTHING BEFORE REUSE.

P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM TO EXTINCTION.

P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P403 + P235 STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS REACTS VIOLENTLY WITH WATER.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: $C_6H_{18}NNaSi_2$

MW: 183.38

CAS-NO. 1070-89-9

PURITY:

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
TOLUENE		
	FLAM. LIQ. 2; SKIN IRRIT. 2; REPR. 2; STOT SE 3; STOT RE 2; ASP. TOX. 1; AQUATIC ACUTE 2; AQUATIC CHRONIC 3; H225, H315, H361, H336, H373, H304, H401, H412 CONCENTRATION LIMITS: 20 %: STOT SE 3, H336;	>= 70 - < 90 %
1,1,1,3,3,3-HEXAMETHYLDISILAZANE, SODIUM SALT		
	ACUTE TOX. 4; SKIN CORR. 1B; EYE DAM. 1; AQUATIC CHRONIC 3; H302, H332, H312, H314, H318, H412	>= 10 - < 20 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	FIRST AIDER NEEDS TO PROTECT HIMSELF. SHOW THIS MATERIAL SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.
IF INHALED	AFTER INHALATION: FRESH AIR. CALL IN PHYSICIAN.
IN CASE OF SKIN CONTACT	IN CASE OF SKIN CONTACT: TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER. CALL A PHYSICIAN IMMEDIATELY.
IN CASE OF EYE CONTACT	AFTER EYE CONTACT: RINSE OUT WITH PLENTY OF WATER. CALL IN OPHTHALMOLOGIST. REMOVE CONTACT LENSES.
IF SWALLOWED	AFTER SWALLOWING: MAKE VICTIM DRINK WATER (TWO GLASSES AT MOST), AVOID VOMITING (RISK OF PERFORATION). PULMONARY FAILURE POSSIBLE AFTER ASPIRATION OF VOMIT. CALL A PHYSICIAN IMMEDIATELY. DO NOT ATTEMPT TO NEUTRALISE.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11.
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	SUITABLE EXTINGUISHING MEDIA CARBON DIOXIDE (CO ₂) DRY POWDER
	UNSUITABLE EXTINGUISHING MEDIA WATER FOAM

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	CARBON OXIDES COMBUSTIBLE. PAY ATTENTION TO FLASHBACK. VAPORS ARE HEAVIER THAN AIR AND MAY SPREAD ALONG FLOORS. MAY NOT GET IN TOUCH WITH: WATER DEVELOPMENT OF HAZARDOUS COMBUSTION GASES OR VAPOURS POSSIBLE IN THE EVENT OF FIRE. FORMS EXPLOSIVE MIXTURES WITH AIR AT AMBIENT TEMPERATURES.
ADVICE FOR FIREFIGHTERS	STAY IN DANGER AREA ONLY WITH SELF-CONTAINED BREATHING APPARATUS. PREVENT SKIN CONTACT BY KEEPING A SAFE DISTANCE OR BY WEARING SUITABLE PROTECTIVE CLOTHING.
FURTHER INFORMATION	REMOVE CONTAINER FROM DANGER ZONE AND COOL WITH WATER. SUPPRESS (KNOCK DOWN) GASES/VAPORS/MISTS WITH A WATER SPRAY JET. PREVENT FIRE EXTINGUISHING WATER FROM CONTAMINATING SURFACE WATER OR THE GROUND WATER SYSTEM.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	ADVICE FOR NON-EMERGENCY PERSONNEL: DO NOT BREATHE VAPORS, AEROSOLS. AVOID SUBSTANCE CONTACT. ENSURE ADEQUATE VENTILATION. KEEP AWAY FROM HEAT AND SOURCES OF IGNITION. EVACUATE THE DANGER AREA, OBSERVE EMERGENCY PROCEDURES, CONSULT AN EXPERT. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS	DO NOT LET PRODUCT ENTER DRAINS. RISK OF EXPLOSION.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	COVER DRAINS. COLLECT, BIND, AND PUMP OFF SPILLS. OBSERVE POSSIBLE MATERIAL RESTRICTIONS (SEE SECTIONS 7 AND 10). DISPOSE OF PROPERLY. CLEAN UP AFFECTED AREA.
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	<p>WORK UNDER HOOD. DO NOT INHALE SUBSTANCE/MIXTURE. AVOID GENERATION OF VAPOURS/AEROSOLS. KEEP WORKPLACE DRY. DO NOT ALLOW PRODUCT TO COME INTO CONTACT WITH WATER. KEEP AWAY FROM OPEN FLAMES, HOT SURFACES AND SOURCES OF IGNITION.TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE. FOR PRECAUTIONS SEE SECTION 2.2.</p>
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	<p>KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. KEEP AWAY FROM HEAT AND SOURCES OF IGNITION. NEVER ALLOW PRODUCT TO GET IN CONTACT WITH WATER DURING STORAGE. HANDLE AND STORE UNDER INERT GAS.</p> <p>Store at 0-8 °C</p>
SPECIFIC END USE(S)	<p>APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED.</p>

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
TOLUENE	108-88-3	TWA	100 PPM 375 MG/M3	USA. OSHA - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS - 1910.1000
		STEL	150 PPM 560 MG/M3	USA. OSHA - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS - 1910.1000
		TWA	200 PPM	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-2
	REMARKS	Z37.12-1967		
		CEIL	300 PPM	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-2
		Z37.12-1967		
		PEAK	500 PPM	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-2
		Z37.12-1967		
		TWA	20 PPM	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)

		VISUAL IMPAIRMENT FEMALE REPRODUCTIVE PREGNANCY LOSS 2019 ADOPTION SUBSTANCES FOR WHICH THERE IS A BIOLOGICAL EXPOSURE INDEX OR INDICES (SEE BEI SECTION) NOT CLASSIFIABLE AS A HUMAN CARCINOGEN		
		TWA	100 PPM 375 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		ST	150 PPM 560 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS

COMPONENT	CAS-NO.	PARAMETERS	VALUE	BIOLOGICAL SPECIMEN	BASIS
TOLUENE	108-88-3	TOLUENE	0.02 MG/L	IN BLOOD	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
	REMARKS	PRIOR TO LAST SHIFT OF WORKWEEK			
		TOLUENE	0.03 MG/L	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
		END OF SHIFT (AS SOON AS POSSIBLE AFTER EXPOSURE CEASES)			
		O-CRESOL	0.3MG/G CREATININ E	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
		END OF SHIFT (AS SOON AS POSSIBLE AFTER EXPOSURE CEASES)			

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS IMMEDIATELY CHANGE CONTAMINATED CLOTHING. APPLY PREVENTIVE SKIN PROTECTION. WASH HANDS AND FACE AFTER WORKING WITH SUBSTANCE.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU). TIGHTLY FITTING SAFETY GOGGLES

SKIN PROTECTION	<p>HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.</p> <p>SPLASH CONTACT MATERIAL: FLUORINATED RUBBER MINIMUM LAYER THICKNESS: 0.7 MM BREAK THROUGH TIME: 30 MIN MATERIAL TESTED: VITOJECT (KCL 890, SIZE M)</p> <p>IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE EC APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.</p>
BODY PROTECTION	FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING.
RESPIRATORY PROTECTION	REQUIRED WHEN VAPOURS/AEROSOLS ARE GENERATED. OUR RECOMMENDATIONS ON FILTERING RESPIRATORY PROTECTION ARE BASED ON THE FOLLOWING STANDARDS: DIN EN 143, DIN 14387 AND OTHER ACCOMPANYING STANDARDS RELATING TO THE USED RESPIRATORY PROTECTION SYSTEM.
CONTROL OF ENVIRONMENTAL EXPOSURE	DO NOT LET PRODUCT ENTER DRAINS. RISK OF EXPLOSION.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Slightly yellow to yellowish liquid
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	
INITIAL BOILING POINT AND BOILING RANGE	
FLASH POINT	
EVAPOURATION RATE	NO DATA AVAILABLE

FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	0.89-0.91 g/mL
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR.
CHEMICAL STABILITY	SENSITIVE TO MOISTURE
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	WARMING. MOISTURE.
INCOMPATIBLE MATERIALS	STRONG OXIDIZING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS	OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - CARBON OXIDES IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	NO DATA AVAILABLE
	INHALATION: NO DATA AVAILABLE
	DERMAL: NO DATA AVAILABLE
	NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	MIXTURE CAUSES BURNS.
SERIOUS EYE DAMAGE/EYE IRRITATION	MIXTURE CAUSES SERIOUS EYE DAMAGE. RISK OF BLINDNESS!
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE
GERM CELL MUTAGENICITY	NO DATA AVAILABLE
CARCINOGENICITY	
IARC:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.
NTP:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.
OSHA:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.
REPRODUCTIVE TOXICITY	SUSPECTED OF DAMAGING THE UNBORN CHILD. SUSPECTED OF DAMAGING FERTILITY.
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	MIXTURE MAY CAUSE DROWSINESS OR DIZZINESS. ACUTE ORAL TOXICITY - IF INGESTED, SEVERE BURNS OF THE MOUTH AND THROAT, AS WELL AS A DANGER OF PERFORATION OF THE ESOPHAGUS AND THE STOMACH. ACUTE INHALATION TOXICITY - MUCOSAL IRRITATIONS, COUGH, SHORTNESS OF BREATH, POSSIBLE DAMAGES;, DAMAGE OF RESPIRATORY TRACT
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	MIXTURE MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. - CENTRAL NERVOUS SYSTEM
ASPIRATION HAZARD	ASPIRATION HAZARD, ASPIRATION MAY CAUSE PULMONARY EDEMA AND PNEUMONITIS.

**ADDITIONAL
INFORMATION**

RTECS: NOT AVAILABLE

MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN, SPASM, INFLAMMATION AND EDEMA OF THE LARYNX, SPASM, INFLAMMATION AND EDEMA OF THE BRONCHI, PNEUMONITIS, PULMONARY EDEMA, BURNING SENSATION, COUGH, WHEEZING, LARYNGITIS, SHORTNESS OF BREATH, HEADACHE, NAUSEA

OTHER DANGEROUS PROPERTIES CAN NOT BE EXCLUDED.

THIS SUBSTANCE SHOULD BE HANDLED WITH PARTICULAR CARE.

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE.

STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	NO DATA AVAILABLE
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED.
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH THE NATIONAL AND LOC NO MIXING WITH OTHER WASTE.

CONTAMINATED PACKAGING DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Sodium bis(trimethylsilyl)amide solution, 1.0 M in THF)
UN NUMBER: 2924
CLASS: 3 (8)
PACKING GROUP: II
REPORTABLE QUANTITY (RQ): 1144 LBS
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Sodium bis(trimethylsilyl)amide solution, 1.0 M in THF)
UN NUMBER: 2924
CLASS: 3 (8)
PACKING GROUP: II
EMS-NO: F-E, S-C

IATA

PROPER SHIPPING NAME: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Sodium bis(trimethylsilyl)amide solution, 1.0 M in THF)
UN NUMBER: 2924
CLASS: 3 (8)
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 302 EHS TPQ.

SARA 313 COMPONENTS

THE FOLLOWING COMPONENTS ARE SUBJECT TO REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:

	CAS-NO.	REVISION DATE
Sodium bis(trimethylsilyl)amide solution, 1.0 M in THF	1070-89-9	07-01-2007

SARA 311/312 HAZARDS FIRE HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H336 MAY CAUSE DROWSINESS OR DIZZINESS.
H361 SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.
H373 MAY CAUSE DAMAGE TO ORGANS (CENTRAL NERVOUS SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE.
H401 TOXIC TO AQUATIC LIFE.
H412 HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

MSDS LEGEND

MW: MOLECULAR WEIGHT
MF: MOLECULAR FORMULA
VOC: VOLATILE ORGANIC COMPOUNDS
ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION : 3.2

REVISION DATE : 07/01/2020