Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 27224

NAME: Hex-1-yne

SYNONYMS: 1-Hexyne

n-Butylacetylene

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE LIQUIDS (CATEGORY 2), H225

SKIN IRRITATION (CATEGORY 2), H315 EYE IRRITATION (CATEGORY 2A), H319 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), RESPIRATORY SYSTEM, H335
ASPIRATION HAZARD (CATEGORY 1), H304

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

፟����

SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.

H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

H315 CAUSES SKIN IRRITATION.

H319 CAUSES SERIOUS EYE IRRITATION. H335 MAY CAUSE RESPIRATORY IRRITATION.

PRECAUTIONARY STATEMENT(S)

P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT

SURFACES. - NO SMOKING.

P233 KEEP CONTAINER TIGHTLY CLOSED.

P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.

P241 USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/

LIGHTING/ EQUIPMENT.

P242 USE ONLY NON-SPARKING TOOLS.

P243 TAKE PRECAUTIONARY MEASURES AGAINST STATIC

DISCHARGE.

P261 AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/

SPRAY.

P264 WASH SKIN THOROUGHLY AFTER HANDLING.

P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE

PROTECTION/ FACE PROTECTION.

P301 + P310 IF SWALLOWED: IMMEDIATELY CALL A POISON CENTER OR

DOCTOR/ PHYSICIAN.

P303 + P361 + P353 IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY

ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/

SHOWER.

P304 + P340 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT

REST IN A POSITION COMFORTABLE FOR BREATHING.

P305 + P351 + P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING.

P312 CALL A POISON CENTER OR DOCTOR/ PHYSICIAN IF YOU

FEEL UNWELL.

P321 SPECIFIC TREATMENT (SEE SUPPLEMENTAL FIRST AID

INSTRUCTIONS ON THIS LABEL).

P331 DO NOT INDUCE VOMITING.

P332 + P313 IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/

ATTENTION.

P337 + P313 IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/

ATTENTION.

P362 TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE

REUSE.

NONE

P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR

ALCOHOL-RESISTANT FOAM FOR EXTINCTION.

P403 + P233 STORE IN A WELL-VENTILATED PLACE, KEEP CONTAINER

TIGHTLY CLOSED.

P403 + P235 STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT

OTHERWISE

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: C_6H_{10}

MW: 82.15

CAS-NO. 693-02-7

PURITY: \geq 98.5% (GLC)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
HEX-1-YNE		
	FLAM. LIQ. 2; SKIN IRRIT. 2	2; -
	EYE IRRIT. 2A; STOT SE 3; A	ASP.
	TOX. 1; H225, H304, H315, H	I319,
	H335	

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

CONTACT

WASH OFF WITH SOAP AND PLENTY OF WATER.

CONSULT A PHYSICIAN.

IN CASE OF EYE

CONTACT

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

IF SWALLOWED DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING

BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND

EFFECTS, BOTH ACUTE AND DELAYED THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA FOR SMALL (INCIPIENT) FIRES, USE MEDIA SUCH AS "ALCOHOL" FOAM, DRY CHEMICAL, OR CARBON DIOXIDE. FOR LARGE FIRES, APPLY WATER FROM AS FAR AS POSSIBLE. USE VERY LARGE QUANTITIES

FAR AS POSSIBLE. USE VERY LARGE QUANTITIES (FLOODING) OF WATER APPLIED AS A MIST OR SPRAY; SOLID STREAMS OF WATER MAY BE INEFFECTIVE. COOL ALL AFFECTED CONTAINERS WITH FLOODING

QUANTITIES OF WATER.

SPECIAL HAZARDS
ARISING FROM THE
SUBSTANCE OR MIXTURE

CARBON OXIDES

ADVICE FOR

FIREFIGHTERS

WEAR SELF CONTAINED BREATHING APPARATUS FOR

FIRE FIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES USE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN

ACCUMULATE IN LOW AREAS.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET-BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE

SECTION 13).

REFERENCE TO OTHER SECTIONS

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

AVOID CONTACT WITH SKIN AND EYES. AVOID

INHALATION OF VAPOUR OR MIST.

USE EXPLOSION-PROOF EQUIPMENT.KEEP AWAY FROM

SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF

ELECTROSTATIC CHARGE.

FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES STORE IN COOL PLACE. KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO

PREVENT LEAKAGE.

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: FLUORINATED RUBBER
MINIMUM LAYER THICKNESS: 0.7 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED WITCHEGT (V.C.) 800 SV

MATERIAL TESTED: VITOJECT (KCL 890, SIZE M)

SPLASH CONTACT

MATERIAL: BUTYL-RUBBER

MINIMUM LAYER THICKNESS: 0.3 MM

BREAK THROUGH TIME: 30 MIN

MATERIAL TESTED:BUTOJECT (KCL 897, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTI- PURPOSE COMBINATION

(US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING

CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF

PROTECTION, USE A FULL-FACE SUPPLIED AIR
RESPIRATOR. USE RESPIRATORS AND COMPONENTS
TESTED AND APPROVED UNDER APPROPRIATE
GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR

CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO

DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Colorless liquid

ODOUR NO DATA AVAILABLE
ODOUR THRESHOLD NO DATA AVAILABLE
PH NO DATA AVAILABLE

MELTING -132 °C

POINT/FREEZING POINT

INITIAL BOILING POINT 71-72 °C

AND BOILING RANGE

FLASH POINT -20 °C Closed cup EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE 337 HPA (253 MMHG) AT 37.7 C

VAPOUR DENSITY
RELATIVE DENSITY
WATER SOLUBILITY
PARTITION COEFFICIENT:
NO DATA AVAILABLE
NO DATA AVAILABLE
NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION NO DATA AVAILABLE

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

CONDITIONS TO AVOID HEAT, FLAMES AND SPARKS. EXTREMES OF

TEMPERATURE AND DIRECT SUNLIGHT.

INCOMPATIBLE MATERIALS OXIDIZING AGENTS

HAZARDOUS OTHER DECOMPOSITION PRODUCTS - NO DATA

DECOMPOSITION AVAILABLE

PRODUCTS IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY DERMAL: NO DATA AVAILABLE

LD50 INTRAPERITONEAL - MOUSE - > 100 MG/KG

SKIN NO DATA AVAILABLE

CORROSION/IRRITATION

SERIOUS EYE NO DATA AVAILABLE

DAMAGE/EYE IRRITATION

RESPIRATORY OR SKIN NO DATA AVAILABLE

SENSITISATION

GERM CELL NO DATA AVAILABLE

MUTAGENICITY

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

ACGIH: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL

CARCINOGEN BY ACGIH.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL

CARCINOGEN BY OSHA.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE

EXPOSURE

INHALATION - MAY CAUSE RESPIRATORY

IRRITATION.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EXPOSURE

NO DATA AVAILABLE

ASPIRATION HAZARD THE SUBSTANCE OR MIXTURE IS KNOWN TO CAUSE

HUMAN ASPIRATION TOXICITY HAZARDS OR HAS TO

BE REGARDED AS IF IT CAUSES A HUMAN

ASPIRATION TOXICITY HAZARD.

ADDITIONAL RTECS: MO9691000

INFORMATION TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL,

PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE

NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS

CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH

AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA

CARE IN IGNITING AS THIS MATERIAL IS HIGHLY

FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE

SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: HYDROCARBONS, LIQUID, N.O.S.

UN NUMBER: 3295
CLASS: 3
PACKING GROUP: II
MARINE POLLUTANT: NO
POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: HYDROCARBONS, LIQUID, N.O.S.

UN NUMBER: 3295
CLASS: 3
PACKING GROUP: II
EMS-NO: F-E, S-D
MARINE POLLUTANT: NO

IATA

PROPER SHIPPING NAME: HYDROCARBONS, LIQUID, N.O.S.

UN NUMBER: 3295 CLASS: 3 PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS SARA 302: NO CHEMICALS IN THIS MATERIAL ARE

SUBJECT TO THE REPORTING REQUIREMENTS OF SARA

TITLE III, SECTION 302.

SARA 313 COMPONENTS SARA 313: THIS MATERIAL DOES NOT CONTAIN ANY

CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS

THAT EXCEED THE THRESHOLD (DE MINIMIS)

REPORTING LEVELS ESTABLISHED BY SARA TITLE III,

SECTION 313.

SARA 311/312 HAZARDS FIRE HAZARD, ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT NO COMPONENTS ARE SUBJECT TO THE TO KNOW COMPONENTS MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. **REVISION DATE**

Hex-1-yne 693-02-7

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

693-02-7 Hex-1-yne

CALIFORNIA PROP. 65

THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS **COMPONENTS** KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER,

BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE

HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

ASPIRATION HAZARD ASP. TOX. EYE IRRIT. EYE IRRITATION

FLAMMABLE LIQUIDS FLAM. LIQ.

HIGHLY FLAMMABLE LIQUID AND VAPOUR. H225

H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CAUSES SKIN IRRITATION. H315

CAUSES SERIOUS EYE IRRITATION. H319 H335 MAY CAUSE RESPIRATORY IRRITATION.

SKIN IRRITATION SKIN IRRIT.

STOT SE SPECIFIC TARGET ORGAN TOXICITY - SINGLE

EXPOSURE

HMIS RATING

HEALTH HAZARD: 2

CHRONIC HEALTH

HAZARD:

FLAMMABILITY: 3 PHYSICAL HAZARD 0 NFPA RATING

HEALTH HAZARD: 2 FIRE HAZARD: 3 REACTIVITY HAZARD: 0

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.