Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 27575

NAME: Sodium *tert*-butoxide

SYNONYMS: Sodium tert-butyl alcohol

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) SELF-HEATING SUBSTANCES AND MIXTURES (CATEGORY 1), H251 SKIN CORROSION (CATEGORY 1B), H314

SERIOUS EYE DAMAGE (CATEGORY 1), H318

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H251 SELF-HEATING: MAY CATCH FIRE.

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

H318 CAUSES SERIOUS EYE DAMAGE.

PRECAUTIONARY STATEMENT(S)

P235 + P410 KEEP COOL. PROTECT FROM SUNLIGHT.

P260 DO NOT BREATHE DUST OR MIST.

P264 WASH SKIN THOROUGHLY AFTER HANDLING.

P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE

PROTECTION/ FACE PROTECTION.

P301 + P330 + P331 IF SWALLOWED: RINSE MOUTH, DO NOT INDUCE

VOMITING.

P303 + P361 + P353 IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY

ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/

SHOWER

P304 + P340 + P310 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT

REST IN A POSITION COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A POISON CENTER OR DOCTOR/

PHYSICIAN.

P305 + P351 + P338 + IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

P310 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A

POISON CENTER OR DOCTOR/PHYSICIAN.

P363 WASH CONTAMINATED CLOTHING BEFORE REUSE.

P405 STORE LOCKED UP.

P407 MAINTAIN AIR GAP BETWEEN STACKS/ PALLETS.

P420 STORE AWAY FROM OTHER MATERIALS.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT REACTS VIOLENTLY WITH WATER.

OTHERWISE

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

TELLOTS VIOLET WITH WHILE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: C_4H_9ONa

MW: 96.1

CAS-NO. 865-48-5

PURITY: $\geq 98\%$ (Assay)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
SODIUM 2-METHYLPROPAN-2-OLATE		
	SELF-HEAT. 1; SKIN CORR. 1B;	<= 100%
	EYE DAM. 1; H251, H314,	
	H251, H314, H318	

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

CONTACT

TAKE OFF CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH OFF WITH SOAP AND PLENTY OF

WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE

CONTACT

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A

PHYSICIAN.CONTINUE RINSING EYES DURING

TRANSPORT TO HOSPITAL.

IF SWALLOWED DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING

BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT

SYMPTOMS AND

EFFECTS, BOTH ACUTE

AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND

ATTENTION AND SPECIAL TREATMENT

NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE DRY POWDER

EXTINGUISHING MEDIA

SPECIAL HAZARDS CARBON OXIDES, SODIUM OXIDES

ARISING FROM THE SUBSTANCE OR MIXTURE

ADVICE FOR WEAR SELF-CONTAINED BREATHING APPARATUS FOR

FIREFIGHTERS FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL USE PERSONAL PROTECTIVE EQUIPMENT. AVOID PRECAUTIONS, DUST FORMATION. AVOID BREATHING VAPOURS, MIST

PRECAUTIONS,DUST FORMATION. AVOID BREATHING VAPOURS, MPROTECTIVEOR GAS. ENSURE ADEQUATE VENTILATION.EQUIPMENT ANDEVACUATE PERSONNEL TO SAFE AREAS. AVOID

EMERGENCY BREATHING DUST.

PROCEDURES FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE

PRECAUTIONS TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

METHODS ANDSWEEP UP AND SHOVEL. CONTAIN SPILLAGE, ANDMATERIALS FORTHEN COLLECT WITH AN ELECTRICALLY PROTECTEDCONTAINMENT ANDVACUUM CLEANER OR BY WET- BRUSHING AND

CLEANING UP PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO

LOCAL REGULATIONS (SEE SECTION 13). DO NOT FLUSH WITH WATER. KEEP IN SUITABLE, CLOSED

CONTAINERS FOR DISPOSAL.

REFERENCE TO OTHER FOR DISPOSAL SEE SECTION 13.

SECTIONS

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE AVOID FORMATION OF DUST AND AEROSOLS.FURTHER **HANDLING** PROCESSING OF SOLID MATERIALS MAY RESULT IN

THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE

ADDITIONAL PROCESSING OCCURS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED.KEEP AWAY FROM

SOURCES OF IGNITION - NO SMOKING. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. NEVER ALLOW PRODUCT TO GET IN CONTACT WITH WATER DURING STORAGE. KEEP IN A DRY PLACE. MOISTURE SENSITIVE. HANDLE AND STORE UNDER INERT GAS. KEEP IN A DRY PLACE. STORAGE CLASS (TRGS 510): PYROPHORIC AND SELF-HEATING HAZARDOUS MATERIALS

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL EXPOSURE LIMIT VALUES. **PARAMETERS**

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT
MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT
MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, FLAME RETARDANT PROTECTIVE CLOTHING, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Whtie to light yellow powder ODOUR NO DATA AVAILABLE ODOUR THRESHOLD NO DATA AVAILABLE PH NO DATA AVAILABLE

MELTING

POINT/FREEZING POINT INITIAL BOILING POINT AND BOILING RANGE

FLASH POINT

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER UPPER EXPLOSION LIMIT: 8 %(V)
FLAMMABILITY OR LOWER EXPLOSION LIMIT: 2.3 %(V)

EXPLOSIVE LIMITS

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY

WATER SOLUBILITY NO DATA AVAILABLE PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION THE SUBSTANCE OR MIXTURE IS CLASSIFIED AS SELF

TEMPERATURE HEATING WITH THE CATEGORY 1.

DECOMPOSITION 300 C

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF REACTS VIOLENTLY WITH WATER.
HAZARDOUS
REACTIONS

CONDITIONS TO AVOID EXPOSURE TO MOISTURE.

INCOMPATIBLE ACIDS, REDUCING AGENTS, OXYGEN, WATER, MATERIALS ALCOHOLS, CHLORINATED SOLVENTS, HALOGENS

HAZARDOUS OTHER DECOMPOSITION PRODUCTS - NO DATA

DECOMPOSITION AVAILABLE

PRODUCTS IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY DERMAL: NO DATA AVAILABLE

SKIN NO DATA AVAILABLE

CORROSION/IRRITATION

SERIOUS EYE NO DATA AVAILABLE

DAMAGE/EYE IRRITATION

RESPIRATORY OR SKIN SENSITISATION

NO DATA AVAILABLE

GERM CELL NO DATA AVAILABLE

MUTAGENICITY

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

ACGIH: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL

CARCINOGEN BY ACGIH.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL

CARCINOGEN BY OSHA.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE

EXPOSURE

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - REPEATED

EXPOSURE

NO DATA AVAILABLE

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL RTECS: NOT AVAILABLE

INFORMATION MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE

OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN., SPASM, INFLAMMATION AND EDEMA OF THE BRONCHI TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE

NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

 ${\tt PBT/VPVB} \ {\tt ASSESSMENT} \ {\tt NOT} \ {\tt AVAILABLE} \ {\tt AS}$

CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH

AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE

DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: ALKALI METAL ALCOHOLATES, SELF-HEATING,

CORROSIVE, N.O.S.(Sodium *tert*-butoxide)

UN NUMBER: 3206 CLASS: 4.2 (8) PACKING GROUP: II

REPORTABLE QUANTITY

(RQ):

POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: ALKALI METAL ALCOHOLATES, SELF-HEATING,

CORROSIVE, N.O.S.(Sodium tert-butoxide)

UN NUMBER: 3206 CLASS: 4.2 (8) PACKING GROUP: II EMS-NO: F-A, S-J

IATA

PROPER SHIPPING NAME: ALKALI METAL ALCOHOLATES, SELF-HEATING,

CORROSIVE, N.O.S.(Sodium *tert*-butoxide)

UN NUMBER: 3206 CLASS: 4.2 (8) PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL

COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DEMINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS REACTIVITY HAZARD, ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT NO COMPONENTS ARE SUBJECT TO THE TO KNOW COMPONENTS MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Sodium *tert*-butoxide 865-48-5

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Sodium *tert*-butoxide 865-48-5

CALIFORNIA PROP. 65 COMPONENTS THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER,

BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE

HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

EYE DAM. SERIOUS EYE DAMAGE

H251 SELF-HEATING: MAY CATCH FIRE.

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

H318 CAUSES SERIOUS EYE DAMAGE.

SELF-HEATING SUBSTANCES AND MIXTURES

SKIN CORR. SKIN CORROSION

HMIS RATING

HEALTH HAZARD: 3

CHRONIC HEALTH

HAZARD:

FLAMMABILITY: 2 PHYSICAL HAZARD 2

NFPA RATING

HEALTH HAZARD: 3
FIRE HAZARD: 2
REACTIVITY HAZARD: 2
SPECIAL HAZARD.I: W
HEALTH HAZARD: 3
FIRE HAZARD:

REACTIVITY HAZARD: 2

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.