

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	30185
NAME:	Lead(IV) oxide
SYNONYMS:	Lead dioxide Lead peroxide
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
OXIDIZING SOLIDS (CATEGORY 3), H272
ACUTE TOXICITY, ORAL (CATEGORY 4), H302
ACUTE TOXICITY, INHALATION (CATEGORY 4), H332
CARCINOGENICITY (CATEGORY 1B), H350

REPRODUCTIVE TOXICITY (CATEGORY 1A), H360
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (CATEGORY 2), H373
ACUTE AQUATIC TOXICITY (CATEGORY 1), H400
CHRONIC AQUATIC TOXICITY (CATEGORY 1), H410

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD

DANGER

HAZARD STATEMENT(S)

H272 MAY INTENSIFY FIRE; OXIDISER.
H302 + H332 HARMFUL IF SWALLOWED OR IF INHALED
H350 MAY CAUSE CANCER.
H360 MAY DAMAGE FERTILITY OR THE UNBORN CHILD.
H373 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED
OR REPEATED EXPOSURE.
H410 VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING
EFFECTS.

PRECAUTIONARY STATEMENT(S)

P201 OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.
P202 DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE
BEEN READ AND UNDERSTOOD.
P210 KEEP AWAY FROM HEAT.
P220 KEEP/STORE AWAY FROM CLOTHING/ COMBUSTIBLE
MATERIALS.
P221 TAKE ANY PRECAUTION TO AVOID MIXING WITH
COMBUSTIBLES.
P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/
SPRAY.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS
PRODUCT.
P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P273 AVOID RELEASE TO THE ENVIRONMENT.
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE
PROTECTION/ FACE PROTECTION.
P301 + P312 + P330 IF SWALLOWED: CALL A POISON CENTER OR DOCTOR/
PHYSICIAN IF YOU FEEL UNWELL. RINSE MOUTH.
P304 + P340 + P312 IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP
COMFORTABLE FOR BREATHING. CALL A POISON CENTER
OR DOCTOR/ PHYSICIAN IF YOU FEEL UNWELL.
P308 + P313 IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/
ATTENTION.
P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR
ALCOHOL-RESISTANT FOAM TO EXTINGUISH.
P391 COLLECT SPILLAGE.
P405 STORE LOCKED UP.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
WASTE DISPOSAL PLANT.

**HAZARDS NOT
OTHERWISE
CLASSIFIED (HNOC)
OR NOT COVERED
BY GHS** NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: PbO₂

MW: 239.2

CAS-NO. 1309-60-0

PURITY: ≥ 97.0% (Assay by titration)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
LEAD DIOXIDE		
	OX. SOL. 3; ACUTE TOX. 4; CARC. 1B; REPR. 1A; STOT RE 2; AQUATIC ACUTE 1; AQUATIC CHRONIC 1; H272, H302 + H332, H350, H360, H373,H410	<= 100%

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.

IN CASE OF SKIN CONTACT WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE CONTACT FLUSH EYES WITH WATER AS A PRECAUTION.

IF SWALLOWED	NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY CHEMICAL OR CARBON DIOXIDE.
-------------------------------------	--

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	LEAD OXIDES
--	-------------

ADVICE FOR FIREFIGHTERS	WEAR SELF-CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.
--------------------------------	--

FURTHER INFORMATION	USE WATER SPRAY TO COOL UNOPENED CONTAINERS.
----------------------------	--

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	USE PERSONAL PROTECTIVE EQUIPMENT. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST. FOR PERSONAL PROTECTION SEE SECTION 8.
--	--

ENVIRONMENTAL PRECAUTIONS	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.
----------------------------------	--

METHODS AND MATERIALS FOR	SWEEP UP AND SHOVEL. CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED
----------------------------------	--

**CONTAINMENT AND
CLEANING UP**

VACUUM CLEANER OR BY WET- BRUSHING AND
PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO
LOCAL REGULATIONS (SEE SECTION 13). KEEP IN
SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.

**REFERENCE TO OTHER
SECTIONS**

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE
HANDLING**

AVOID CONTACT WITH SKIN AND EYES. AVOID
FORMATION OF DUST AND AEROSOLS.FURTHER
PROCESSING OF SOLID MATERIALS MAY RESULT IN
THE FORMATION OF COMBUSTIBLE DUSTS. THE
POTENTIAL FOR COMBUSTIBLE DUST FORMATION
SHOULD BE TAKEN INTO CONSIDERATION BEFORE
ADDITIONAL PROCESSING OCCURS.
PROVIDE APPROPRIATE EXHAUST VENTILATION AT
PLACES WHERE DUST IS FORMED.KEEP AWAY FROM
SOURCES OF IGNITION - NO SMOKING.KEEP AWAY
FROM HEAT AND SOURCES OF IGNITION.
FOR PRECAUTIONS SEE SECTION 2.2.

**CONDITIONS FOR SAFE
STORAGE, INCLUDING
ANY INCOMPATIBILITIES**

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND
WELL-VENTILATED PLACE.
KEEP IN A DRY PLACE.
STORAGE CLASS (TRGS 510): OXIDIZING HAZARDOUS
MATERIALS

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2
NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
LEAD DIOXIDE	1309-60-0	TWA	0.05 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)

	REMARKS	CENTRAL NERVOUS SYSTEM IMPAIRMENT HEMATOLOGIC EFFECTS PERIPHERAL NERVOUS SYSTEM IMPAIRMENT SUBSTANCES FOR WHICH THERE IS A BIOLOGICAL EXPOSURE INDEX OR INDICES (SEE BEI SECTION) CONFIRMED ANIMAL CARCINOGEN WITH UNKNOWN RELEVANCE TO HUMANS VARIES		
		TWA	0.050000 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		CENTRAL NERVOUS SYSTEM IMPAIRMENT HEMATOLOGIC EFFECTS PERIPHERAL NERVOUS SYSTEM IMPAIRMENT SUBSTANCES FOR WHICH THERE IS A BIOLOGICAL EXPOSURE INDEX OR INDICES (SEE BEI SECTION) CONFIRMED ANIMAL CARCINOGEN WITH UNKNOWN RELEVANCE TO HUMANS VARIES		
		TWA	0.050000 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		SEE APPENDIX C		
		PEL	0.050000 MG/M3	OSHA SPECIFICALLY REGULATED CHEMICALS/CARCINOGENS
		1910.1025 IF AN EMPLOYEE IS EXPOSED TO LEAD FOR MORE THAN 8 HOURS IN ANY WORK DAY, THE PERMISSIBLE EXPOSURE LIMIT, AS A TIME WEIGHTED AVERAGE (TWA) FOR THAT DAY, SHALL BE REDUCED ACCORDING TO THE FOLLOWING FORMULA: MAXIMUM PERMISSIBLE LIMIT (IN MG/M3)=400 HOURS WORKED IN THE DAY THIS SECTION APPLIES TO ALL OCCUPATIONAL EXPOSURE TO LEAD, EXCEPT AS PROVIDED IN PARAGRAPH (A)(2). IT DOES NOT APPLY TO THE CONSTRUCTION INDUSTRY OR TO AGRICULTURAL OPERATIONS COVERED BY 29 CFR PART 1928. OSHA SPECIFICALLY REGULATED CARCINOGEN		

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL
HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE
BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

**EYE/FACE
PROTECTION**

SAFETY GLASSES WITH SIDE-SHIELDS CONFORMING TO EN166 USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MI
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

**RESPIRATORY
PROTECTION**

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

**CONTROL OF
ENVIRONMENTAL
EXPOSURE**

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Dark brown amorphous powder
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	290 °C (dec.) (Approx.)
INITIAL BOILING POINT AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	THE SUBSTANCE OR MIXTURE IS CLASSIFIED AS OXIDIZING WITH THE CATEGORY 3.
OTHER SAFETY INFORMATION	NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE

CONDITIONS TO AVOID	NO DATA AVAILABLE
INCOMPATIBLE MATERIALS	STRONG REDUCING AGENTS, POWDERED METALS
HAZARDOUS DECOMPOSITION PRODUCTS	OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	INHALATION: NO DATA AVAILABLE DERMAL: NO DATA AVAILABLE LD50 INTRAPERITONEAL - GUINEA PIG - 220 MG/KG
SKIN CORROSION/IRRITATION	NO DATA AVAILABLE
SERIOUS EYE DAMAGE/EYE IRRITATION	NO DATA AVAILABLE
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE
GERM CELL MUTAGENICITY	NO DATA AVAILABLE
CARCINOGENICITY	
IARC:	2A - GROUP 2A: PROBABLY CARCINOGENIC TO HUMANS (LEAD DIOXIDE)
NTP:	REASONABLY ANTICIPATED TO BE A HUMAN CARCINOGEN THE REFERENCE NOTE HAS BEEN ADDED BY TD BASED ON THE BACKGROUND INFORMATION OF THE NTP. (LEAD DIOXIDE
OSHA:	OSHA SPECIFICALLY REGULATED CARCINOGEN (LEAD DIOXIDE)
REPRODUCTIVE TOXICITY	MAY CAUSE CONGENITAL MALFORMATION IN THE FETUS. KNOWN HUMAN REPRODUCTIVE TOXICANT
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	NO DATA AVAILABLE

ASPIRATION HAZARD

NO DATA AVAILABLE

**ADDITIONAL
INFORMATION**

RTECS: OG0700000

LEAD SALTS HAVE BEEN REPORTED TO CROSS THE PLACENTA AND TO INDUCE EMBRYO- AND FETO-MORTALITY. THEY ALSO HAVE TERATOGENIC EFFECT IN SOME ANIMAL SPECIES. NO TERATOGENIC EFFECTS HAVE BEEN REPORTED WITH EXPOSURE TO ORGANOMETALLIC LEAD COMPOUNDS. ADVERSE EFFECTS OF LEAD ON HUMAN REPRODUCTION, EMBRYONIC AND FETAL DEVELOPMENT, AND POSTNATAL (E.G., MENTAL) DEVELOPMENT HAVE BEEN REPORTED. EXCESSIVE EXPOSURE CAN AFFECT BLOOD, NERVOUS, AND DIGESTIVE SYSTEMS. THE SYNTHESIS OF HEMOGLOBIN IS INHIBITED AND RESULTS IN ANEMIA. IF LEFT UNTREATED, NEUROMUSCULAR DYSFUNCTION, POSSIBLE PARALYSIS, AND ENCEPHALOPATHY CAN RESULT. ADDITIONAL SYMPTOMS OF OVEREXPOSURE INCLUDE: JOINT AND MUSCLE PAIN, WEAKNESS OF THE EXTENSOR MUSCLES (FREQUENTLY THE HAND AND WRIST), HEADACHE, DIZZINESS, ABDOMINAL PAIN, DIARRHEA, CONSTIPATION, NAUSEA, VOMITING, BLUE LINE ON THE GUMS, INSOMNIA, AND METALLIC TASTE. HIGH BODY LEVELS PRODUCE INCREASED CEREBROSPINAL PRESSURE, BRAIN DAMAGE, AND STUPOR LEADING TO COMA AND OFTEN DEATH., ANOREXIA., VOMITING, CONVULSIONS, TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.
STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY

NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY**BIODEGRADABILITY**

RESULT: - NOT READILY BIODEGRADABLE.

**BIOACCUMULATIVE
POTENTIAL**

NO DATA AVAILABLE

MOBILITY IN SOIL

NO DATA AVAILABLE

**RESULTS OF PBT AND
VPVB ASSESSMENT**

PBT/VPVB ASSESSMENT NOT AVAILABLE AS
CHEMICAL SAFETY ASSESSMENT NOT
REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS

AN ENVIRONMENTAL HAZARD CANNOT BE
EXCLUDED IN THE EVENT OF UNPROFESSIONAL
HANDLING OR DISPOSAL. VERY TOXIC TO AQUATIC
LIFE WITH LONG LASTING EFFECTS.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT

BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH
AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA
CARE IN IGNITING AS THIS MATERIAL IS HIGHLY
FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE
SOLUTIONS TO A LICENSED DISPOSAL COMPANY.
CONTACT A LICENSED PROFESSIONAL WASTE
DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.
DISSOLVE OR MIX THE MATERIAL WITH A
COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL
INCINERATOR EQUIPPED WITH AN AFTERBURNER AND
SCRUBBER.

**CONTAMINATED
PACKAGING**

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: LEAD DIOXIDE
UN NUMBER: 1872
CLASS: 5.1
PACKING GROUP: III
REPORTABLE QUANTITY
(RQ):
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: LEAD DIOXIDE
UN NUMBER: 1872
CLASS: 5.1
PACKING GROUP: III
EMS-NO: F-A, S-Q
MARINE POLLUTANT: YES

IATA
PROPER SHIPPING NAME: LEAD DIOXIDE
UN NUMBER: 1872
CLASS: 5.1
PACKING GROUP: III

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DEMINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Lead(IV) oxide	1309-60-0	4/24/1993

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Lead(IV) oxide	1309-60-0	4/24/1993

NEW JERSEY RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Lead(IV) oxide	1309-60-0	4/24/1993

CALIFORNIA PROP. 65 COMPONENTS WARNING! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

	CAS-NO.	REVISION DATE
Lead(IV) oxide	1309-60-0	9/28/2007

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

ACUTE TOX.	ACUTE TOXICITY
AQUATIC ACUTE	ACUTE AQUATIC TOXICITY
AQUATIC CHRONIC	CHRONIC AQUATIC TOXICITY
CARC.	CARCINOGENICITY
H272	MAY INTENSIFY FIRE; OXIDISER.

H302	HARMFUL IF SWALLOWED.
H302 + H332	HARMFUL IF SWALLOWED OR IF INHALED
H332	HARMFUL IF INHALED.
H350	MAY CAUSE CANCER.
H360	MAY DAMAGE FERTILITY OR THE UNBORN CHILD.
H373	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.
H400	VERY TOXIC TO AQUATIC LIFE.

HMIS RATING

HEALTH HAZARD:	2
CHRONIC HEALTH HAZARD:	*
FLAMMABILITY:	0
PHYSICAL HAZARD	1

NFPA RATING

HEALTH HAZARD:	2
FIRE HAZARD:	0
REACTIVITY HAZARD:	1
SPECIAL HAZARD.I:	OX

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*