Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 33070

NAME: Potassium *tert*-butoxide solution, 2.0 M in THF

SYNONYMS: Potassium *tert*-butylate solution

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE LIQUIDS (CATEGORY 2), H225

ACUTE TOXICITY, ORAL (CATEGORY 4), H302 SKIN CORROSION (CATEGORY 1A), H314 SERIOUS EYE DAMAGE (CATEGORY 1), H318 CARCINOGENICITY (CATEGORY 2), H351 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), RESPIRATORY SYSTEM, H335

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD **DANGER**

HAZARD STATEMENT(S)

H225	HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H302	HARMFUL IF SWALLOWED.
H314	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H335	MAY CAUSE RESPIRATORY IRRITATION.
H351	SUSPECTED OF CAUSING CANCER.

P

11331	SOSI ECTED OF CHOSING CANCER.				
PRECAUTIONARY STATEMENT(S)					
P201	OBTAIN SPECIAL INSTRUCTIONS BEFORE USE				
P202	DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE				
	BEEN READ AND UNDERSTOOD.				
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT				
	SURFACES. NO SMOKING.				
P233	KEEP CONTAINER TIGHTLY CLOSED.				
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.				
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/				
	LIGHTING/ EQUIPMENT.				
P242	USE ONLY NON-SPARKING TOOLS.				
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC				
	DISCHARGE.				
P261	AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/				
	SPRAY.				
P264	WASH SKIN THOROUGHLY AFTER HANDLING.				
P270	DO NOT EAT, DRINK OR SMOKE WHEN USING THIS				
	PRODUCT.				
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.				
P280	WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE				
	PROTECTION/ FACE PROTECTION.				
P301 + P312 + P330	IF SWALLOWED: CALL A POISON CENTER/DOCTOR IF YOU				
	FEEL UNWELL. RINSE MOUTH.				
P301 + P330 + P331	IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE				
	VOMITING.				
P303 + P361 + P353	IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL				
	CONTAMINATED CLOTHING. RINSE SKIN WITH				
	WATER/SHOWER.				
D204 - D240 - D212	HE DALLA ED. DEMONE DEDGON TO EDEGNA ID 132 WEEK				
P304 + P340 + P310	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP				
	COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A				

POISON CENTER/DOCTOR.

P305 + P351 + P338 + IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL P310 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A POISON CENTER/DOCTOR. IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ P308 + P313ATTENTION. P363 WASH CONTAMINATED CLOTHING BEFORE REUSE. P370 + P378IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM TO EXTINGUISH. STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER P403 + P233

TIGHTLY CLOSED.

STORE IN A WELL-VENTILATED PLACE. KEEP COOL. P403 + P235

P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT **OTHERWISE**

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

NONE

MF: C_4H_9OK

MW: 112.21

PURITY: \geq 99% (Assay by titration)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION			
TETRAHYDROFURAN					
CAS - 109-99-9	FLAM. LIQ. 2; ACUTE TOX. 4;	>= 70 - < 90 %			
	EYE IRRIT. 2A; CARC. 2; STOT				
	SE 3; H225, H302, H319, H335,				
	H351				
COMPONENT	CLASSIFICATION	CONCENTRATION			
POTASSIUM TERT-BUTANOLATE					
CAS - 865-47-4	FLAM. SOL. 1; SKIN CORR. 1A;	>= 10 - < 20 %			
	EYE DAM. 1; H228, H314,				
	H318				

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION. SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

CONTACT

WASH OFF WITH SOAP AND PLENTY OF WATER.

CONSULT A PHYSICIAN.

IN CASE OF EYE

CONTACT

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A PHYSICIAN. CONTINUE RINSING EYES DURING TRANSPORT TO

HOSPITAL.

IF SWALLOWED NEVER GIVE ANYTHING BY MOUTH TO AN

UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER.

CONSULT A PHYSICIAN.

MOST IMPORTANT

SYMPTOMS AND

EFFECTS, BOTH ACUTE

AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL

ATTENTION AND SPECIAL TREATMENT

NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY

EXTINGUISHING MEDIA CHEMICAL OR CARBON DIOXIDE.

SPECIAL HAZARDS ARISING FROM THE

SUBSTANCE OR MIXTURE

HYDROGEN CHLORIDE GAS, CARBON OXIDES

ADVICE FOR WEAR SELF-CONTAINED BREATHING APPARATUS FOR

FIREFIGHTERS FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES

USE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN

ACCUMULATE IN LOW AREAS.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET-BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE

SECTION 13).

REFERENCE TO OTHER SECTIONS

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

AVOID CONTACT WITH SKIN AND EYES. AVOID INHALATION OF VAPOUR OR MIST.

USE EXPLOSION-PROOF EQUIPMENT.KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF

ELECTROSTATIC CHARGE.

FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT

UPRIGHT TO PREVENT LEAKAGE.

HYDROLYSES READILY. HANDLE AND STORE UNDER INERT GAS. DRY RESIDUE IS EXPLOSIVE. STORE UNDER INERT GAS. TEST FOR PEROXIDE FORMATION PERIODICALLY AND BEFORE DISTILLATION.

STORAGE CLASS (TRGS 510): FLAMMABLE LIQUIDS

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS
			PARAMETERS	
TETRAHYDROFURAN	109-99-9	TWA	50.000000 PPM	USA. ACGIH
				THRESHOLD
				LIMIT VALUES
				(TLV)
	REMARKS	CENTRAL 1	NERVOUS SYSTEM	M IMPAIRMENT
		UPPER RESPIRATORY TRACT IRRITATION		
		KIDNEY DAMAGE		
		CONFIRMED ANIMAL CARCINOGEN WITH		
		UNKNOWN RELEVANCE TO HUMANS		
			OF CUTANEOUS AE	
		STEL	100.000000	USA.
			PPM	OCCUPATIONAL
				EXPOSURE
				LIMITS
				(OSHA) - TABLE
				Z-1 LIMITS FOR
				AIR
				CONTAMINANTS
		CENTRAL NERVOUS SYSTEM IMPAIRMENT		
		UPPER RESPIRATORY TRACT IRRITATION		
		KIDNEY DAMAGE		
		CONFIRMED ANIMAL CARCINOGEN WITH		
		UNKNOWN RELEVANCE TO HUMANS		
			OF CUTANEOUS AF	,
		TWA	200.000000	USA. NIOSH
			PPM	RECOMMENDED
			590.000000	EXPOSURE
		OT.	MG/M3	LIMITS
		ST	250.000000	USA. NIOSH
			PPM	RECOMMENDED
			735.000000	EXPOSURE
			MG/M3	LIMITS

TWA	200.000000	USA.
	PPM	OCCUPATIONAL
	590.000000	EXPOSURE
	MG/M3	LIMITS
		(OSHA) - TABLE
		Z-1 LIMITS FOR
		AIR
		CONTAMINANTS
THE VALU	JE IN MG/M3 IS A	PPROXIMATE.
PEL	200 PPM	CALIFORNIA
	590 MG/M3	PERMISSIBLE
		EXPOSURE
		LIMITS FOR
		CHEMICAL
		CONTAMINANTS
		(TITLE 8,
		ARTICLE 107)
STEL	250 PPM	CALIFORNIA
	735 MG/M3	PERMISSIBLE
		EXPOSURE
		LIMITS FOR
		CHEMICAL
		CONTAMINANTS
		(TITLE 8,
		ARTICLE 107)

HAZARDOUS COMPONENTS WITHOUT WORKPLACE CONTROL PARAMETERS

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS

COMPONENT	CAS-NO.	VALUE	BIOLOGICAL SPECIMEN	BASIS
TETRAHYDROFURAN	109-99-9	2.0000 MG/L	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
	REMARKS	END OF SHIFT (AS SOON AS POSSIBLE AFTER EXPOSURE CEASES)		

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING

CONTROLS

HANDLE IN ACCORDANCE WITH GOOD

INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END

OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION FACE SHIELD AND SAFETY GLASSES USE

EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

SPLASH CONTACT

MATERIAL: BUTYL-RUBBER

MINIMUM LAYER THICKNESS: 0.3 MM

BREAK THROUGH TIME: 10 MIN

MATERIAL TESTED:BUTOJECT (KCL 897, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF

THE CE APPROVED GLOVES. THIS

RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL

HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC

USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Colorless to yellowish brown liquid

ODOUR NO DATA AVAILABLE
ODOUR THRESHOLD NO DATA AVAILABLE
PH NO DATA AVAILABLE

MELTING

POINT/FREEZING POINT INITIAL BOILING POINT AND BOILING RANGE

FLASH POINT -21°C

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY 0.929 g/cm³

WATER SOLUBILITY NO DATA AVAILABLE PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION THE SUBSTANCE OR MIXTURE IS NOT CLASSIFIED AS

TEMPERATURE SELF HEATING.

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

CONDITIONS TO AVOID HEAT, FLAMES AND SPARKS.

INCOMPATIBLE MATERIALS

STRONG ACIDS, STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - CARBON OXIDES,

POTASSIUM OXIDES

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY NO DATA AVAILABLE

INHALATION: NO DATA AVAILABLE DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN NO DATA AVAILABLE

CORROSION/IRRITATION

SERIOUS EYE NO DATA AVAILABLE

DAMAGE/EYE IRRITATION

RESPIRATORY OR SKIN

SENSITISATION

NO DATA AVAILABLE

GERM CELL NO DATA AVAILABLE **MUTAGENICITY**

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL

CARCINOGEN BY OSHA.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE

EXPOSURE

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - REPEATED

EXPOSURE

NO DATA AVAILABLE

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL RTECS: NOT AVAILABLE

INFORMATION MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE

> OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN.

STOMACH - IRREGULARITIES - BASED ON HUMAN

EVIDENCE

SECTION 12. **ECOLOGICAL INFORMATION**

TOXICITY NO DATA AVAILABLE

PERSISTENCE AND **DEGRADABILITY**

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND

PBT/VPVB ASSESSMENT NOT AVAILABLE AS VPVB ASSESSMENT

CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH

AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA

CARE IN IGNITING AS THIS MATERIAL IS HIGHLY

FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE

SOLUTIONS TO A LICENSED DISPOSAL COMPANY.

CONTACT A

LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE

TO DISPOSE OF THIS MATERIAL.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: WATER-REACTIVE LIQUID, CORROSIVE, N.O.S.

(POTASSIUM TERT-BUTANOLATE,

TETRAHYDROFURAN)

UN NUMBER: 3129 CLASS: 4.3 (8) PACKING GROUP: I

REPORTABLE QUANTITY 1142 LBS

(RO)

POISON INHALATION NO

HAZARD

IMDG

PROPER SHIPPING NAME: WATER-REACTIVE LIQUID, CORROSIVE, N.O.S.

(POTASSIUM TERT-BUTANOLATE.

TETRAHYDROFURAN)

UN NUMBER: 3129 CLASS: 4.3 (8) PACKING GROUP: I

EMS-NO: F-G, S-N

IATA

PROPER SHIPPING NAME: WATER-REACTIVE LIQUID, CORROSIVE, N.O.S.

(POTASSIUM TERT-BUTANOLATE,

TETRAHYDROFURAN)

UN NUMBER: 3129 CLASS: 4.3 (8) PACKING GROUP: I

IATA PASSENGER: NOT PERMITTED FOR TRANSPORT

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL

COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS FIRE HAZARD, ACUTE HEALTH HAZARD, CHRONIC

HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

TETRAHYDROFURAN 109-99-9 4/24/1993

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

TETRAHYDROFURAN 109-99-9 4/24/1993

Potassium *tert*-butoxide 865-47-4

solution, 2.0 M in THF

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

TETRAHYDROFURAN 109-99-9 4/24/1993

Potassium *tert*-butoxide 865-47-4

solution, 2.0 M in THF

CALIFORNIA PROP. 65 COMPONENTS THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER,

BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE

HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

ACUTE TOX. ACUTE TOXICITY CARC. CARCINOGENICITY

EYE DAM. SERIOUS EYE DAMAGE

EYE IRRIT. EYE IRRITATION

FLAM. LIQ. FLAMMABLE LIQUIDS FLAM. SOL. FLAMMABLE SOLIDS

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR

H228 FLAMMABLE SOLID

H302 HARMFUL IF SWALLOWED.

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H318 CAUSES SERIOUS EYE DAMAGE.
H319 CAUSES SERIOUS EYE IRRITATION.
H335 MAY CAUSE RESPIRATORY IRRITATION.
H351 SUSPECTED OF CAUSING CANCER.

HMIS RATING

HEALTH HAZARD: 3

CHRONIC HEALTH

HAZARD:

FLAMMABILITY: 3 PHYSICAL HAZARD 2

NFPA RATING

HEALTH HAZARD: 3 FIRE HAZARD: 3 REACTIVITY HAZARD: 0 MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.