Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 33417

NAME: Selenium powder, -100 mesh, >= 99.9% (Metals basis)

SYNONYMS:

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

ACUTE TOXICITY, ORAL (CATEGORY 3), H301 ACUTE TOXICITY, INHALATION (CATEGORY 3), H331 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (CATEGORY 2), H373 CHRONIC AQUATIC TOXICITY (CATEGORY 4), H413 FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H301 + H331 TOXIC IF SWALLOWED OR IF INHALED

H373 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED

OR REPEATED EXPOSURE.

H413 MAY CAUSE LONG LASTING HARMFUL EFFECTS TO

AQUATIC LIFE.

PRECAUTIONARY STATEMENT(S)

P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/

SPRAY.

P264 WASH SKIN THOROUGHLY AFTER HANDLING. P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS

PRODUCT.

P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P273 AVOID RELEASE TO THE ENVIRONMENT.

P301 + P310 + P330 IF SWALLOWED: IMMEDIATELY CALL A POISON

CENTER/DOCTOR. RINSE MOUTH.

P304 + P340 + P311 IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP

COMFORTABLE FOR BREATHING. CALL A POISON

CENTER/DOCTOR.

P314 GET MEDICAL ADVICE/ ATTENTION IF YOU FEEL UNWELL.

P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER

TIGHTLY CLOSED.

P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT NONE

OTHERWISE

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: Se

MW: 78.96

CAS-NO. 7782-49-2

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION			
Selenium powder, -100 mesh, >= 99.9% (Metals basis)					
	ACUTE TOX. 3; STOT RE 2;	<= 100 %			
	AQUATIC CHRONIC 4; H301 +				
	H331, H373, H413				

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCE	DIPTION	OF FIRST AID	MEASURES
170,31 0		OF FIRST ALL	VIP.A.SIIRP.S

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

CONTACT

WASH OFF WITH SOAP AND PLENTY OF WATER. TAKE

VICTIM IMMEDIATELY TO HOSPITAL. CONSULT A

PHYSICIAN.

IN CASE OF EYE

CONTACT

FLUSH EYES WITH WATER AS A PRECAUTION.

IF SWALLOWED NEVER GIVE ANYTHING BY MOUTH TO AN

UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER.

CONSULT A PHYSICIAN.

MOST IMPORTANT

SYMPTOMS AND

EFFECTS, BOTH ACUTE

AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY

IMMEDIATE MEDICAL ATTENTION AND

SPECIAL TREATMENT

NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

SUITABLE USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY

EXTINGUISHING MEDIA CHEMICAL OR CARBON DIOXIDE.

SPECIAL HAZARDS ARISING FROM THE

SUBSTANCE OR MIXTURE

NO DATA AVAILABLE

ADVICE FOR WEAR SELF CONTAINED BREATHING APPARATUS FOR

FIREFIGHTERS FIRE FIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL WEAR RESPIRATORY PROTECTION. AVOID DUST **PRECAUTIONS,** FORMATION. AVOID BREATHING VAPOURS, MIST OR

PROTECTIVE GAS. ENSURE ADEQUATE VENTILATION.

EQUIPMENT AND EVACUATE PERSONNEL TO SAFE AREAS. AVOID

EMERGENCY BREATHING DUST.

PROCEDURES FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE **PRECAUTIONS** TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

METHODS AND PICK UP AND ARRANGE DISPOSAL WITHOUT

MATERIALS FORCREATING DUST. SWEEP UP AND SHOVEL. KEEP INCONTAINMENT ANDSUITABLE, CLOSED CONTAINERS FOR DISPOSAL.

CLEANING UP

REFERENCE TO OTHER FOR DISPOSAL SEE SECTION 13.

SECTIONS

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS.FURTHER PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE

ADDITIONAL PROCESSING OCCURS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT

PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND

WELL-VENTILATED PLACE.

STORE UNDER INERT GAS. KEEP IN A DRY PLACE.

Store at RT

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2

NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS	
Selenium powder,	7782-49-2	TWA	0.2 MG/M3	USA. ACGIH	
-100 mesh, >=				THRESHOLD	
99.9% (Metals				LIMIT VALUES	
basis)				(TLV)	
	REMARKS	EYE & UPPER RESPIRATORY TRACT IRRITATION			
		TWA	0.200000 MG/M3	USA. ACGIH	
				THRESHOLD	
				LIMIT VALUES	
				(TLV)	
		EYE & UPPI	EYE & UPPER RESPIRATORY TRACT IRRITATION		
		TWA	0.200000 MG/M3	USA.	
				OCCUPATIONAL	
				EXPOSURE	
				LIMITS (OSHA) -	
				TABLE Z-1	
				LIMITS FOR AIR	
				CONTAMINANTS	
		TWA	0.200000 MG/M3	USA. NIOSH	
				RECOMMENDED	
				EXPOSURE	
				LIMITS	
		TWA	0.2 MG/M3	USA. NIOSH	
				RECOMMENDED	
				EXPOSURE	
				LIMITS	
		TWA	0.2 MG/M3	USA.	
				OCCUPATIONAL	
				EXPOSURE	
				LIMITS (OSHA) -	
				TABLE Z-1	
				LIMITS FOR AIR	
				CONTAMINANTS	

	TWA		USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
	UPPER RESPIRA IRRITATION	TORY TRACT IRRI	TATION EYE
	PEL		CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH HANDS BEFORE BREAKS AND IMMEDIATELY AFTER HANDLING THE PRODUCT.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION FACE SHIELD AND SAFETY GLASSES USE

EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT
MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N99 (US) OR TYPE P2 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Greyish black powder
ODOUR NO DATA AVAILABLE
ODOUR THRESHOLD NO DATA AVAILABLE
PH NO DATA AVAILABLE

MELTING 216 - 218 °C

POINT/FREEZING POINT

INITIAL BOILING POINT 682 - 686 °C

AND BOILING RANGE

FLASH POINT

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY 4.81

WATER SOLUBILITY INSOLUBLE PARTITION COEFFICIENT: LOG POW: 5

N- OCTANOL/WATER

AUTO-IGNITION NO DATA AVAILABLE

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS NO DATA AVAILABLE

CONDITIONS TO AVOID NO DATA AVAILABLE

INCOMPATIBLE STRONG OXIDIZING AGENTS, DO NOT STORE NEAR ACIDS., AMIDES, CARBIDES, METALS, NICKEL, NITRIC MATERIALS

ACID, NITROGEN TRICHLORIDE, OXYGEN, POTASSIUM,

ZINC

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - SELENIUM/SELENIUM

OXIDES

OTHER DECOMPOSITION PRODUCTS - NO DATA

AVAILABLE

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY LD50 ORAL - RAT - 6,700 MG/KG

> REMARKS: BEHAVIORAL:SOMNOLENCE (GENERAL DEPRESSED ACTIVITY). LUNGS, THORAX, OR

> RESPIRATION: DYSPNEA. NUTRITIONAL AND GROSS

METABOLIC: CHANGES IN: OTHER CHANGES

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN NO DATA AVAILABLE

CORROSION/IRRITATION

SERIOUS EYE NO DATA AVAILABLE

DAMAGE/EYE IRRITATION

RESPIRATORY OR SKIN NO DATA AVAILABLE

SENSITISATION

GERM CELL NO DATA AVAILABLE

MUTAGENICITY

CARCINOGENICITY

CARCINOGENICITY - MOUSE - ORAL

TUMORIGENIC:EOUIVOCAL TUMORIGENIC AGENT BY RTECS CRITERIA. SKIN AND APPENDAGES: OTHER: TUMORS.

THIS PRODUCT IS OR CONTAINS A COMPONENT THAT IS NOT CLASSIFIABLE AS TO ITS CARCINOGENICITY BASED ON ITS IARC, ACGIH, NTP, OR EPA CLASSIFICATION. NO COMPONENT OF THIS PRODUCT PRESENT AT IARC:

LEVELS GREATER THAN OR EQUAL TO 0.1% IS

IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED

HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL

CARCINOGEN BY OSHA.

REPRODUCTIVE TOXICITY DEVELOPMENTAL TOXICITY - MOUSE - ORAL

EFFECTS ON EMBRYO OR FETUS: FETOTOXICITY (EXCEPT DEATH, E.G., STUNTED FETUS). EFFECTS ON

EMBRYO OR FETUS: FETAL DEATH.

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE

EXPOSURE

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EXPOSURE

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

ASPIRATION HAZARD N

NO DATA AVAILABLE

ADDITIONAL INFORMATION

RTECS: VS7700000

ANEMIA, VOMITING, DIARRHOEA, COUGH, DIFFICULTY IN BREATHING, ACUTE SELENIUM POISONING PRODUCES CENTRAL NERVOUS SYSTEM

EFFECTS, WHICH INCLUDE NERVOUSNESS,

CONVULSIONS, AND DROWSINESS. OTHER SIGNS OF INTOXICATION CAN INCLUDE SKIN ERUPTIONS, LASSITUDE, GASTROINTESTINAL DISTRESS, TEETH THAT ARE DISCOLORED OR DECAYED, ODOROUS ("GARLIC") BREATH, AND PARTIAL LOSS OF HAIR AND NAILS. CHRONIC EXPOSURE BY INHALATION CAN PRODUCE SYMPTOMS THAT INCLUDE PALLOR, COATING OF THE TONGUE, ANEMIA, IRRITATION OF THE MUCOSA, LUMBAR PAIN, LIVER AND SPLEEN

DAMAGE, AS WELL AS ANY OF THE OTHER

PREVIOUSLY MENTIONED SYMPTOMS. CHRONIC CONTACT WITH SELENIUM COMPOUNDS MAY CAUSE GARLIC ODOR OF BREATH AND SWEAT, DERMATITIS,

AND MODERATE EMOTIONAL INSTABILITY.,

DERMATITIS, GARLIC-LIKE BREATH ODOR, PALLOR,

NERVOUSNESS, DEPRESSION

STOMACH - IRREGULARITIES - BASED ON HUMAN

EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY

TOXICITY TO FISH MORTALITY NOEC - CYPRINODON VARIEGATUS

(SHEEPSHEAD MINNOW) - 2 MG/L - 96.0 H

MORTALITY LOEC - ONCORHYNCHUS MYKISS

(RAINBOW TROUT) - 7.8 MG/L - 96.0 H

TOXICITY TO DAPHNIA AND OTHER AQUATIC

Н

INVERTEBRATES

TOXICITY TO ALGAE

EC50 - PSEUDOKIRCHNERIELLA SUBCAPITATA - 99

LC50 - DAPHNIA MAGNA (WATER FLEA) - 0.43 MG/L - 48

MG/L - 72 H

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION LEPOMIS MACROCHIRUS - 60 D - 640 G/L

BIOCONCENTRATION FACTOR (BCF): 7.7

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS

CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT

CONDUCTED

OTHER ADVERSE

EFFECTS

AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL

HANDLING OR DISPOSAL.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS

TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN

AFTERBURNER AND SCRUBBER.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S. (SELENIUM POWDER)

UN NUMBER: 3077
CLASS: 9
PACKING GROUP: III
REPORTABLE QUANTITY 100 LBS

(RQ):

POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S. (SELENIUM POWDER)

UN NUMBER: 3077
CLASS: 9
PACKING GROUP: III
EMS-NO: F-A, S-A
MARINE POLLUTANT YES

IATA

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S. (SELENIUM POWDER)

UN NUMBER: 3077 CLASS: 9 PACKING GROUP: III

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THE FOLLOWING COMPONENTS ARE SUBJECT TO

REPORTING LEVELS ESTABLISHED BY SARA TITLE III,

SECTION 313:

CAS-NO. REVISION DATE

Selenium powder, -100 mesh, >= 99.9% (Metals basis)

h, 7782-49-2

07/01/2007

SARA 311/312 HAZARDS ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Selenium powder, -100 mesh, 7782-49-2 07/01/2007

>= 99.9% (Metals basis)

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Selenium powder, -100 mesh, 7782-49-2 07/01/2007

>= 99.9% (Metals basis)

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Selenium powder, -100 mesh, 7782-49-2 07/01/2007

>= 99.9% (Metals basis)

CALIFORNIA PROP. 65 COMPONENTS THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER,

BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE

HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

ACUTE TOX. ACUTE TOXICITY

AQUATIC CHRONIC CHRONIC AQUATIC TOXICITY

H301 TOXIC IF SWALLOWED.

H301 + H331 TOXIC IF SWALLOWED OR IF INHALED

H331 TOXIC IF INHALED.

H373 MAY CAUSE DAMAGE TO ORGANS THROUGH

PROLONGED OR REPEATED EXPOSURE.

H413 MAY CAUSE LONG LASTING HARMFUL EFFECTS TO

AQUATIC LIFE.

HMIS RATING

HEALTH HAZARD: 2 CHRONIC HEALTH *

HAZARD:

FLAMMABILITY: 0 PHYSICAL HAZARD 0

NFPA RATING

HEALTH HAZARD: 2 FIRE HAZARD: 0 REACTIVITY HAZARD: 0

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL

INDUSTRIAL HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY

NUMBER

OSHA: OCCUPATIONAL SAFETY AND HEALTH

ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION:3.1. REVISION DATE: 07/01/2007