

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 33903

NAME: Camphene

SYNONYMS:

24 HOUR EMERGENCY (800) 535-5053(USA)
TELEPHONE: 352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER (630) 766-2112
SERVICE:

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

FLAMMABLE SOLIDS (CATEGORY 1), H228
EYE IRRITATION (CATEGORY 2A), H319
SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 1), H400
LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 1), H410

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS PICTOGRAM



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H228 FLAMMABLE SOLID.
H319 CAUSES SERIOUS EYE IRRITATION.
H410 VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT(S)

P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. NO SMOKING.
P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241 USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/ LIGHTING EQUIPMENT.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P273 AVOID RELEASE TO THE ENVIRONMENT.
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.
P305 + P351 + P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.
P337 + P313 IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ ATTENTION.
P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P391 COLLECT SPILLAGE.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: $C_{10}H_{16}$
MW: 136.24
CAS-NO. 79-92-5
PURITY: 97 - 100% (GC)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Camphene		
	FLAM. SOL. 1; EYE IRRIT. 2A; AQUATIC ACUTE 1; AQUATIC CHRONIC 1; H228, H319, H400, H410	<= 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.
IF SWALLOWED	DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY CHEMICAL OR CARBON DIOXIDE.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	CARBON OXIDES
ADVICE FOR FIREFIGHTERS	WEAR SELF-CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.
FURTHER INFORMATION	USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	USE PERSONAL PROTECTIVE EQUIPMENT. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	SWEEP UP AND SHOVEL. CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WETBRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL. CONTAIN SPILLAGE, PICK UP WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WETBRUSHING AND TRANSFER TO A CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13).
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS.FURTHER
--	--

PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE ADDITIONAL PROCESSING OCCURS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING. TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE.
FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE.

Store at 0 - 8 °C

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

SAFETY GLASSES WITH SIDE-SHIELDS CONFORMING TO EN166 USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION	HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.
	FULL CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)
	SPLASH CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)
	IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.
BODY PROTECTION	IMPERVIOUS CLOTHING, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.
RESPIRATORY PROTECTION	WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).
CONTROL OF ENVIRONMENTAL EXPOSURE	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	White translucent waxy solid
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING	
POINT/FREEZING POINT	
INITIAL BOILING POINT	157 - 159 °C
AND BOILING RANGE	
FLASH POINT	23 °C
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	THE SUBSTANCE OR MIXTURE IS A FLAMMABLE SOLID WITH THE CATEGORY 1.
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE
OTHER SAFETY INFORMATION	NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	HEAT, FLAMES AND SPARKS.
INCOMPATIBLE MATERIALS	STRONG OXIDIZING AGENTS

**HAZARDOUS
DECOMPOSITION
PRODUCTS**

HAZARDOUS DECOMPOSITION PRODUCTS FORMED
UNDER FIRE CONDITIONS. - CARBON OXIDES
OTHER DECOMPOSITION PRODUCTS - NO DATA
AVAILABLE
IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY

NO DATA AVAILABLE

INHALATION: NO DATA AVAILABLE

LD50 DERMAL - RABBIT - > 2,500 MG/KG
REMARKS: (IUCLID)

NO DATA AVAILABLE

**SKIN
CORROSION/IRRITATION**

SKIN - RABBIT
RESULT: NO SKIN IRRITATION

**SERIOUS EYE
DAMAGE/EYE IRRITATION**

EYES - RABBIT
RESULT: EYE IRRITATION

**RESPIRATORY OR SKIN
SENSITISATION**

HUMAN EXPERIENCE
RESULT: NEGATIVE
REMARKS: (IUCLID)

**GERM CELL
MUTAGENICITY**

AMES TEST
RESULT: NEGATIVE
(IUCLID)
RESULT: NEGATIVE

CARCINOGENICITY

IARC:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED
HUMAN CARCINOGEN BY IARC.

NTP:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS A KNOWN OR ANTICIPATED
CARCINOGEN BY NTP.

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON
OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	NO DATA AVAILABLE
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: EX1055000 TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES	EC50 - DAPHNIA MAGNA (WATER FLEA) - 13 - 36 MG/L - 48 H REMARKS: (LIT.)
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL HANDLING OR DISPOSAL. VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME:	FLAMMABLE SOLIDS, ORGANIC, N.O.S. (Camphene)
UN NUMBER:	1325
CLASS:	4.1
PACKING GROUP:	II
REPORTABLE QUANTITY (RQ):	
POISON INHALATION HAZARD:	NO

IMDG

PROPER SHIPPING NAME:	FLAMMABLE SOLIDS, ORGANIC, N.O.S. (Camphene)
UN NUMBER:	1325
CLASS:	4.1
PACKING GROUP:	II
EMS-NO:	F-A, S-G
MARINE POLLUTANT:	YES

IATA

PROPER SHIPPING NAME:	FLAMMABLE SOLIDS, ORGANIC, N.O.S. (Camphene)
UN NUMBER:	1325
CLASS:	4.1
PACKING GROUP:	II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS	NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.
----------------------------	---

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS
FIRE HAZARD, ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS
NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Camphene	79-92-5	07-31-1994

NEW JERSEY RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Camphene	79-92-5	07-31-1994

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H228	FLAMMABLE SOLID.
H319	CAUSES SERIOUS EYE IRRITATION.
H410	VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

