Chem-Impex International Inc.

Tel: (630) 766-2112 E-mail: <u>sales@chemimpex.com</u> Shipping and Correspondence: 935 Dillon Drive Wood Dale, IL 60191 USA

Fax: (630) 766-2218 Web site: <u>www.chemimpex.com</u> Manufacturing site: 825 Dillon Drive Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	34403
NAME:	Isoamyl acetate
SYNONYMS:	Isopentyl acetate
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE LIQUIDS (CATEGORY 3), H226 FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM	
SIGNAL WORD	WARNING
HAZARD STATEMENT(S	
H226	FLAMMABLE LIQUID AND VAPOUR.
PRECAUTIONARY STAT	'EMENT(S)
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT
	SURFACES NO SMOKING.
P233	KEEP CONTAINER TIGHTLY CLOSED.
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/
	LIGHTING/ EQUIPMENT.
P242	USE ONLY NON-SPARKING TOOLS.
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC
	DISCHARGE.
P280	WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE
	PROTECTION.
P303 + P361 + P353	IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY
	ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/
	SHOWER.
P370 + P378	IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR
D 402 - D225	ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P403 + P235	STORE IN A WELL-VENTILATED PLACE. KEEP COOL.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
	WASTE DISPOSAL PLANT.
HAZARDS NOT	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR
OTHERWISE	CRACKING.
CLASSIFIED (HNOC)	CRACKING.
OR NOT COVERED	
BY GHS	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:	$C_7H_{14}O_2$
MW:	130.19
CAS-NO.	123-92-2
PURITY:	\geq 99% (GC)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Isoamyl acetate		
	FLAM. LIQ. 3; AQUATIC	<= 100 %
	ACUTE 3; H226, H402	

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	FLUSH EYES WITH WATER AS A PRECAUTION.
IF SWALLOWED	DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT	THE MOST IMPORTANT KNOWN SYMPTOMS AND
SYMPTOMS AND	EFFECTS ARE DESCRIBED IN THE LABELLING (SEE
EFFECTS, BOTH ACUTE AND DELAYED	SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE	USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY
EXTINGUISHING MEDIA	CHEMICAL OR CARBON DIOXIDE.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	CARBON OXIDES

ADVICE FOR	WEAR SELF CONTAINED BREATHING APPARATUS FOR
FIREFIGHTERS	FIRE FIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL	AVOID BREATHING VAPOURS, MIST OR GAS. REMOVE
PRECAUTIONS,	ALL SOURCES OF IGNITION. BEWARE OF VAPOURS
PROTECTIVE	ACCUMULATING TO FORM EXPLOSIVE
EQUIPMENT AND	CONCENTRATIONS. VAPOURS CAN ACCUMULATE IN
EMERGENCY	LOW AREAS.
PROCEDURES	FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE
PRECAUTIONS	TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET-BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13).
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	AVOID INHALATION OF VAPOUR OR MIST. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE. FOR PRECAUTIONS SEE SECTION 2.2.
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE.
SPECIFIC END USE(S)	Store at RT APART FROM THE USES MENTIONED IN SECTION 1.2
	NO OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS	
Isoamyl acetate	123-92-2	TWA	100 PPM	USA. NIOSH	
			525 MG/M3	RECOMMENDED EXPOSURE	
				LIMITS	
		TWA	100 PPM	USA. OCCUPATIONAL	
			525 MG/M3	EXPOSURE LIMITS (OSHA) -	
				TABLE Z-1 LIMITS FOR AIR	
				CONTAMINANTS	
	REMARKS	THE VALUE	THE VALUE IN MG/M3 IS APPROXIMATE.		
		TWA	50 PPM	USA. ACGIH THRESHOLD	
				LIMIT VALUES (TLV)	
		UPPER RES	SPIRATORY TRACT	IRRITATION	
		STEL	100 PPM	USA. ACGIH THRESHOLD	
			LIMIT VALUES (TLV)		
		UPPER RES	SPIRATORY TRACT	IRRITATION	
		STEL	100 PPM	CALIFORNIA PERMISSIBLE	
		532 MG/M3	EXPOSURE LIMITS FOR		
				CHEMICAL CONTAMINANTS	
		PEL	50 PPM	CALIFORNIA PERMISSIBLE	
			266 MG/M3	EXPOSURE LIMITS FOR	
				CHEMICAL CONTAMINANTS	

EXPOSURE CONTROLS

APPROPRIATE	HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL
ENGINEERING CONTROLS	HYGIENE AND SAFETY PRACTICE. WASH HANDS
	BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION	HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.
	SPLASH CONTACT MATERIAL: BUTYL-RUBBER MINIMUM LAYER THICKNESS: 0.3 MM BREAK THROUGH TIME: 60 MIN MATERIAL TESTED:BUTOJECT (KCL 897, SIZE M)
	IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.
BODY PROTECTION	IMPERVIOUS CLOTHING, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.
RESPIRATORY PROTECTION	WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).
CONTROL OF ENVIRONMENTAL EXPOSURE	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

	Calarlaga lignid
APPEARANCE ODOUR	Colorless liquid FRUITY
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING	
POINT/FREEZING POINT	
INITIAL BOILING POINT	
AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID,	NO DATA AVAILABLE
GAS)	
UPPER/LOWER	UPPER EXPLOSION LIMIT: 7.5 %(V)
FLAMMABILITY OR	LOWER EXPLOSION LIMIT: 1 %(V)
EXPLOSIVE LIMITS	
VAPOUR PRESSURE	4.5 HPA AT 20 C
VAPOUR DENSITY	4.5
RELATIVE DENSITY	
WATER SOLUBILITY	2 G/L AT 25 C
PARTITION COEFFICIENT:	LOG POW: 2.7 AT 35 C
N- OCTANOL/WATER	
AUTO-IGNITION	379 C AT 1,013.25 HPA
TEMPERATURE	
DECOMPOSITION	NO DATA AVAILABLE
TEMPERATURE	
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION

SOLUBILITY IN OTHER SOLVENTS RELATIVE VAPOUR DENSITY ALCOHOL - COMPLETELY MISCIBLE ETHER - COMPLETELY MISCIBLE 4.5

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.
CONDITIONS TO AVOID	HEAT, FLAMES AND SPARKS
INCOMPATIBLE MATERIALS	OXIDIZING AGENTS, STRONG ACIDS AND STRONG BASES, REDUCING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - CARBON OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	LD50 ORAL - RABBIT - 7,400 MG/KG
	REMARKS: (ECHA)

INHALATION: NO DATA AVAILABLE

LD50 DERMAL - RAT - > 5,000 MG/KG REMARKS: (RTECS)

NO DATA AVAILABLE

SKIN	SKIN RABBIT
CORROSION/IRRITATION	RESULT: NO SKIN IRRITATION - 4 H

SERIOUS EYEEYES - RABBITDAMAGE/EYE IRRITATIONRESULT: NO EYE IRRITATION - 24 H

RESPIRATORY OR SKINMAXIMISATION TEST - GUINEA PIG**SENSITISATION**RESULT: NEGATIVE

GERM CELL	AMES TEST
MUTAGENICITY	S. TYPHIMURIUM
	RESULT: NEGATIVE

MOUSE - MALE AND FEMALE - BONE MARROW RESULT: NEGATIVE

NO COMPONENT OF THIS PRODUCT PRESENT AT

CARCINOGENICITY IARC:

LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS PROBABLE, POSSIBLE OR
CONFIRMED HUMAN CARCINOGEN BY IARC.NTP:NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS A KNOWN OR ANTICIPATED
CARCINOGEN BY NTP.OSHA:NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON
OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN NO DATA AVAILABLE TOXICITY - SINGLE EXPOSURE

SPECIFIC TARGET ORGAN NO DATA AVAILABLE **TOXICITY - REPEATED EXPOSURE**

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION RTECS: NS9800000

CONTACT WITH EYES CAN CAUSE: REDNESS, BLURRED VISION, PROVOKES TEARS. SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING, DIZZINESS, DROWSINESS, COUGH, CHEST PAIN, DIFFICULTY IN BREATHING.

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY TOXICITY TO FISH	STATIC TEST LC50 - DANIO RERIO (ZEBRA FISH) - 22 - 46 MG/L - 96 H	
TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES	EC50 - DAPHNIA MAGNA STRAUS - 42 MG/L - 48 H (DIN 38412)	
TOXICITY TO ALGAE	STATIC TEST ERC50 - DESMODESMUS SUBSPICATUS (GREEN ALGAE) - > 100 MG/L - 72 H	
TOXICITY TO BACTERIA	NOEC - ACTIVATED SLUDGE - CA. 300 MG/L - 30 MIN	
PERSISTENCE AND DEGRADABILITY		
BIODEGRADABILITY	RESULT: - READILY BIODEGRADABLE.	
BIOACCUMULATIVE POTENTIAL	NO BIOACCUMULATION IS TO BE EXPECTED (LOG POW <= 4).	
MOBILITY IN SOIL	NO DATA AVAILABLE	

RESULTS OF PBT AND	PBT/VPVB ASSESSMENT NOT AVAILABLE AS
VPVB ASSESSMENT	CHEMICAL SAFETY ASSESSMENT NOT
	REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA
	CARE IN IGNITING AS THIS MATERIAL IS HIGHLY
	FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE
	SOLUTIONS TO A LICENSED DISPOSAL COMPANY.
	CONTACT A LICENSED PROFESSIONAL WASTE
	DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.
CONTRACTOR	

CONTAMINATEDDISPOSE OF AS UNUSED PRODUCT.PACKAGING

SECTION 14. TRANSPORT INFORMATION

DOT (US) PROPER SHIPPING NAME: UN NUMBER: CLASS: PACKING GROUP: REPORTABLE QUANTITY (RQ): POISON INHALATION HAZARD:	AMYL ACETATES N.O.S. (Isoamyl acetate) 1104 3 III 5000 LBS NO
IMDG PROPER SHIPPING NAME: UN NUMBER: CLASS: PACKING GROUP: EMS-NO:	AMYL ACETATES N.O.S. (Isoamyl acetate) 1104 3 III F-E, S-D
IATA PROPER SHIPPING NAME: UN NUMBER: CLASS: PACKING GROUP:	AMYL ACETATES N.O.S. (Isoamyl acetate) 1104 3 III

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS	NO CHEMICALS IN THIS M THE REPORTING REQUIRE SECTION 302.	
SARA 313 COMPONENTS	COMPONENTS WITH KNOW EXCEED THE THRESHOLD	
SARA 311/312 HAZARDS	FIRE HAZARD, CHRONIC H	,
MASSACHUSETTS RIGHT	FO KNOW COMPONENTS	
	CAS-NO.	REVISION DATE
Isoamyl acetate	123-92-2	02-16-1993
PENNSYLVANIA RIGHT TO KNOW COMPONENTS		
	CAS-NO.	REVISION DATE
Isoamyl acetate	123-92-2	02-16-1993

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. Isoamyl acetate 123-92-2 REVISION DATE 02-16-1993

CALIFORNIA PROP. 65 COMPONENTS

THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.H226FLAMMABLE LIQUID AND VAPOUR.

MSDS LEGEND	
MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENENTAL
	INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH
	ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)
IMPORTANT:	

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.1.

REVISION DATE: 01/27/2017