

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	34425
NAME:	Isobutyl acetate
SYNONYMS:	Acetic acid isobutyl ester
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
FLAMMABLE LIQUIDS (CATEGORY 2), H225
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), CENTRAL
NERVOUS SYSTEM, H336

ACUTE AQUATIC TOXICITY (CATEGORY 3), H402

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H336 MAY CAUSE DROWSINESS OR DIZZINESS.
H402 HARMFUL TO AQUATIC LIFE.

PRECAUTIONARY STATEMENT(S)

P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.
P233 KEEP CONTAINER TIGHTLY CLOSED.
P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241 USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/ LIGHTING/ EQUIPMENT.
P242 USE ONLY NON-SPARKING TOOLS.
P243 TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.
P261 AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA
P273 AVOID RELEASE TO THE ENVIRONMENT.
P280 WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE PROTECTION.
P303 + P361 + P353 IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER.
P304 + P340 + P312 IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.
P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.
P403 + P235 STORE IN A WELL-VENTILATED PLACE. KEEP COOL.
P405 STORE LOCKED UP.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

**HAZARDS NOT
OTHERWISE
CLASSIFIED (HNOC)
OR NOT COVERED
BY GHS**

REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: C₆H₁₂O₂
MW: 116.16
CAS-NO. 110-19-0
PURITY: 98 - 100% (GC)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Isobutyl acetate	FLAM. LIQ. 2; STOT SE 3; AQUATIC ACUTE 3; H225, H336, H402	90 - 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.

IN CASE OF SKIN CONTACT WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE CONTACT FLUSH EYES WITH WATER AS A PRECAUTION

IF SWALLOWED DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL NO DATA AVAILABLE

**ATTENTION AND
SPECIAL TREATMENT
NEEDED**

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

**SUITABLE
EXTINGUISHING MEDIA** USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY
CHEMICAL OR CARBON DIOXIDE.

**SPECIAL HAZARDS
ARISING FROM THE
SUBSTANCE OR MIXTURE** NO DATA AVAILABLE

**ADVICE FOR
FIREFIGHTERS** WEAR SELF CONTAINED BREATHING APPARATUS FOR
FIRE FIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES** USE PERSONAL PROTECTIVE EQUIPMENT. AVOID
BREATHING VAPOURS, MIST OR GAS. ENSURE
ADEQUATE VENTILATION. REMOVE ALL SOURCES OF
IGNITION. EVACUATE PERSONNEL TO SAFE AREAS.
BEWARE OF VAPOURS ACCUMULATING TO FORM
EXPLOSIVE CONCENTRATIONS. VAPOURS CAN
ACCUMULATE IN LOW AREAS.
FOR PERSONAL PROTECTION SEE SECTION 8.

**ENVIRONMENTAL
PRECAUTIONS** PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE
TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.
DISCHARGE INTO THE ENVIRONMENT MUST BE
AVOIDED.

**METHODS AND
MATERIALS FOR
CONTAINMENT AND
CLEANING UP** CONTAIN SPILLAGE, AND THEN COLLECT WITH AN
ELECTRICALLY PROTECTED VACUUM CLEANER OR BY
WET-BRUSHING AND PLACE IN CONTAINER FOR
DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE
SECTION 13).

**REFERENCE TO OTHER
SECTIONS** FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AVOID INHALATION OF VAPOUR OR MIST.
 USE EXPLOSION-PROOF EQUIPMENT.KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE.
 FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE.

Store at RT

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
Isobutyl acetate	110-19-0	TWA	150 PPM	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
	REMARKS	UPPER RESPIRATORY TRACT IRRITATION EYE IRRITATION ADOPTED VALUES OR NOTATIONS ENCLOSED ARE THOSE FOR WHICH CHANGES ARE PROPOSED IN THE NIC SEE NOTICE OF INTENDED CHANGES (NIC)		
		TWA	150 PPM 700 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		TWA	150 PPM 700 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		THE VALUE IN MG/M3 IS APPROXIMATE.		
		PEL	150 PPM 700 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS
		TWA	50 PPM	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		UPPER RESPIRATORY TRACT IRRITATION EYE IRRITATION		

		STEL	150 PPM	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		UPPER RESPIRATORY TRACT IRRITATION EYE IRRITATION		

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.4 MM

BREAK THROUGH TIME: 30 MIN

MATERIAL TESTED:CAMATRIL (KCL 730, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

IMPERVIOUS CLOTHING, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTIPURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear, colorless liquid
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	
INITIAL BOILING POINT AND BOILING RANGE	115 - 117 °C
FLASH POINT	16 °C
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	UPPER EXPLOSION LIMIT: 10.5 %(V) LOWER EXPLOSION LIMIT: 1.3 %(V)
VAPOUR PRESSURE	20 HPA (15 MMHG) AT 20 C
VAPOUR DENSITY	4.01 - (AIR = 1.0)
RELATIVE DENSITY	
WATER SOLUBILITY	5.6 G/L AT 20 C - SOLUBLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	LOG POW: 2.3 AT 25 C
AUTO-IGNITION TEMPERATURE	430 C AT 1,019 HPA (764 MMHG)
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION

SURFACE TENSION	62.5 MN/M AT 20 C
-----------------	-------------------

RELATIVE VAPOUR DENSITY 4.01 - (AIR = 1.0)

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.
CONDITIONS TO AVOID	HEAT, FLAMES AND SPARKS
INCOMPATIBLE MATERIALS	STRONG OXIDIZING AGENTS, STRONG BASES
HAZARDOUS DECOMPOSITION PRODUCTS	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - CARBON OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	LD50 ORAL - RAT - MALE - 13,413 MG/KG INHALATION: NO DATA AVAILABLE LD50 DERMAL - RABBIT - > 17,400 MG/KG NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	NO DATA AVAILABLE
SERIOUS EYE DAMAGE/EYE IRRITATION	NO DATA AVAILABLE
RESPIRATORY OR SKIN SENSITISATION	MAXIMISATION TEST - GUINEA PIG RESULT: DOES NOT CAUSE SKIN SENSITISATION.

GERM CELL MUTAGENICITY	HAMSTER LUNGS RESULT: NEGATIVE
CARCINOGENICITY	
IARC:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.
NTP:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.
OSHA:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.
REPRODUCTIVE TOXICITY	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	NO DATA AVAILABLE
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: AI4025000 TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	
TOXICITY TO FISH	LC50 - ORYZIAS LATIPES - 17 MG/L - 96 H
TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES	IMMOBILIZATION EC50 - DAPHNIA MAGNA (WATER FLEA) - 25 MG/L - 48 H
TOXICITY TO ALGAE	GROWTH INHIBITION EC50 - PSEUDOKIRCHNERIELLA SUBCAPITATA (GREEN ALGAE) - 370 MG/L - 72 H

PERSISTENCE AND DEGRADABILITY

BIODEGRADABILITY	AEROBIC - EXPOSURE TIME 20 D RESULT: 81 % - READILY BIODEGRADABLE.
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL HANDLING OR DISPOSAL. HARMFUL TO AQUATIC LIFE.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME:	ISOBUTYL ACETATE N.O.S. (Isobutyl acetate)
UN NUMBER:	1213
CLASS:	3
PACKING GROUP:	II
REPORTABLE QUANTITY (RQ):	5000 LBS
POISON INHALATION HAZARD:	NO

IMDG

PROPER SHIPPING NAME:	ISOBUTYL ACETATE N.O.S. (Isobutyl acetate)
UN NUMBER:	1213

CLASS: 3
PACKING GROUP: II
EMS-NO: F-E, S-D

IATA

PROPER SHIPPING NAME: ISOBUTYL ACETATE N.O.S. (Isobutyl acetate)
UN NUMBER: 1213
CLASS: 3
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313

SARA 311/312 HAZARDS FIRE HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Isobutyl acetate	110-19-0	03-01-2007

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Isobutyl acetate	110-19-0	03-01-2007

CALIFORNIA PROP. 65 COMPONENTS

THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

AQUATIC ACUTE	ACUTE AQUATIC TOXICITY
FLAM. LIQ.	FLAMMABLE LIQUIDS
H225	HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H336	MAY CAUSE DROWSINESS OR DIZZINESS.
H402	HARMFUL TO AQUATIC LIFE.
STOT SE	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

MSDS LEGEND

MW: MOLECULAR WEIGHT
MF: MOLECULAR FORMULA
VOC: VOLATILE ORGANIC COMPOUNDS
ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL
INDUSTRIAL HYGINISTS
CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH
ADMINISTRATION
PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.1.

REVISION DATE: 01/27/2017