# **Chem-Impex International Inc.**

Tel: (630) 766-2112 E-mail: <u>sales@chemimpex.com</u> Shipping and Correspondence: 935 Dillon Drive Wood Dale, IL 60191 USA

Fax: (630) 766-2218 Web site: <u>www.chemimpex.com</u> Manufacturing site: 825 Dillon Drive Wood Dale, IL 60191 USA

# SAFETY DATA SHEET

#### SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	34620
NAME:	Methyl hexanoate
SYNONYMS:	Hexanoic acid methyl ester Methyl caproate
24 HOUR EMERGENCY	(800) 535-5053(USA)
TELEPHONE:	352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

## SECTION 2. HAZARDS IDENTIFICATION

#### CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE LIQUIDS (CATEGORY 3), H226 ACUTE TOXICITY, INHALATION (CATEGORY 3), H331 FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD



HAZARD STATEMENT(S)	1	
U226	ГI	۸

HAZARD STATEMENT(S	,
H226	FLAMMABLE LIQUID AND VAPOUR.
H331	TOXIC IF INHALED.
PRECAUTIONARY STAT	
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT
	SURFACES NO SMOKING.
P233	KEEP CONTAINER TIGHTLY CLOSED.
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/
	LIGHTING EQUIPMENT.
P242	USE ONLY NON-SPARKING TOOLS.
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC
	DISCHARGE.
P261	AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/
	SPRAY.
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA
P280	WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE
	PROTECTION.
P303 + P361 + P353	IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY
	ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/
	SHOWER.
P304 + P340 + P311	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP
	COMFORTABLE FOR BREATHING. CALL A POISON
	CENTER/DOCTOR.
P370 + P378	IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR
	ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P403 + P233	STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER
	TIGHTLY CLOSED.
P403 + P235	STORE IN A WELL-VENTILATED PLACE. KEEP COOL.
P405	STORE LOCKED UP.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
	WASTE DISPOSAL PLANT.
HAZARDS NOT	NONE

HAZARDS NOT 1 OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:	$\mathrm{C_7H_{14}O_2}$
MW:	130.19
CAS-NO.	106-70-7
PURITY:	99 - 100% (GC)

## HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Methyl hexanoate		
	FLAM. LIQ. 3; ACUTE TOX. 3;	<= 100 %
	H226, H331	
FOR THE FULL TEX	T OF THE H-STATEMENTS MENTION	NED IN THIS SECTION SEE

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

# SECTION 4. FIRST-AID MEASURES

## **DESCRIPTION OF FIRST AID MEASURES**

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	WASH OFF WITH SOAP AND PLENTY OF WATER. TAKE VICTIM IMMEDIATELY TO HOSPITAL. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	FLUSH EYES WITH WATER AS A PRECAUTION
IF SWALLOWED	DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

# SECTION 5. FIRE AND EXPLOSION DATA

#### **EXTINGUISHING MEDIA**

SUITABLE EXTINGUISHING MEDIA	SUITABLE EXTINGUISHING MEDIA DRY POWDER DRY SAND
	UNSUITABLE EXTINGUISHING MEDIA DO NOT USE WATER JET.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	CARBON OXIDES
ADVICE FOR FIREFIGHTERS	WEAR SELF CONTAINED BREATHING APPARATUS FOR FIRE FIGHTING IF NECESSARY.
FURTHER INFORMATION	USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	WEAR RESPIRATORY PROTECTION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN ACCUMULATE IN LOW AREAS. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS METHODS AND	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. CONTAIN SPILLAGE, AND THEN COLLECT WITH NON-
MATERIALS FOR CONTAINMENT AND CLEANING UP	COMBUSTIBLE ABSORBENT MATERIAL, (E.G. SAND, EARTH, DIATOMACEOUS EARTH, VERMICULITE) AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL / NATIONAL REGULATIONS (SEE SECTION 13).
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

## SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	AVOID CONTACT WITH SKIN AND EYES. AVOID INHALATION OF VAPOUR OR MIST. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE. FOR PRECAUTIONS SEE SECTION 2.2.
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE.
SPECIFIC END USE(S)	APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **CONTROL PARAMETERS**

## **COMPONENTS WITH WORKPLACE CONTROL PARAMETERS** CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

#### **EXPOSURE CONTROLS**

APPROPRIATE	AVOID CONTACT WITH SKIN, EYES AND CLOTHING.
ENGINEERING	WASH HANDS BEFORE BREAKS AND IMMEDIATELY
CONTROLS	AFTER HANDLING THE PRODUCT.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYE/FACE PROTECTION** FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION	HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE''S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.
	FULL CONTACT MATERIAL: BUTYL-RUBBER MINIMUM LAYER THICKNESS: 0.3 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:BUTOJECT (KCL 897 , SIZE M)
	SPLASH CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.4 MM BREAK THROUGH TIME: 30 MIN MATERIAL TESTED:CAMATRIL (KCL 730, SIZE M)
	IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.
BODY PROTECTION	COMPLETE SUIT PROTECTING AGAINST CHEMICALS, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.
<b>RESPIRATORY</b> <b>PROTECTION</b>	WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).
CONTROL OF ENVIRONMENTAL EXPOSURE	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING	
POINT/FREEZING POINT	
INITIAL BOILING POINT	150 - 152 °C
AND BOILING RANGE	
FLASH POINT	45 °C
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID,	NO DATA AVAILABLE
GAS)	
UPPER/LOWER	NO DATA AVAILABLE
FLAMMABILITY OR	
EXPLOSIVE LIMITS	
VAPOUR PRESSURE	5 HPA AT 25 C
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT:	LOG POW: 2.34 - THE PRECEDING DATA, OR
N- OCTANOL/WATER	INTERPRETATION OF DATA, WAS DETERMINED USING
	QUANTITATIVE STRUCTURE ACTIVITY RELATIONSHIP
	(QSAR) MODELING.
AUTO-IGNITION	NO DATA AVAILABLE
TEMPERATURE	
DECOMPOSITION	NO DATA AVAILABLE
TEMPERATURE	
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

#### **OTHER SAFETY INFORMATION**

NO DATA AVAILABLE

# SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE

#### CONDITIONS TO AVOID HEAT, FLAMES AND SPARKS

INCOMPATIBLE STRONG OXIDIZING AGENTS MATERIALS

HAZARDOUSHAZARDOUS DECOMPOSITION PRODUCTS FORMEDDECOMPOSITIONUNDER FIRE CONDITIONS. - CARBON OXIDESPRODUCTSOTHER DECOMPOSITION PRODUCTS - NO DATA

OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

## SECTION 11. TOXICOLOGICAL INFORMATION

#### INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY NO DATA AVAILABLE

LC50 INHALATION - MOUSE - 4 H - 7 MG/L

LD50 DERMAL - GUINEA PIG - 5,000 MG/KG

NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.

NO DATA AVAILABLE

SKINSKIN - RATCORROSION/IRRITATIONRESULT: NO SKIN IRRITATION - 4 H

SERIOUS EYEEYES - RATDAMAGE/EYE IRRITATIONRESULT: NO EYE IRRITATION - 24 H

**RESPIRATORY OR SKIN**BUEHLER TEST - GUINEA PIG**SENSITISATION**RESULT: DOES NOT CAUSE SKIN SENSITISATION.

CARCINOGEN BY NTP.

GERM CELL NO DATA AVAILABLE MUTAGENICITY

CARCINOGENICITY IARC:

NTP:

OSHA:

**REPRODUCTIVE TOXICITY** NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	NO DATA AVAILABLE
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: MO8401400
	TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

## SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	NO DATA AVAILABLE
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

## SECTION 13. DISPOSAL CONSIDERATIONS

#### WASTE TREATMENT METHODS

**PRODUCT**OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS<br/>TO A LICENSED DISPOSAL COMPANY. BURN IN A<br/>CHEMICAL INCINERATOR EQUIPPED WITH AN<br/>AFTERBURNER AND SCRUBBER BUT EXERT EXTRA<br/>CARE IN IGNITING AS THIS MATERIAL IS HIGHLY<br/>FLAMMABLE.

## SECTION 14. TRANSPORT INFORMATION

DOT (US) PROPER SHIPPING NAME: UN NUMBER: CLASS: PACKING GROUP: REPORTABLE QUANTITY (RQ):	ESTERS, N.O.S. (Methyl hexanoate) 3272 3 III
POISON INHALATION	NO
HAZARD:	
IMDG PROPER SHIPPING NAME: UN NUMBER: CLASS: PACKING GROUP: EMS-NO:	ESTERS, N.O.S. (Methyl hexanoate) 3272 3 III F-E, S-D
IATA PROPER SHIPPING NAME: UN NUMBER: CLASS: PACKING GROUP:	ESTERS, N.O.S. (Methyl hexanoate) 3272 3 III

#### SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS	NO CHEMICALS IN THIS M THE REPORTING REQUIRE SECTION 302.	
SARA 313 COMPONENTS	COMPONENTS WITH KNOW EXCEED THE THRESHOLD	
SARA 311/312 HAZARDS	FIRE HAZARD	
MASSACHUSETTS RIGHT TO KNOW COMPONENTS	NO COMPONENTS ARE SUI MASSACHUSETTS RIGHT T	
PENNSYLVANIA RIGHT TO KNOW COMPONENTS CAS-NO. REVISION DATE		
Methyl hexanoate	106-70-7	

## NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. 106-70-7 **REVISION DATE** 

Methyl hexanoate

# SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.	
H226	FLAMMABLE LIQUID AND VAPOUR.
H331	TOXIC IF INHALED.

MSDS LEGEND		
MW:	MOLECULAR WEIGHT	
MF:	MOLECULAR FORMULA	
VOC:	VOLATILE ORGANIC COMPOUNDS	
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENENTAL	
	INDUSTRIAL HYGINISTS	
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER	
OSHA:	OCCUPATIONAL SAFETY AND HEALTH	
	ADMINISTRATION	
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)	
TLV:	THRESHOLD LIMIT VALUE (ACGIH)	
IMPORTANT:		
THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE		
BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO		
WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR		
IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY		
RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO		
DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR		
PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR		
DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT,		
INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.		
EVEN IF CII HAS BEEN ADVISEL	O OF THE POSSIBILITY OF SUCH DAMAGES.	

VERSION: 3.1.

REVISION DATE: 01/27/2017