Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 35272

NAME: Lead(II) nitrate

SYNONYMS:

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

OXIDIZING SOLIDS (CATEGORY 2), H272 ACUTE TOXICITY, ORAL (CATEGORY 4), H302 ACUTE TOXICITY, INHALATION (CATEGORY 4), H332 SERIOUS EYE DAMAGE (CATEGORY 1), H318 CARCINOGENICITY (CATEGORY 1B), H350 REPRODUCTIVE TOXICITY (CATEGORY 1A), H360 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (CATEGORY 1), BLOOD, CENTRAL NERVOUS SYSTEM, IMMUNE SYSTEM, KIDNEY, H372 SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 1), H400 LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 1), H410

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM







SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H272 MAY INTENSIFY FIRE; OXIDISER.

H302 + H332 HARMFUL IF SWALLOWED OR IF INHALED

H318 CAUSES SERIOUS EYE DAMAGE.

H350 MAY CAUSE CANCER.

H360 MAY DAMAGE FERTILITY OR THE UNBORN CHILD. H372 CAUSES DAMAGE TO ORGANS (BLOOD, CENTRAL

NERVOUS SYSTEM, IMMUNE SYSTEM, KIDNEY) THROUGH

PROLONGED OR REPEATED EXPOSURE.

H410 VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING

EFFECTS.

PRECAUTIONARY STATEMENT(S)

P201 OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

P202 DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE

BEEN READ AND UNDERSTOOD.

P210 KEEP AWAY FROM HEAT.

P220 KEEP/STORE AWAY FROM CLOTHING/ COMBUSTIBLE

MATERIALS.

P221 TAKE ANY PRECAUTION TO AVOID MIXING WITH

COMBUSTIBLES.

P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/

SPRAY.

P264 WASH SKIN THOROUGHLY AFTER HANDLING.

P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS

PRODUCT.

P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P273 AVOID RELEASE TO THE ENVIRONMENT.

P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE

PROTECTION/ FACE PROTECTION.

P301 + P312 + P330 IF SWALLOWED: CALL A POISON CENTER OR DOCTOR/

PHYSICIAN IF YOU FEEL UNWELL. RINSE MOUTH.

P304 + P340 + P312 IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP

COMFORTABLE FOR BREATHING. CALL A POISON CENTER

OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

P305 + P351 + P338 + IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

P310 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A

POISON CENTER OR DOCTOR/PHYSICIAN.

P308 + P313 IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/

ATTENTION.

P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR

ALCOHOL-RESISTANT FOAM TO EXTINGUISH.

P391 COLLECT SPILLAGE. P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT

OTHERWISE

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

NONE

MF: $Pb(NO_3)_2$

MW: 331.21

CAS-NO. 10099-74-8

PURITY: ≥ 99.995%

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Lead(II) nitrate		
	OX. SOL. 2; ACUTE TOX. 4; EYE DAM. 1; CARC. 1B; REPR. 1A; STOT RE 1; AQUATIC ACUTE 1; AQUATIC CHRONIC 1; H272, H302, H332, H318, H350, H360, H372, H400, H410 M-FACTOR - AQUATIC ACUTE: 10	<= 100%

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

WASH OFF WITH SOAP AND PLENTY OF WATER. IN CASE OF SKIN

CONTACT CONSULT A PHYSICIAN.

IN CASE OF EYE RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A PHYSICIAN. CONTACT

IF SWALLOWED NEVER GIVE ANYTHING BY MOUTH TO AN

UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER.

CONSULT A PHYSICIAN.

MOST IMPORTANT THE MOST IMPORTANT KNOWN SYMPTOMS AND SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

EFFECTS, BOTH ACUTE SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND

SPECIAL TREATMENT

NEEDED

AND DELAYED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE DRY POWDER DRY SAND

EXTINGUISHING MEDIA

SPECIAL HAZARDS NITROGEN OXIDES (NOX), LEAD OXIDES

ARISING FROM THE

SUBSTANCE OR MIXTURE

WEAR SELF-CONTAINED BREATHING APPARATUS FOR ADVICE FOR

FIREFIGHTERS FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL USE PERSONAL PROTECTIVE EOUIPMENT. AVOID PRECAUTIONS, DUST FORMATION. AVOID BREATHING VAPOURS, MIST

PROTECTIVE OR GAS. ENSURE ADEQUATE VENTILATION. EQUIPMENT AND EMERGENCY PROCEDURES

EVACUATE PERSONNEL TO SAFE AREAS. AVOID

BREATHING DUST.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP SWEEP UP AND SHOVEL. CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET- BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.

REFERENCE TO OTHER SECTIONS

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS.FURTHER PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE

ADDITIONAL PROCESSING OCCURS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED.KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.KEEP AWAY

FROM HEAT AND SOURCES OF IGNITION. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND

WELL-VENTILATED PLACE.

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2

NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS	
			PARAMETERS		
Lead(II) nitrate	10099-74-8	TWA	0.05 MG/M3	USA. ACGIH THRESHOLD LIMIT	
,				VALUES (TLV)	
	REMARKS	KS CENTRAL NERVOUS SYSTEM IMPAIRMENT			
		HEMATOLOGIC EFFECTS PERIPHERAL NERVOUS SYSTEM IMPAIRMENT SUBSTANCES FOR WHICH THERE IS A BIOLOGICAL EXPOSURE INDEX OR INDICES (SEE BEI SECTION)			
			CONFIRMED ANIMAL CARCINOGEN WITH UNKNOWN		
		RELEVANCE TO HUMANS			
		VARIES			
		PEL	0.05 MG/M3	OSHA SPECIFICALLY	
				REGULATED	
				CHEMICALS/CARCINOGENS	
			1910.1025		
			IF AN EMPLOYEE IS EXPOSED TO LEAD FOR MORE THAN 8		
		HOURS IN ANY WORK DAY, THE PERMISSIBLE EXPOSURE			
LIMIT, AS A TIME WEIGHTED AVERAGE					
	DAY, SHALL BE REDUCED ACCORDING TO THE				
FORMULA: MAXIMUM PERMISSIBLE LIMIT (I)=400 HOURS WORKED IN THE DAY THIS SEC					
				POSURE TO LEAD, EXCEPT AS	
				(A)(2). IT DOES NOT APPLY TO	
				STRY OR TO AGRICULTURAL	
		_	OPERATIONS COVERED BY 29 CFR PART 1928.		
			OSHA SPECIFICALLY REGULATED CARCINOGEN		
		TWA	0.05 MG/M3	USA. NIOSH RECOMMENDED	
				EXPOSURE LIMITS	
			SEE APPENDIX C		
		PEL	0.05	CALIFORNIA PERMISSIBLE	
			MG/M3	EXPOSURE LIMITS FOR	
				CHEMICAL CONTAMINANTS	
		SEE SECTION 5198			

EXPOSURE CONTROLS

APPROPRIATE HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL **ENGINEERING** HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE **CONTROLS** BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR **PROTECTION**

EYE PROTECTION TESTED AND APPROVED UNDER

APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH

(US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT
MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.
DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE White crystalline powder

ODOUR ODOURLESS

ODOUR THRESHOLD NO DATA AVAILABLE PH 3 - 4 AT 50 G/L AT 20 C

MELTING 470 °C (dec.)

POINT/FREEZING POINT INITIAL BOILING POINT AND BOILING RANGE

FLASH POINT

EVAPORATION RATE NO DATA AVAILABLE

FLAMMABILITY (SOLID, THE PRODUCT IS NOT FLAMMABLE. - FLAMMABILITY

GAS) (SOLIDS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE AT 20 C - OECD TEST GUIDELINE 104LOW

VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY

WATER SOLUBILITY 486 G/L AT 20 C - OECD TEST GUIDELINE 105

PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION 400 C - NF T 20-036

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE

OXIDIZING PROPERTIES THE SUBSTANCE OR MIXTURE IS CLASSIFIED AS

OXIDIZING WITH THE CATEGORY 2.

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS NO DATA AVAILABLE

CONDITIONS TO AVOID NO DATA AVAILABLE

INCOMPATIBLE MATERIALS

NO DATA AVAILABLE

HAZARDOUS DECOMPOSITION PRODUCTS HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - NITROGEN OXIDES (NOX),

LEAD OXIDES

OTHER DECOMPOSITION PRODUCTS - NO DATA

AVAILABLE

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY NO DATA AVAILABLE

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN CORROSION/IRRITATION

SKIN - IN VITRO STUDY RESULT: NON-CORROSIVE

(OECD TEST GUIDELINE 431) SKIN - IN VITRO STUDY

RESULT: NO SKIN IRRITATION (OECD TEST GUIDELINE 439)

SERIOUS EYE

EYES - IN VITRO STUDY

DAMAGE/EYE IRRITATION

RESULT: SEVERE IRRITATIONS - 4 H

(OECD TEST GUIDELINE 437)

RESPIRATORY OR SKIN

SENSITISATION

(IN ANALOGY TO SIMILAR PRODUCTS)

GERM CELL MUTAGENICITY NO DATA AVAILABLE

CARCINOGENICITY

IARC: 2A - GROUP 2A: PROBABLY CARCINOGENIC TO

HUMANS

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY MAY DAMAGE THE UNBORN CHILD. POSITIVE

EVIDENCE FROM HUMAN EPIDEMIOLOGICAL

STUDIES.

MAY DAMAGE FERTILITY. POSITIVE EVIDENCE FROM

HUMAN EPIDEMIOLOGICAL STUDIES.

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE EXPOSURE

ACUTE INHALATION TOXICITY - POSSIBLE

DAMAGES:, MUCOSAL IRRITATIONS

SPECIFIC TARGET ORGAN

TOXICITY - REPEATED

EXPOSURE

CAUSES DAMAGE TO ORGANS THROUGH

PROLONGED OR REPEATED EXPOSURE. - BLOOD, CENTRAL NERVOUS SYSTEM, IMMUNE SYSTEM,

KIDNEY

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL **INFORMATION**

RTECS: OG2100000

LEAD SALTS HAVE BEEN REPORTED TO CROSS THE PLACENTA AND TO INDUCE EMBRYO- AND FETOMORTALITY.

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

SYSTEMIC EFFECTS:

AFTER ABSORPTION:

AFTER A LATENCY PERIOD:

METALLIC TASTE, SALIVATION, VOMITING, DROP IN **BLOOD PRESSURE**

A LETHAL EFFECT IS POSSIBLE AFTER THE UPTAKE OF LARGE QUANTITIES.

THE FOLLOWING APPLIES TO LEAD COMPOUNDS IN GENERAL: DUE TO THE POOR ABSORBABILITY VIA THE GASTROINTESTINAL TRACT, ONLY VERY HIGH DOSES LEAD TO ACUTE CASES OF INTOXICATION. AFTER A LATENCY PERIOD OF SEVERAL HOURS, METALLIC TASTE, NAUSEA, VOMITING, AND COLICS OCCUR, IN MANY INSTANCES FOLLOWED BY SHOCK. CHRONIC UPTAKE CAUSES PERIPHERAL MUSCULAR WEAKNESS ("DROP-WRIST"), ANAEMIA, AND CENTRAL-NERVOUS DISORDERS. WOMEN OF CHILD-BEARING AGE SHOULD NOT BE EXPOSED TO THE SUBSTANCE OVER LONGER PERIODS OF TIME (OBSERVE CRITICAL THRESHOLD).

THE FOLLOWING APPLIES TO NITRITES/NITRATES IN GENERAL: METHAEMOGLOBINAEMIA AFTER THE UPTAKE OF LARGE QUANTITIES. OTHER DANGEROUS PROPERTIES CAN NOT BE EXCLUDED. THIS SUBSTANCE SHOULD BE HANDLED WITH PARTICULAR CARE.

STOMACH - IRREGULARITIES - BASED ON HUMAN **EVIDENCE**

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY

TOXICITY TO DAPHNIA AND OTHER AQUATIC

INVERTEBRATES TOXICITY TO ALGAE EC50 - DAPHNIA MAGNA (WATER FLEA) - 1.8 MG/L - 48

REMARKS: (ECOTOX DATABASE) EC50 - ALGAE - 0.024 - 0.029 MG/L - 28 H

REMARKS: (LIT.)

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL

NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS

AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL

HANDLING OR DISPOSAL.

VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING

EFFECTS.

DEPENDING ON THE CONCENTRATION, PHOSPHORUS AND/OR NITROGEN COMPOUNDS MAY CONTRIBUTE TO THE EUTROPHICATION OF DRINKING- WATER

SUPPLIES.

DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS

TO A LICENSED DISPOSAL COMPANY. BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND

SCRUBBER.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: LEAD NITRATE

UN NUMBER: 1469
CLASS: 5.1 (6.1)
PACKING GROUP: II
REPORTABLE QUANTITY 10 LBS

(RO):

MARINE POLLUTANT: YES POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: LEAD NITRATE

UN NUMBER: 1469
CLASS: 5.1 (6.1)
PACKING GROUP: II
EMS-NO: F-A, S-Q
MARINE POLLUTANT: YES

IATA

PROPER SHIPPING NAME: LEAD NITRATE

UN NUMBER: 1469 CLASS: 5.1 (6.1) PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THE FOLLOWING COMPONENTS ARE SUBJECT TO

REPORTING LEVELS ESTABLISHED BY SARA TITLE III,

SECTION 313:

CAS-NO. REVISION DATE

Lead(II) nitrate 10099-74-8 02-16-1993

SARA 311/312 HAZARDS

REACTIVITY HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Lead(II) nitrate 10099-74-8 02-16-1993

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H272 MAY INTENSIFY FIRE; OXIDISER.

H302 + H332 HARMFUL IF SWALLOWED OR IF INHALED

H318 CAUSES SERIOUS EYE DAMAGE.

H350 MAY CAUSE CANCER.

H360 MAY DAMAGE FERTILITY OR THE UNBORN CHILD.
H372 CAUSES DAMAGE TO ORGANS (BLOOD, CENTRAL
NERVOUS SYSTEM, IMMUNE SYSTEM, KIDNEY)
THROUGH PROLONGED OR REPEATED EXPOSURE.

VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING

EFFECTS.

MSDS LEGEND

H410

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION:3.1 REVISION DATE: 01/27/2017