Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 35278

NAME: Lithium fluoride anhydrous

SYNONYMS:

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

ACUTE TOXICITY, ORAL (CATEGORY 3), H301 SKIN IRRITATION (CATEGORY 2), H315 EYE IRRITATION (CATEGORY 2A), H319 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), RESPIRATORY SYSTEM, H335 FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H301 TOXIC IF SWALLOWED. H315 CAUSES SKIN IRRITATION.

H319 CAUSES SERIOUS EYE IRRITATION. H335 MAY CAUSE RESPIRATORY IRRITATION.

PRECAUTIONARY STATEMENT(S)

P261 AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/

SPRAY.

P264 WASH SKIN THOROUGHLY AFTER HANDLING. P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS

PRODUCT.

P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P280 WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE

PROTECTION.

P301 + P310 IF SWALLOWED: IMMEDIATELY CALL A POISON CENTER OR

DOCTOR/PHYSICIAN.

P302 + P352 IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER. P304 + P340 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT

REST IN A POSITION COMFORTABLE FOR BREATHING.

P305 + P351 + P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING.

P312 CALL A POISON CENTER OR DOCTOR/ PHYSICIAN IF YOU

FEEL UNWELL.

P321 SPECIFIC TREATMENT (SEE SUPPLEMENTAL FIRST AID

INSTRUCTIONS ON THIS LABEL).

P330 RINSE MOUTH.

P332 + P313 IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/

ATTENTION.

P337 + P313 IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/

ATTENTION.

P362 TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE

REUSE.

P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER

TIGHTLY CLOSED.

P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT CONTACT WITH ACIDS LIBERATES VERY TOXIC GAS.

OTHERWISE WEAK HYDROGEN FLUORIDE-RELEASER

CLASSIFIED (HNOC)

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: LiF

MW: 25.94

CAS-NO. 7789-24-4

PURITY: ≥ 99.5%

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION					
Lithium fluoride anhydrous							
	ACUTE TOX. 3; SKIN IRRIT. 2;	<= 100%					
	EYE IRRIT. 2A; STOT SE 3;						
	H301, H315, H319, H335						

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE

CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.HYDROFLUORIC (HF) ACID BURNS REQUIRE IMMEDIATE AND SPECIALIZED FIRST AID AND MEDICAL TREATMENT. SYMPTOMS MAY BE DELAYED UP TO 24 HOURS DEPENDING ON THE CONCENTRATION OF HF. AFTER DECONTAMINATION WITH WATER, FURTHER DAMAGE CAN OCCUR DUE TO PENETRATION/ABSORPTION OF THE FLUORIDE ION. TREATMENT SHOULD BE DIRECTED TOWARD BINDING THE FLUORIDE ION AS WELL AS THE EFFECTS OF EXPOSURE. SKIN EXPOSURES CAN BE TREATED WITH A 2.5% CALCIUM GLUCONATE GEL REPEATED UNTIL BURNING CEASES. MORE SERIOUS SKIN EXPOSURES MAY REQUIRE SUBCUTANEOUS CALCIUM GLUCONATE EXCEPT FOR DIGITAL AREAS UNLESS THE PHYSICIAN IS EXPERIENCED IN THIS TECHNIQUE, DUE TO THE POTENTIAL FOR TISSUE INJURY FROM INCREASED PRESSURE. ABSORPTION CAN READILY OCCUR THROUGH THE SUBUNGUAL AREAS AND SHOULD BE

CONSIDERED WHEN UNDERGOING

DECONTAMINATION. PREVENTION OF ABSORPTION OF THE FLUORIDE ION IN CASES OF INGESTION CAN BE OBTAINED BY GIVING MILK, CHEWABLE CALCIUM CARBONATE TABLETS OR MILK OF MAGNESIA TO CONSCIOUS VICTIMS. CONDITIONS SUCH AS

HYPOCALCEMIA, HYPOMAGNESEMIA AND CARDIAC ARRHYTHMIAS SHOULD BE MONITORED FOR, SINCE

THEY CAN OCCUR AFTER EXPOSURE.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN WASH OFF WITH SOAP AND PLENTY OF WATER. TAKE

CONTACT VICTIM IMMEDIATELY TO HOSPITAL. CONSULT A

PHYSICIAN.FIRST TREATMENT WITH CALCIUM

GLUCONATE PASTE.

IN CASE OF EYE RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

IF SWALLOWED NEVER GIVE ANYTHING BY MOUTH TO AN

UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER.

CONSULT A PHYSICIAN.

MOST IMPORTANT

SYMPTOMS AND

EFFECTS, BOTH ACUTE

AND DELAYED

CONTACT

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND

ATTENTION AND SPECIAL TREATMENT

NEEDED

SUITABLE

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

EXTINGUISHING MEDIA

DRY POWDER

SPECIAL HAZARDS

ARISING FROM THE

SUBSTANCE OR MIXTURE

HYDROGEN FLUORIDE, LITHIUM OXIDES

NOT COMBUSTIBLE.

ADVICE FOR

WEAR SELF-CONTAINED BREATHING APPARATUS FOR

FIREFIGHTERS FIREFIGHTING IF NECESSARY.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES

WEAR RESPIRATORY PROTECTION. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP PICK UP AND ARRANGE DISPOSAL WITHOUT CREATING DUST. SWEEP UP AND SHOVEL. DO NOT FLUSH WITH WATER. KEEP IN SUITABLE, CLOSED

CONTAINERS FOR DISPOSAL.

REFERENCE TO OTHER SECTIONS

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

AVOID CONTACT WITH SKIN AND EYES. AVOID

FORMATION OF DUST AND AEROSOLS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT

PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND

WELL-VENTILATED PLACE.

ANY INCOMPATIBILITIES NEVER ALLOW PRODUCT TO GET IN CONTACT WITH

WATER DURING STORAGE. DO NOT STORE NEAR

ACIDS. KEEP IN A DRY PLACE.

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS	
			PARAMETERS		
Lithium fluoride	7789-24-4	TWA	2.5 MG/M3	USA. OCCUPATIONAL	
anhydrous				EXPOSURE LIMITS	
				(OSHA) - TABLE Z-1	
				LIMITS FOR AIR	
				CONTAMINANTS	
	REMARKS	CAS NUMBER VARIES WITH COMPOUND			
		TWA	2.5 MG/M3	USA. ACGIH THRESHOLD	
				LIMIT VALUES (TLV)	
		BONE DAMAGE			
		FLUOROSIS			
		SUBSTANCES FOR WHICH THERE IS A BIOLOGICAL			
		EXPOSURE INDEX OR INDICES (SEE BEI SECTION)			
		NOT CLASSIFIABLE AS A HUMAN CARCINOGEN			
		VARIES			
		PEL	2.5 MG/M3	CALIFORNIA	
				PERMISSIBLE EXPOSURE	
				LIMITS FOR CHEMICAL	
				CONTAMINANTS	

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS

COMPONENT	CAS-NO.	PARAMETERS	VALUE	BIOLOGICAL	BASIS
				SPECIMEN	
Lithium fluoride	7789-24-4	FLUORIDE	2 MG/L	URINE	ACGIH -
anhydrous					BIOLOGICAL
					EXPOSURE
					INDICES (BEI)
	REMARKS	PRIOR TO SHIF	T (16 HOU	RS AFTER EXP	OSURE CEASES)
		FLUORIDE	3 MG/L	URINE	ACGIH -
					BIOLOGICAL
					EXPOSURE
					INDICES (BEI)
		END OF SHIFT (AS SOON AS POSSIBLE AFTER EXPOSURE			
		CEASES)			

EXPOSURE CONTROLS

APPROPRIATE AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH **ENGINEERING** HANDS BEFORE BREAKS AND IMMEDIATELY AFTER

CONTROLS HANDLING THE PRODUCT.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR

PROTECTION EYE PROTECTION TESTED AND APPROVED UNDER

APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH

(US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER

SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER

FROM EN 374, CONTACT THE SUPPLIER OF THE CE

APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY

ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE

SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING

AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE White powder

ODOUR NO DATA AVAILABLE
ODOUR THRESHOLD NO DATA AVAILABLE
PH 7.0 - 8.5 AT 0.26 G/L AT 25 C

MELTING 845 °C

POINT/FREEZING POINT

INITIAL BOILING POINT 1673 °C

AND BOILING RANGE

FLASH POINT

EVAPORATION RATE NO DATA AVAILABLE

FLAMMABILITY (SOLID, THE PRODUCT IS NOT FLAMMABLE.

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY 2.64

WATER SOLUBILITY CA.0.3 G/L AT 20 C PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION NO DATA AVAILABLE

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS

NO DATA AVAILABLE

CONDITIONS TO AVOID AVOID MOISTURE.

INCOMPATIBLE MATERIALS

STRONG OXIDIZING AGENTS, STRONG ACIDS

HAZARDOUS DECOMPOSITION PRODUCTS HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - HYDROGEN FLUORIDE,

LITHIUM OXIDES

REACTS WITH WATER TO FORM: - HYDROGEN

FLUORIDE

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY LD50 ORAL - RAT - 143 MG/KG

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN NO DATA AVAILABLE

CORROSION/IRRITATION

SERIOUS EYE NO DATA AVAILABLE

DAMAGE/EYE IRRITATION

RESPIRATORY OR SKIN NO DATA AVAILABLE

SENSITISATION

GERM CELL NO DATA AVAILABLE MUTAGENICITY

CARCINOGENICITY THIS PRODUCT IS OR CONTAINS A COMPONENT THAT

IS NOT CLASSIFIABLE AS TO ITS CARCINOGENICITY

BASED ON ITS IARC, ACGIH, NTP, OR EPA

CLASSIFICATION.

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY

LITHIUM AND ITS COMPOUNDS ARE POSSIBLE TERATOGENS BY ANALOGY TO LITHIUM CARBONATE WHICH HAS EQUIVOCAL HUMAN TERATOGENIC DATA AND POSITIVE ANIMAL TERATOGENIC DATA.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE INHALATION - MAY CAUSE RESPIRATORY IRRITATION.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE NO DATA AVAILABLE

ASPIRATION HAZARD

NO DATA AVAILABLE

ADDITIONAL INFORMATION

RTECS: NOT AVAILABLE

FLUORIDE ION CAN REDUCE SERUM CALCIUM LEVELS POSSIBLY CAUSING FATAL HYPOCALCEMIA.

CYANOSIS AND T-WAVE INVERSION HAVE OCCURRED IN THE BREAST-FED INFANTS OF WOMEN RECEIVING LITHIUM CARBONATE THERAPY. LITHIUM AND ITS COMPOUNDS ARE POSSIBLE TERATOGENS BY ANALOGY TO LITHIUM CARBONATE WHICH HAS EQUIVOCAL HUMAN TERATOGENIC DATA AND POSITIVE ANIMAL TERATOGENIC DATA. BURNING SENSATION, COUGH, WHEEZING, LARYNGITIS. SHORTNESS OF BREATH, HEADACHE, NAUSEA, VOMITING, LARGE DOSES OF LITHIUM ION HAVE CAUSED DIZZINESS AND PROSTRATION, AND CAN CAUSE KIDNEY DAMAGE IF SODIUM INTAKE IS LIMITED. DEHYDRATION, WEIGHT LOSS, DERMATOLOGICAL EFFECTS, AND THYROID DISTURBANCES HAVE BEEN REPORTED. CENTRAL NERVOUS SYSTEM EFFECTS THAT INCLUDE SLURRED SPEECH, BLURRED VISION, SENSORY LOSS, ATAXIA, AND CONVULSIONS MAY OCCUR. DIARRHEA, VOMITING, AND NEUROMUSCULAR EFFECTS SUCH AS TREMOR, CLONUS, AND HYPERACTIVE REFLEXES MAY OCCUR AS A RESULT OF REPEATED EXPOSURE TO LITHIUM ION. TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS

CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS

TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN

AFTERBURNER AND SCRUBBER.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: TOXIC SOLID, INORGANIC, N.O.S. (LITHIUM FLUORIDE

ANHYDROUS)

UN NUMBER: 3288
CLASS: 6.1
PACKING GROUP: III
POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: TOXIC SOLID, INORGANIC, N.O.S. (LITHIUM FLUORIDE

ANHYDROUS)

UN NUMBER: 3288
CLASS: 6.1
PACKING GROUP: III
EMS-NO: F-A, S-A

IATA

PROPER SHIPPING NAME: TOXIC SOLID, INORGANIC, N.O.S. (LITHIUM FLUORIDE

ANHYDROUS)

UN NUMBER: 3288 CLASS: 6.1 PACKING GROUP: III

SECTION 15. REGULATORY INFORMATION

302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL

COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DEMINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT NO COMPONENTS ARE SUBJECT TO THE TO KNOW COMPONENTS MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Lithium fluoride anhydrous 7789-24-4 06-01-2008

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Lithium fluoride anhydrous 7789-24-4 06-01-2008

CALIFORNIA PROP. 65

COMPONENTS

THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER,

BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE

HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H301 TOXIC IF SWALLOWED. H315 CAUSES SKIN IRRITATION. H319 CAUSES SERIOUS EYE IRRITATION. H335 MAY CAUSE RESPIRATORY IRRITATION.

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION:3.1 REVISION DATE: 01/27/2017