

Chem-Impex International Inc.

Tel: (630) 766-2112

E-mail: sales@chemimpex.com

Shipping and Correspondence:

935 Dillon Drive

Wood Dale, IL 60191 USA

Fax: (630) 766-2218

Web site: www.chemimpex.com

Manufacturing site:

825 Dillon Drive

Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 35416

NAME: Barium manganate

SYNONYMS:

24 HOUR EMERGENCY TELEPHONE: (800) 535-5053(USA)
352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE: (630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

OXIDIZING SOLIDS (CATEGORY 2), H272

ACUTE TOXICITY, ORAL (CATEGORY 4), H302

ACUTE TOXICITY, INHALATION (CATEGORY 4), H332

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H272 MAY INTENSIFY FIRE; OXIDISER.
H302 + H332 HARMFUL IF SWALLOWED OR IF INHALED.

PRECAUTIONARY STATEMENT(S)

P210 KEEP AWAY FROM HEAT.
P220 KEEP/STORE AWAY FROM CLOTHING/ COMBUSTIBLE MATERIALS.
P221 TAKE ANY PRECAUTION TO AVOID MIXING WITH COMBUSTIBLES.
P261 AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.
P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P280 WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE PROTECTION.
P301 + P312 + P330 IF SWALLOWED: CALL A POISON CENTER OR DOCTOR/ PHYSICIAN IF YOU FEEL UNWELL. RINSE MOUTH.
P304 + P340 + P312 IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.
P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: BaMnO₄

MW: 256.26

CAS-NO. 7787-35-1

PURITY: $\geq 90\%$

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Barium manganate	OX. SOL. 2; ACUTE TOX. 4; H272, H302, H332	$\leq 100\%$

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.

IN CASE OF SKIN CONTACT WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE CONTACT FLUSH EYES WITH WATER AS A PRECAUTION.

IF SWALLOWED NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

**SUITABLE
EXTINGUISHING MEDIA** DRY POWDER DRY SAND

**SPECIAL HAZARDS
ARISING FROM THE
SUBSTANCE OR MIXTURE** BARIUM OXIDE, MANGANESE/MANGANESE OXIDES

**ADVICE FOR
FIREFIGHTERS** WEAR SELF-CONTAINED BREATHING APPARATUS FOR
FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES** USE PERSONAL PROTECTIVE EQUIPMENT. AVOID
DUST FORMATION. AVOID BREATHING VAPOURS, MIST
OR GAS. ENSURE ADEQUATE VENTILATION.
EVACUATE PERSONNEL TO SAFE AREAS. AVOID
BREATHING DUST. FOR PERSONAL PROTECTION SEE
SECTION 8.

**ENVIRONMENTAL
PRECAUTIONS** DO NOT LET PRODUCT ENTER DRAINS.

**METHODS AND
MATERIALS FOR
CONTAINMENT AND
CLEANING UP** SWEEP UP AND SHOVEL. CONTAIN SPILLAGE, AND
THEN COLLECT WITH AN ELECTRICALLY PROTECTED
VACUUM CLEANER OR BY WET-BRUSHING AND PLACE
IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL
REGULATIONS (SEE SECTION 13). KEEP IN SUITABLE,
CLOSED CONTAINERS FOR DISPOSAL.

**REFERENCE TO OTHER
SECTIONS** FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE
HANDLING** AVOID CONTACT WITH SKIN AND EYES. AVOID
FORMATION OF DUST AND AEROSOLS. FURTHER
PROCESSING OF SOLID MATERIALS MAY RESULT IN
THE FORMATION OF COMBUSTIBLE DUSTS. THE
POTENTIAL FOR COMBUSTIBLE DUST FORMATION
SHOULD BE TAKEN INTO CONSIDERATION BEFORE
ADDITIONAL PROCESSING OCCURS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED.KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.KEEP AWAY FROM HEAT AND SOURCES OF IGNITION.
FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE.
MOISTURE SENSITIVE. KEEP IN A DRY PLACE.

Store at RT

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2
NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
Barium manganate	7787-35-1	C	5 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
	REMARKS	CEILING LIMIT IS TO BE DETERMINED FROM BREATHING-ZONE AIR SAMPLES.		
		TWA	0.1 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		CENTRAL NERVOUS SYSTEM IMPAIRMENT NOT CLASSIFIABLE AS A HUMAN CARCINOGEN VARIES		
		TWA	0.02 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		CENTRAL NERVOUS SYSTEM IMPAIRMENT NOT CLASSIFIABLE AS A HUMAN CARCINOGEN VARIES		
		TWA	1 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		ST	3 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		PEL	0.2 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS (TITLE 8, ARTICLE 107)

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

SAFETY GLASSES WITH SIDE-SHIELDS CONFORMING TO EN166 USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Light blue to dark blue powder
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	
INITIAL BOILING POINT AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	4.85
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	THE SUBSTANCE OR MIXTURE IS CLASSIFIED AS OXIDIZING WITH THE CATEGORY 2.

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	AVOID MOISTURE.
INCOMPATIBLE MATERIALS	ACIDS, REDUCING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - BARIUM OXIDE, MANGANESE/MANGANESE OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	NO DATA AVAILABLE INHALATION: NO DATA AVAILABLE DERMAL: NO DATA AVAILABLE NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	NO DATA AVAILABLE
SERIOUS EYE DAMAGE/EYE IRRITATION	NO DATA AVAILABLE
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE
GERM CELL MUTAGENICITY	NO DATA AVAILABLE

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE NO DATA AVAILABLE

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION RTECS: NOT AVAILABLE

MEN EXPOSED TO MANGANESE DUSTS SHOWED A DECREASE IN FERTILITY. CHRONIC MANGANESE POISONING PRIMARILY INVOLVES THE CENTRAL NERVOUS SYSTEM. EARLY SYMPTOMS INCLUDE LANGUOR, SLEEPINESS AND WEAKNESS IN THE LEGS. A STOLID MASK-LIKE APPEARANCE OF THE FACE, EMOTIONAL DISTURBANCES SUCH AS UNCONTROLLABLE LAUGHTER AND A SPASTIC GAIT WITH TENDENCY TO FALL IN WALKING ARE FINDINGS IN MORE ADVANCED CASES. HIGH INCIDENCE OF PNEUMONIA HAS BEEN FOUND IN WORKERS EXPOSED TO THE DUST OR FUME OF SOME MANGANESE COMPOUNDS.

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

TOXICITY	NO DATA AVAILABLE
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)	
PROPER SHIPPING NAME:	OXIDIZING SOLID, N.O.S. (Barium manganate)
UN NUMBER:	1479
CLASS:	5.1
PACKING GROUP:	II
REPORTABLE QUANTITY (RQ):	
POISON INHALATION HAZARD:	NO
IMDG	
PROPER SHIPPING NAME:	OXIDIZING SOLID, N.O.S. (Barium manganate)

UN NUMBER: 1479
CLASS: 5.1
PACKING GROUP: II
EMS-NO: F-A, S-Q
MARINE POLLUTANT : YES

IATA

PROPER SHIPPING NAME: OXIDIZING SOLID, N.O.S. (Barium manganate)
UN NUMBER: 1479
CLASS: 5.1
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS THE FOLLOWING COMPONENTS ARE SUBJECT TO REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:

	CAS-NO.	REVISION DATE
Barium manganate	7787-35-1	07/08/2015

SARA 311/312 HAZARDS REACTIVITY HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Barium manganate	7787-35-1	07/08/2015

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H272	MAY INTENSIFY FIRE; OXIDISER.
H302 + H332	HARMFUL IF SWALLOWED OR IF INHALED.

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL
HYGINISTS
CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION: 3.1.

REVISION DATE: 01/27/2017