

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	35635
NAME:	Lithium fluoride
SYNONYMS:	Fluorolithium
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
ACUTE TOXICITY, ORAL (CATEGORY 3), H301
SKIN IRRITATION (CATEGORY 2), H315
EYE IRRITATION (CATEGORY 2A), H319
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3),
RESPIRATORY SYSTEM, H335

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H301 TOXIC IF SWALLOWED.
H315 CAUSES SKIN IRRITATION.
H319 CAUSES SERIOUS EYE IRRITATION.
H335 MAY CAUSE RESPIRATORY IRRITATION.

PRECAUTIONARY STATEMENT(S)

P261 AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/
SPRAY.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS
PRODUCT.
P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P280 WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE
PROTECTION.
P301 + P310 IF SWALLOWED: IMMEDIATELY CALL A POISON CENTER OR
DOCTOR/ PHYSICIAN.
P302 + P352 IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.
P304 + P340 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT
REST IN A POSITION COMFORTABLE FOR BREATHING.
P305 + P351 + P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL
MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND
EASY TO DO. CONTINUE RINSING.
P312 CALL A POISON CENTER OR DOCTOR/ PHYSICIAN IF YOU
FEEL UNWELL.
P321 SPECIFIC TREATMENT (SEE SUPPLEMENTAL FIRST AID
INSTRUCTIONS ON THIS LABEL).
P330 RINSE MOUTH.
P332 + P313 IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/
ATTENTION.
P337 + P313 IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/
ATTENTION.
P362 TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE
REUSE.
P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER
TIGHTLY CLOSED.
P405 STORE LOCKED UP.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
WASTE DISPOSAL PLANT.

**HAZARDS NOT
OTHERWISE
CLASSIFIED (HNOC)**

CONTACT WITH ACIDS LIBERATES VERY TOXIC GAS.
WEAK HYDROGEN FLUORIDE-RELEASER

**OR NOT COVERED
BY GHS**

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: LiF
MW: 25.94
CAS-NO. 7789-24-4
PURITY: $\geq 99\%$ AT

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Lithium fluoride		
	ACUTE TOX. 3; SKIN IRRIT. 2; EYE IRRIT. 2A; STOT SE 3; H301, H315, H319, H335	$\leq 100\%$

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE

CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT OF DANGEROUS AREA. HYDROFLUORIC (HF) ACID BURNS REQUIRE IMMEDIATE AND SPECIALIZED FIRST AID AND MEDICAL TREATMENT. SYMPTOMS MAY BE DELAYED UP TO 24 HOURS DEPENDING ON THE CONCENTRATION OF HF. AFTER DECONTAMINATION WITH WATER, FURTHER DAMAGE CAN OCCUR DUE TO PENETRATION/ABSORPTION OF THE FLUORIDE ION. TREATMENT SHOULD BE DIRECTED TOWARD BINDING THE FLUORIDE ION AS WELL AS THE EFFECTS OF EXPOSURE. SKIN EXPOSURES CAN BE TREATED WITH A 2.5% CALCIUM GLUCONATE GEL REPEATED UNTIL BURNING CEASES. MORE SERIOUS SKIN EXPOSURES MAY REQUIRE SUBCUTANEOUS CALCIUM GLUCONATE EXCEPT FOR DIGITAL AREAS UNLESS THE PHYSICIAN IS EXPERIENCED IN THIS TECHNIQUE, DUE TO THE POTENTIAL FOR TISSUE INJURY FROM INCREASED PRESSURE. ABSORPTION CAN READILY OCCUR THROUGH THE SUBUNGUAL AREAS AND SHOULD BE

CONSIDERED WHEN UNDERGOING DECONTAMINATION. PREVENTION OF ABSORPTION OF THE FLUORIDE ION IN CASES OF INGESTION CAN BE OBTAINED BY GIVING MILK, CHEWABLE CALCIUM CARBONATE TABLETS OR MILK OF MAGNESIA TO CONSCIOUS VICTIMS. CONDITIONS SUCH AS HYPOCALCEMIA, HYPOMAGNESEMIA AND CARDIAC ARRHYTHMIAS SHOULD BE MONITORED FOR, SINCE THEY CAN OCCUR AFTER EXPOSURE.

IF INHALED

IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.

IN CASE OF SKIN CONTACT

WASH OFF WITH SOAP AND PLENTY OF WATER. TAKE VICTIM IMMEDIATELY TO HOSPITAL. CONSULT A PHYSICIAN. FIRST TREATMENT WITH CALCIUM GLUCONATE PASTE.

IN CASE OF EYE CONTACT

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

IF SWALLOWED

NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA

DRY POWDER

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

HYDROGEN FLUORIDE, LITHIUM OXIDES
NOT COMBUSTIBLE.

ADVICE FOR FIREFIGHTERS

WEAR SELF-CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	WEAR RESPIRATORY PROTECTION. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	PICK UP AND ARRANGE DISPOSAL WITHOUT CREATING DUST. SWEEP UP AND SHOVEL. DO NOT FLUSH WITH WATER. KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2.
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. NEVER ALLOW PRODUCT TO GET IN CONTACT WITH WATER DURING STORAGE. DO NOT STORE NEAR ACIDS. KEEP IN A DRY PLACE. Store at RT
SPECIFIC END USE(S)	APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
Lithium fluoride	7789-24-4	TWA	2.5 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
	REMARKS	CAS NUMBER VARIES WITH COMPOUND		
		TWA	2.5 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		BONE DAMAGE FLUOROSIS SUBSTANCES FOR WHICH THERE IS A BIOLOGICAL EXPOSURE INDEX OR INDICES (SEE BEI SECTION) NOT CLASSIFIABLE AS A HUMAN CARCINOGEN VARIES		
		PEL	2.5 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS

COMPONENT	CAS-NO.	PARAMETERS	VALUE	BIOLOGICAL SPECIMEN	BASIS
Lithium fluoride	7789-24-4	FLUORIDE	2 MG/L	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
	REMARKS	PRIOR TO SHIFT (16 HOURS AFTER EXPOSURE CEASES)			
		FLUORIDE	3 MG/L	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
		END OF SHIFT (AS SOON AS POSSIBLE AFTER EXPOSURE CEASES)			

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH HANDS BEFORE BREAKS AND IMMEDIATELY AFTER HANDLING THE PRODUCT.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	White powder
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	7.0 - 8.5 AT 0.26 G/L AT 25 C
MELTING POINT/FREEZING POINT	845 °C
INITIAL BOILING POINT AND BOILING RANGE	1673 °C
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	THE PRODUCT IS NOT FLAMMABLE.
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	2.64
WATER SOLUBILITY	CA.0.3 G/L AT 20 C
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE
OTHER SAFETY INFORMATION	NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	AVOID MOISTURE.
INCOMPATIBLE MATERIALS	STRONG OXIDIZING AGENTS, STRONG ACIDS

**HAZARDOUS
DECOMPOSITION
PRODUCTS**

HAZARDOUS DECOMPOSITION PRODUCTS FORMED
UNDER FIRE CONDITIONS. - HYDROGEN FLUORIDE,
LITHIUM OXIDES
REACTS WITH WATER TO FORM: - HYDROGEN
FLUORIDE
IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY

LD50 ORAL - RAT - 143 MG/KG

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

**SKIN
CORROSION/IRRITATION**

NO DATA AVAILABLE

**SERIOUS EYE
DAMAGE/EYE IRRITATION**

NO DATA AVAILABLE

**RESPIRATORY OR SKIN
SENSITISATION**

NO DATA AVAILABLE

**GERM CELL
MUTAGENICITY**

NO DATA AVAILABLE

CARCINOGENICITY

THIS PRODUCT IS OR CONTAINS A COMPONENT THAT
IS NOT CLASSIFIABLE AS TO ITS CARCINOGENICITY
BASED ON ITS IARC, ACGIH, NTP, OR EPA
CLASSIFICATION.

IARC:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS PROBABLE, POSSIBLE OR
CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS A KNOWN OR ANTICIPATED
CARCINOGEN BY NTP.

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON
OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY	LITHIUM AND ITS COMPOUNDS ARE POSSIBLE TERATOGENS BY ANALOGY TO LITHIUM CARBONATE WHICH HAS EQUIVOCAL HUMAN TERATOGENIC DATA AND POSITIVE ANIMAL TERATOGENIC DATA.
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	INHALATION - MAY CAUSE RESPIRATORY IRRITATION.
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	NO DATA AVAILABLE
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	<p>RTECS: NOT AVAILABLE</p> <p>FLUORIDE ION CAN REDUCE SERUM CALCIUM LEVELS POSSIBLY CAUSING FATAL HYPOCALCEMIA.</p> <p>CYANOSIS AND T-WAVE INVERSION HAVE OCCURRED IN THE BREAST-FED INFANTS OF WOMEN RECEIVING LITHIUM CARBONATE THERAPY. LITHIUM AND ITS COMPOUNDS ARE POSSIBLE TERATOGENS BY ANALOGY TO LITHIUM CARBONATE WHICH HAS EQUIVOCAL HUMAN TERATOGENIC DATA AND POSITIVE ANIMAL TERATOGENIC DATA. BURNING SENSATION, COUGH, WHEEZING, LARYNGITIS, SHORTNESS OF BREATH, HEADACHE, NAUSEA, VOMITING, LARGE DOSES OF LITHIUM ION HAVE CAUSED DIZZINESS AND PROSTRATION, AND CAN CAUSE KIDNEY DAMAGE IF SODIUM INTAKE IS LIMITED. DEHYDRATION, WEIGHT LOSS, DERMATOLOGICAL EFFECTS, AND THYROID DISTURBANCES HAVE BEEN REPORTED. CENTRAL NERVOUS SYSTEM EFFECTS THAT INCLUDE SLURRED SPEECH, BLURRED VISION, SENSORY LOSS, ATAXIA, AND CONVULSIONS MAY OCCUR. DIARRHEA, VOMITING, AND NEUROMUSCULAR EFFECTS SUCH AS TREMOR, CLONUS, AND HYPERACTIVE REFLEXES MAY OCCUR AS A RESULT OF REPEATED EXPOSURE TO LITHIUM ION. TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.</p> <p>STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE</p>

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	NO DATA AVAILABLE
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)	
PROPER SHIPPING NAME:	TOXIC SOLID, INORGANIC, N.O.S. (LITHIUM FLUORIDE ANHYDROUS)
UN NUMBER:	3288
CLASS:	6.1
PACKING GROUP:	III
POISON INHALATION HAZARD:	NO
IMDG	

PROPER SHIPPING NAME: TOXIC SOLID, INORGANIC, N.O.S. (LITHIUM FLUORIDE ANHYDROUS)
UN NUMBER: 3288
CLASS: 6.1
PACKING GROUP: III
EMS-NO: F-A, S-A

IATA
PROPER SHIPPING NAME: TOXIC SOLID, INORGANIC, N.O.S. (LITHIUM FLUORIDE ANHYDROUS)
UN NUMBER: 3288
CLASS: 6.1
PACKING GROUP: III

SECTION 15. REGULATORY INFORMATION

302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DEMINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Lithium fluoride	7789-24-4	06-01-2008

NEW JERSEY RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Lithium fluoride	7789-24-4	06-01-2008

CALIFORNIA PROP. 65 COMPONENTS THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.
H301 TOXIC IF SWALLOWED.
H315 CAUSES SKIN IRRITATION.

H319
H335

CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE RESPIRATORY IRRITATION.

MSDS LEGEND

MW: MOLECULAR WEIGHT
MF: MOLECULAR FORMULA
VOC: VOLATILE ORGANIC COMPOUNDS
ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL
HYGINISTS
CAS: CHEMICAL ABSTRACTS SERVICE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION:3.1

REVISION DATE: 01/27/2017