

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 35645

NAME: Lithium perchlorate

SYNONYMS:

24 HOUR EMERGENCY TELEPHONE: (800) 535-5053(USA)
352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE: (630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
OXIDIZING SOLIDS (CATEGORY 2), H272
SKIN IRRITATION (CATEGORY 2), H315
EYE IRRITATION (CATEGORY 2A), H319
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3),
RESPIRATORY SYSTEM, H335

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD

DANGER

HAZARD STATEMENT(S)

H272 MAY INTENSIFY FIRE; OXIDIZER.
H315 CAUSES SKIN IRRITATION.
H319 CAUSES SERIOUS EYE IRRITATION.
H335 MAY CAUSE RESPIRATORY IRRITATION.

PRECAUTIONARY STATEMENT(S)

P210 KEEP AWAY FROM HEAT.
P220 KEEP/STORE AWAY FROM CLOTHING/ COMBUSTIBLE MATERIALS.
P221 TAKE ANY PRECAUTION TO AVOID MIXING WITH COMBUSTIBLES.
P261 AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P280 WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE PROTECTION.
P302 + P352 IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.
P304 + P340 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING.
P305 + P351 + P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.
P312 CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.
P321 SPECIFIC TREATMENT (SEE SUPPLEMENTAL FIRST AID INSTRUCTIONS ON THIS LABEL).
P332 + P313 IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ ATTENTION.
P337 + P313 IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ ATTENTION.
P362 TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE.
P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.
P405 STORE LOCKED UP.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

**HAZARDS NOT
OTHERWISE
CLASSIFIED (HNOC)**

NONE

**OR NOT COVERED
BY GHS**

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: LiClO₄
MW: 106.39
CAS-NO. 7791-03-9
PURITY: ≥99.99% Metals basis

HAZARDOUS COMPONENTS

| COMPONENT | CLASSIFICATION | CONCENTRATION |
|----------------------------|--|---------------|
| Lithium perchlorate | | |
| | OX. SOL. 2; ACUTE TOX. 4; SKIN IRRIT. 2; EYE IRRIT. 2A; STOT SE 3; H272, H302, H315, H319, H335 | ≤ 100 % |

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.

IN CASE OF SKIN CONTACT WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE CONTACT RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

IF SWALLOWED NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA

USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

HYDROGEN CHLORIDE GAS, LITHIUM OXIDES

ADVICE FOR FIREFIGHTERS

WEAR SELF CONTAINED BREATHING APPARATUS FOR FIRE FIGHTING IF NECESSARY.

FURTHER INFORMATION

USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

USE PERSONAL PROTECTIVE EQUIPMENT. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

SWEEP UP AND SHOVEL. CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WETBRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.

REFERENCE TO OTHER SECTIONS FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED.KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.KEEP AWAY FROM HEAT AND SOURCES OF IGNITION. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE.
HYGROSCOPIC.
Store at RT

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION SAFETY GLASSES WITH SIDE-SHIELDS CONFORMING TO EN166 USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

**SKIN
PROTECTION**

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

**BODY
PROTECTION**

IMPERVIOUS CLOTHING, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

**RESPIRATORY
PROTECTION**

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

**CONTROL OF
ENVIRONMENTAL
EXPOSURE**

DO NOT LET PRODUCT ENTER DRAINS.

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|--------------------------------|
| APPEARANCE | White crystals |
| ODOUR | NO DATA AVAILABLE |
| ODOUR THRESHOLD | NO DATA AVAILABLE |
| PH | 6.0 - 9.5 AT 106.4 G/L AT 25 C |
| MELTING POINT/FREEZING POINT | 236 °C (Approx.) |
| INITIAL BOILING POINT AND BOILING RANGE | 430 °C |
| FLASH POINT | |
| EVAPORATION RATE | NO DATA AVAILABLE |
| FLAMMABILITY (SOLID, GAS) | NO DATA AVAILABLE |
| UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS | NO DATA AVAILABLE |
| VAPOUR PRESSURE | NO DATA AVAILABLE |
| VAPOUR DENSITY | NO DATA AVAILABLE |
| RELATIVE DENSITY | 2.42 |
| WATER SOLUBILITY | CA.106.4 G/L AT 20 C |
| PARTITION COEFFICIENT: N- OCTANOL/WATER | NO DATA AVAILABLE |
| AUTO-IGNITION TEMPERATURE | NO DATA AVAILABLE |
| DECOMPOSITION TEMPERATURE | NO DATA AVAILABLE |
| VISCOSITY | NO DATA AVAILABLE |
| EXPLOSIVE PROPERTIES | NO DATA AVAILABLE |
| OXIDIZING PROPERTIES | NO DATA AVAILABLE |
| OTHER SAFETY INFORMATION | NO DATA AVAILABLE |

SECTION 10. STABILITY AND REACTIVITY

| | |
|---|--|
| REACTIVITY | NO DATA AVAILABLE |
| CHEMICAL STABILITY | STABLE UNDER RECOMMENDED STORAGE CONDITIONS. |
| POSSIBILITY OF HAZARDOUS REACTIONS | NO DATA AVAILABLE |
| CONDITIONS TO AVOID | AVOID MOISTURE. |
| INCOMPATIBLE MATERIALS | ORGANIC MATERIALS, POWDERED METALS |

**HAZARDOUS
DECOMPOSITION
PRODUCTS**

HAZARDOUS DECOMPOSITION PRODUCTS FORMED
UNDER FIRE CONDITIONS. - HYDROGEN CHLORIDE
GAS, LITHIUM OXIDES
OTHER DECOMPOSITION PRODUCTS - NO DATA
AVAILABLE
IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY

NO DATA AVAILABLE

INHALATION: IRRITATING TO RESPIRATORY SYSTEM.

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

**SKIN
CORROSION/IRRITATION**

NO DATA AVAILABLE

**SERIOUS EYE
DAMAGE/EYE IRRITATION**

NO DATA AVAILABLE

**RESPIRATORY OR SKIN
SENSITISATION**

NO DATA AVAILABLE

**GERM CELL
MUTAGENICITY**

NO DATA AVAILABLE

CARCINOGENICITY

IARC:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED
HUMAN CARCINOGEN BY IARC

ACGIH:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS A CARCINOGEN OR POTENTIAL
CARCINOGEN BY ACGIH.

NTP:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS A KNOWN OR ANTICIPATED
CARCINOGEN BY NTP.

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON
OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY

NO DATA AVAILABLE

| | |
|---|--|
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE | MAY CAUSE RESPIRATORY IRRITATION. ACUTE INHALATION TOXICITY - IRRITATION SYMPTOMS IN THE RESPIRATORY TRACT. |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | NO DATA AVAILABLE |
| ASPIRATION HAZARD | NO DATA AVAILABLE |
| ADDITIONAL INFORMATION | <p>RTECS: NOT AVAILABLE</p> <p>LARGE DOSES OF LITHIUM ION HAVE CAUSED DIZZINESS AND PROSTRATION, AND CAN CAUSE KIDNEY DAMAGE IF SODIUM INTAKE IS LIMITED. DEHYDRATION, WEIGHT LOSS, DERMATOLOGICAL EFFECTS, AND THYROID DISTURBANCES HAVE BEEN REPORTED. CENTRAL NERVOUS SYSTEM EFFECTS THAT INCLUDE SLURRED SPEECH, BLURRED VISION, SENSORY LOSS, ATAXIA, AND CONVULSIONS MAY OCCUR. DIARRHEA, VOMITING, AND NEUROMUSCULAR EFFECTS SUCH AS TREMOR, CLONUS, AND HYPERACTIVE REFLEXES MAY OCCUR AS A RESULT OF REPEATED EXPOSURE TO LITHIUM ION., TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.</p> <p>THE FOLLOWING APPLIES TO LITHIUM COMPOUNDS IN GENERAL: WHEN HANDLED OR USED INAPPROPRIATELY, THE ABSORPTION OF LARGE QUANTITIES IS FOLLOWED BY CNS DISORDERS, AGITATION, SPASMS, ATAXIA (IMPAIRED LOCOMOTOR COORDINATION) DUE TO DISTURBED ELECTROLYTE BALANCE. OTHER DANGEROUS PROPERTIES CAN NOT BE EXCLUDED. HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE.</p> |

SECTION 12. ECOLOGICAL INFORMATION

| | |
|-------------------------|---|
| TOXICITY TO FISH | LC50 - LEUCISCUS IDUS (GOLDEN ORFE) - 1,850 MG/L - 48 H REMARKS: (REFERRED TO THE ANION) |
|-------------------------|---|

| | |
|--|---|
| TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES TOXICITY TO ALGAE | EC50 - DAPHNIA MAGNA (WATER FLEA) - 1,077 MG/L - 24 H REMARKS: (REFERRED TO THE ANION) IC5 - M.AERUGINOSA - 79 MG/L - 8 D REMARKS: (REFERRED TO THE ANION) IC5 - SCENEDESMUS QUADRICAUDA (GREEN ALGAE) - 360 MG/L - 7 D REMARKS: (REFERRED TO THE ANION) |
| PERSISTENCE AND DEGRADABILITY | NO DATA AVAILABLE |
| BIOACCUMULATIVE POTENTIAL | NO DATA AVAILABLE |
| MOBILITY IN SOIL | NO DATA AVAILABLE |
| RESULTS OF PBT AND VPVB ASSESSMENT | PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED |
| OTHER ADVERSE EFFECTS | FURTHER INFORMATION ON ECOLOGY AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL HANDLING OR DISPOSAL. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED. |

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

| | |
|-----------------------------------|--|
| PRODUCT | BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. |
| CONTAMINATED PACKAGING | DISPOSE OF AS UNUSED PRODUCT. |

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: PERCHLORATES, INORGANIC, N.O.S.
UN NUMBER: 1481
CLASS: 5.1
PACKING GROUP: II
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: PERCHLORATES, INORGANIC, N.O.S.
UN NUMBER: 1481
CLASS: 5.1
PACKING GROUP: II
EMS-NO: F-H, S-Q

IATA

PROPER SHIPPING NAME: PERCHLORATES, INORGANIC, N.O.S.
UN NUMBER: 1481
CLASS: 5.1
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS

REACTIVITY HAZARD, ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

| | CAS-NO. | REVISION DATE |
|---------------------|-----------|---------------|
| LITHIUM PERCHLORATE | 7791-03-9 | |

NEW JERSEY RIGHT TO KNOW COMPONENTS

| | CAS-NO. | REVISION DATE |
|---------------------|-----------|---------------|
| LITHIUM PERCHLORATE | 7791-03-9 | |

CALIFORNIA PROP. 65 COMPONENTS

THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

| | |
|------|-----------------------------------|
| H272 | MAY INTENSIFY FIRE; OXIDIZER. |
| H315 | CAUSES SKIN IRRITATION. |
| H319 | CAUSES SERIOUS EYE IRRITATION. |
| H335 | MAY CAUSE RESPIRATORY IRRITATION. |

MSDS LEGEND

| | |
|--------|--|
| MW: | MOLECULAR WEIGHT |
| MF: | MOLECULAR FORMULA |
| VOC: | VOLATILE ORGANIC COMPOUNDS |
| ACGIH: | AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS |
| CAS: | CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER |
| OSHA: | OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION |
| PEL: | PERMISSIBLE EXPOSURE LIMIT (OSHA) |
| TLV: | THRESHOLD LIMIT VALUE (ACGIH) |

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION: 3.1.

REVISION DATE: 01/27/2017