

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 35783
NAME: Rubidium chromate
SYNONYMS:
24 HOUR EMERGENCY TELEPHONE: (800) 535-5053(USA)
352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS: (800) 869-9290
CUSTOMER SERVICE: (630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
OXIDIZING SOLIDS (CATEGORY 2), H272
SKIN SENSITISATION (CATEGORY 1), H317
CARCINOGENICITY (CATEGORY 1B), H350

SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 1), H400
LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 1), H410

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H272 MAY INTENSIFY FIRE; OXIDISER.
H317 MAY CAUSE AN ALLERGIC SKIN REACTION.
H350 MAY CAUSE CANCER.
H410 VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT(S)

P201 OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.
P202 DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.
P210 KEEP AWAY FROM HEAT.
P220 KEEP/STORE AWAY FROM CLOTHING/ COMBUSTIBLE MATERIALS.
P221 TAKE ANY PRECAUTION TO AVOID MIXING WITH COMBUSTIBLES.
P261 AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
P272 CONTAMINATED WORK CLOTHING MUST NOT BE ALLOWED OUT OF THE WORKPLACE.
P273 AVOID RELEASE TO THE ENVIRONMENT.
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.
P302 + P352 IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.
P308 + P313 IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ ATTENTION.
P333 + P313 IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ ATTENTION.
P363 WASH CONTAMINATED CLOTHING BEFORE REUSE.
P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM TO EXTINGUISH.
P391 COLLECT SPILLAGE.
P405 STORE LOCKED UP.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: Rb₂CrO₄
MW: 286.93
CAS-NO. 13446-72-5
PURITY: ≥14.5 - 21.7 % Chromium

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Rubidium chromate		
	OX. SOL. 2; SKIN SENS. 1; CARC. 1B; AQUATIC ACUTE 1; AQUATIC CHRONIC 1; H272, H317, H350, H400, H410 M-FACTOR - AQUATIC ACUTE: 10	<= 100%

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.

IN CASE OF SKIN CONTACT WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE CONTACT FLUSH EYES WITH WATER AS A PRECAUTION.

IF SWALLOWED NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

EFFECTS, BOTH ACUTE AND DELAYED SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA DRY POWDER DRY SAND

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE RUBIDIUM OXIDES, CHROMIUM OXIDES

ADVICE FOR FIREFIGHTERS WEAR SELF-CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES USE PERSONAL PROTECTIVE EQUIPMENT. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST. FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP SWEEP UP AND SHOVEL. CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET- BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.

REFERENCE TO OTHER SECTIONS FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS.FURTHER PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE ADDITIONAL PROCESSING OCCURS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED.KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.KEEP AWAY FROM HEAT AND SOURCES OF IGNITION. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE.
KEEP IN A DRY PLACE.

Store at RT

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
	REMARKS	SEE TABLE Z-2 FOR THE EXPOSURE LIMIT FOR ANY OPERATIONS OR SECTORS WHERE THE EXPOSURE LIMIT IN 1910.1026 IS STAYED OR IS OTHERWISE NOT IN EFFECT SUBSTANCE LISTED; FOR MORE INFORMATION SEE OSHA DOCUMENT 1910.1026		
Rubidium chromate	13446-72-5	CEIL	1MG/10M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-2

		Z37.7-1971 THIS STANDARD APPLIES TO ANY OPERATIONS OR SECTORS FOR WHICH THE EXPOSURE LIMIT IN THE CHROMIUM (VI) STANDARD, SEC. 1910.1026, IS STAYED OR IS OTHERWISE NOT IN EFFECT.		
		TWA	0.0002 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		DERMAL SENSITIZATION RESPIRATORY SENSITIZATION RESPIRATORY TRACT IRRITATION SINONASAL CANCER LUNG CANCER ASTHMA 2018 ADOPTION CONFIRMED HUMAN CARCINOGEN DANGER OF CUTANEOUS ABSORPTION VARIES		
		STEL	0.0005 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		DERMAL SENSITIZATION RESPIRATORY SENSITIZATION RESPIRATORY TRACT IRRITATION SINONASAL CANCER LUNG CANCER ASTHMA 2018 ADOPTION CONFIRMED HUMAN CARCINOGEN DANGER OF CUTANEOUS ABSORPTION VARIES		
		PEL	0.005 MG/M3	OSHA SPECIFICALLY REGULATED CHEMICALS/CARCINOGENS
		1910.1026 THIS STANDARD APPLIES TO OCCUPATIONAL EXPOSURES TO CHROMIUM (VI) IN ALL FORMS AND COMPOUNDS IN GENERAL INDUSTRY, EXCEPT: (A) EXPOSURES THAT OCCUR IN THE APPLICATION OF PESTICIDES REGULATED BY THE ENVIRONMENTAL PROTECTION AGENCY OR ANOTHER FEDERAL GOVERNMENT AGENCY (E.G., THE TREATMENT OF WOOD WITH PRESERVATIVES); (B) EXPOSURES TO PORTLAND CEMENT; OR (C) WHERE THE EMPLOYER HAS OBJECTIVE DATA DEMONSTRATING THAT A MATERIAL CONTAINING CHROMIUM OR A SPECIFIC PROCESS, OPERATION, OR ACTIVITY INVOLVING CHROMIUM CANNOT RELEASE DUSTS, FUMES, OR MISTS OF CHROMIUM (VI) IN CONCENTRATIONS AT OR ABOVE 0.5 GM/M3 AS AN 8-HOUR TIME-WEIGHTED AVERAGE (TWA) UNDER ANY EXPECTED CONDITIONS OF USE. CHROMIUM (VI) [HEXAVALENT CHROMIUM OR CR(VI)] MEANS CHROMIUM WITH A VALENCE OF POSITIVE SIX, IN ANY FORM AND IN ANY COMPOUND OSHA SPECIFICALLY REGULATED CARCINOGEN		

		TWA	0.0002 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		POTENTIAL OCCUPATIONAL CARCINOGEN SEE APPENDIX C SEE APPENDIX A		
		PEL	0.005 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS
		SEE SECTIONS 1532.2, 5206 & 8359		
		C	0.1 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS
		SEE SECTIONS 1532.2, 5206 & 8359		

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS

COMPONENT	CAS-NO.	PARAMETERS	VALUE	BIOLOGICAL SPECIMEN	BASIS
Rubidium chromate	13446-72-5	TOTAL CHROMIUM	25 G/L	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
	REMARKS	END OF SHIFT AT END OF WORKWEEK			
		TOTAL CHROMIUM	10 G/L	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
		INCREASE DURING SHIFT			

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

BODY PROTECTION	COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.
RESPIRATORY PROTECTION	WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).
CONTROL OF ENVIRONMENTAL EXPOSURE	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Yellow to yellow-green
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	
INITIAL BOILING POINT AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	3.52
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	THE SUBSTANCE OR MIXTURE IS CLASSIFIED AS OXIDIZING WITH THE CATEGORY 2.

**OTHER SAFETY
INFORMATION**

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	NO DATA AVAILABLE
INCOMPATIBLE MATERIALS	STRONG REDUCING AGENTS, ACIDS
HAZARDOUS DECOMPOSITION PRODUCTS	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - RUBIDIUM OXIDES, CHROMIUM OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	NO DATA AVAILABLE INHALATION: NO DATA AVAILABLE DERMAL: NO DATA AVAILABLE NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	NO DATA AVAILABLE
SERIOUS EYE DAMAGE/EYE IRRITATION	NO DATA AVAILABLE
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE

GERM CELL MUTAGENICITY	NO DATA AVAILABLE
CARCINOGENICITY	PRESUMED TO HAVE CARCINOGENIC POTENTIAL FOR HUMANS
IARC:	1 - GROUP 1: CARCINOGENIC TO HUMANS
NTP:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.
OSHA:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.
REPRODUCTIVE TOXICITY	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	NO DATA AVAILABLE
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: NOT AVAILABLE EXPOSURE TO CHROMATE SALTS HAS BEEN REPORTED TO PRODUCE SKIN AND NASAL ULCERATIONS WITH CONTINUED EXPOSURE LEADING TO PERFORATION OF THE NASAL SEPTA, COUGH, SHORTNESS OF BREATH, HEADACHE, NAUSEA, VOMITING STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	NO DATA AVAILABLE
PERSISTENCE AND DEGRADABILITY	
BIODEGRADABILITY	RESULT: - NOT READILY BIODEGRADABLE.
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE

**RESULTS OF PBT AND
VPVB ASSESSMENT**

PBT/VPVB ASSESSMENT NOT AVAILABLE AS
CHEMICAL SAFETY ASSESSMENT NOT
REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS

AN ENVIRONMENTAL HAZARD CANNOT BE
EXCLUDED IN THE EVENT OF UNPROFESSIONAL
HANDLING OR DISPOSAL.
VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING
EFFECTS.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT

OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS
TO A LICENSED DISPOSAL COMPANY. BURN IN A
CHEMICAL INCINERATOR EQUIPPED WITH AN
AFTERBURNER AND SCRUBBER BUT EXERT EXTRA
CARE IN IGNITING AS THIS MATERIAL IS HIGHLY
FLAMMABLE. CONTACT A LICENSED PROFESSIONAL
WASTE DISPOSAL SERVICE TO DISPOSE OF THIS
MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A
COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL
INCINERATOR EQUIPPED WITH AN AFTERBURNER AND
SCRUBBER.

**CONTAMINATED
PACKAGING**

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: OXIDIZING SOLID, N.O.S. (Rubidium chromate)
UN NUMBER: 1479
CLASS: 5.1
PACKING GROUP: II
REPORTABLE QUANTITY
(RQ):
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: OXIDIZING SOLID, N.O.S. (Rubidium chromate)
UN NUMBER: 1479
CLASS: 5.1
PACKING GROUP: II

EMS-NO: F-A, S-Q
MARINE POLLUTANT: YES

IATA

PROPER SHIPPING NAME: OXIDIZING SOLID, N.O.S. (Rubidium chromate)
UN NUMBER: 1479
CLASS: 5.1
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS THE FOLLOWING COMPONENTS ARE SUBJECT TO REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:

	CAS-NO.	REVISION DATE
Rubidium chromate	13446-72-5	04/24/1993

SARA 311/312 HAZARDS REACTIVITY HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
Rubidium chromate	13446-72-5	04/24/1993

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H272 MAY INTENSIFY FIRE; OXIDISER.
H317 MAY CAUSE AN ALLERGIC SKIN REACTION.
H350 MAY CAUSE CANCER.
H410 VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

MSDS LEGEND

MW: MOLECULAR WEIGHT
MF: MOLECULAR FORMULA
VOC: VOLATILE ORGANIC COMPOUNDS
ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS

CAS: CHEMICAL ABSTRACTS SERVICE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION: 3.1

REVISION DATE: 01/27/2017