

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	35924
NAME:	Tin(II) chloride
SYNONYMS:	Stannous chloride Dichlorotin
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

CORROSIVE TO METALS (CATEGORY 1), H290

ACUTE TOXICITY, ORAL (CATEGORY 4), H302
 ACUTE TOXICITY, INHALATION (CATEGORY 4), H332
 SKIN CORROSION (CATEGORY 1B), H314
 SERIOUS EYE DAMAGE (CATEGORY 1), H318
 SKIN SENSITISATION (CATEGORY 1), H317
 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3),
 RESPIRATORY SYSTEM, H335
 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE, ORAL (CATEGORY 2),
 CARDIO-VASCULAR SYSTEM, H373
 SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 2), H401
 LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 3), H412

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
 PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H290 MAY BE CORROSIVE TO METALS.
 H302 + H332 HARMFUL IF SWALLOWED OR IF INHALED.
 H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
 H317 MAY CAUSE AN ALLERGIC SKIN REACTION.
 H335 MAY CAUSE RESPIRATORY IRRITATION.
 H373 MAY CAUSE DAMAGE TO ORGANS (CARDIO-VASCULAR SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE IF SWALLOWED.
 H401 TOXIC TO AQUATIC LIFE.
 H412 HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT(S)

P234 KEEP ONLY IN ORIGINAL CONTAINER.
 P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
 P264 WASH SKIN THOROUGHLY AFTER HANDLING.
 P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.
 P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
 P272 CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.
 P273 AVOID RELEASE TO THE ENVIRONMENT.
 P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.
 P301 + P312 + P330 IF SWALLOWED: CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL. RINSE MOUTH.
 P301 + P330 + P331 IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING.
 P303 + P361 + P353 IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER.

P304 + P340 + P310	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A POISON CENTER/DOCTOR.
P305 + P351 + P338 + P310	IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A POISON CENTER/DOCTOR.
P314 P333 + P313	GET MEDICAL ADVICE/ ATTENTION IF YOU FEEL UNWELL. IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ ATTENTION.
P363 P390 P403 + P233	WASH CONTAMINATED CLOTHING BEFORE REUSE. ABSORB SPILLAGE TO PREVENT MATERIAL DAMAGE. STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.
P405 P406	STORE LOCKED UP. STORE IN CORROSIVE RESISTANT CONTAINER WITH A RESISTANT INNER LINER.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.
HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS	NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:	SnCl ₂
MW:	189.62
CAS-NO.	7772-99-8
PURITY:	≥99.99% Metals basis

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Tin(II) chloride	MET. CORR. 1; ACUTE TOX. 4; SKIN CORR. 1B; EYE DAM. 1; SKIN SENS. 1; STOT SE 3; STOT RE 2; AQUATIC ACUTE 2; AQUATIC CHRONIC 3; H290, H302, H332, H314, H318, H317, H335, H373, H401, H412 M-FACTOR - AQUATIC CHRONIC: 10	<= 100%

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	TAKE OFF CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.CONTINUE RINSING EYES DURING TRANSPORT TO HOSPITAL.
IF SWALLOWED	DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY CHEMICAL OR CARBON DIOXIDE.
-------------------------------------	--

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	HYDROGEN CHLORIDE GAS, TIN/TIN OXIDES NOT COMBUSTIBLE.
ADVICE FOR FIREFIGHTERS	WEAR SELF-CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.
FURTHER INFORMATION	NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	WEAR RESPIRATORY PROTECTION. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	PICK UP AND ARRANGE DISPOSAL WITHOUT CREATING DUST. SWEEP UP AND SHOVEL. KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS. FURTHER PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE ADDITIONAL PROCESSING OCCURS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2.
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE.

MOISTURE SENSITIVE. STORE UNDER INERT GAS.

Store at RT

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2
NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
Tin(II) chloride	7772-99-8	TWA	2 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		TWA	2 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
	REMARKS	PNEUMOCONIOSIS (OR STANNOSIS) ADOPTED VALUES OR NOTATIONS ENCLOSED ARE THOSE FOR WHICH CHANGES ARE PROPOSED IN THE NIC SEE NOTICE OF INTENDED CHANGES (NIC) VARIES		
		TWA	2 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		TWA	2 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	White to off-white powder
ODOUR	ODOURLESS
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	2.18 AT 20 °C
MELTING POINT/FREEZING POINT	246 °C
INITIAL BOILING POINT AND BOILING RANGE	652 °C
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	THE PRODUCT IS NOT FLAMMABLE.
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	33 HPA AT CA.429 °C
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	3.95
WATER SOLUBILITY	CA.178 G/L AT 20 °C - COMPLETELY SOLUBLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NOT APPLICABLE FOR INORGANIC SUBSTANCES
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE
OTHER SAFETY INFORMATION	NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	AVOID MOISTURE.

INCOMPATIBLE MATERIALS	STRONG BASES, STRONG OXIDIZING AGENTS, SODIUM/SODIUM OXIDES, POTASSIUM, HYDROGEN PEROXIDE, BROMINE TRIFLUORIDE, HYDRAZINE, HALIDES, STRONG REDUCING AGENTS, CALCIUM ACETYLIDE
HAZARDOUS DECOMPOSITION PRODUCTS	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - HYDROGEN CHLORIDE GAS, TIN/TIN OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	LD50 ORAL - RAT - MALE - 1,910 MG/KG LC50 INHALATION - RAT - MALE AND FEMALE - 4 H - 2 MG/L REMARKS: CALCULATION METHOD INHALATION: CORROSIVE TO RESPIRATORY SYSTEM. DERMAL: NO DATA AVAILABLE NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	SKIN RABBIT RESULT: CORROSIVE - 4 H
SERIOUS EYE DAMAGE/EYE IRRITATION	CAUSES SERIOUS EYE DAMAGE.
RESPIRATORY OR SKIN SENSITISATION	PATCH TEST: - HUMAN RESULT: POSITIVE REMARKS: (ECHA)
GERM CELL MUTAGENICITY	IN VITRO MAMMALIAN CELL GENE MUTATION TEST MOUSE LYMPHOMA TEST RESULT: NEGATIVE MOUSE MALE RESULT: NEGATIVE (NATIONAL TOXICOLOGY PROGRAM)
CARCINOGENICITY IARC:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.
OSHA:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.
REPRODUCTIVE TOXICITY	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	MAY CAUSE RESPIRATORY IRRITATION. ACUTE ORAL TOXICITY - IF INGESTED, SEVERE BURNS OF THE MOUTH AND THROAT, AS WELL AS A DANGER OF PERFORATION OF THE OESOPHAGUS AND THE STOMACH. ACUTE INHALATION TOXICITY - MUCOSAL IRRITATIONS, COUGH, SHORTNESS OF BREATH, POSSIBLE DAMAGES:, DAMAGE OF RESPIRATORY TRACT
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	ORAL - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. - CARDIOVASCULAR SYSTEM
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: XP8700000 MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN, COUGH, SHORTNESS OF BREATH, HEADACHE, NAUSEA TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED. SYSTEMIC EFFECTS: METAL-FUME FEVER AFTER INHALATION OF LARGE QUANTITIES. OTHER DANGEROUS PROPERTIES CAN NOT BE EXCLUDED. HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	
TOXICITY TO FISH	STATIC TEST LC50 - OTHER FISH - 9 MG/L - 96 H REMARKS: (ECHA)

TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES	EC50 - DAPHNIA (WATER FLEA) - 31 - 88 MG/L - 48 H
PERSISTENCE AND DEGRADABILITY	THE METHODS FOR DETERMINING THE BIOLOGICAL DEGRADABILITY ARE NOT APPLICABLE TO INORGANIC SUBSTANCES.
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL HANDLING OR DISPOSAL. TOXIC TO AQUATIC LIFE. BIOLOGICAL EFFECTS: HARMFUL EFFECT DUE TO PH SHIFT. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)	
PROPER SHIPPING NAME:	CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (TIN DICHLORIDE)
UN NUMBER:	3260
CLASS:	8
PACKING GROUP:	II

REPORTABLE QUANTITY
(RQ):
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (TIN DICHLORIDE)
UN NUMBER: 3260
CLASS: 8
PACKING GROUP: II
EMS-NO: F-A, S-B

IATA

PROPER SHIPPING NAME: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (TIN DICHLORIDE)
UN NUMBER: 3260
CLASS: 8
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 302 EHS TPQ.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H290 MAY BE CORROSIVE TO METALS.
H302 + H332 HARMFUL IF SWALLOWED OR IF INHALED.
H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H317 MAY CAUSE AN ALLERGIC SKIN REACTION.
H335 MAY CAUSE RESPIRATORY IRRITATION.
H373 MAY CAUSE DAMAGE TO ORGANS (CARDIO-VASCULAR SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE IF SWALLOWED.
H401 TOXIC TO AQUATIC LIFE.

H412

HARMFUL TO AQUATIC LIFE WITH LONG LASTING
EFFECTS.

MSDS LEGEND

MW: MOLECULAR WEIGHT
MF: MOLECULAR FORMULA
VOC: VOLATILE ORGANIC COMPOUNDS
ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL
HYGINISTS
CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION: 3.1.

REVISION DATE: 01/27/2017