Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 36237

NAME: Dichloro(chloromethyl)methylsilane

SYNONYMS: (Chloromethyl)dichloromethylsilane

(Chloromethyl)methyldichlorosilane

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

FLAMMABLE LIQUIDS (CATEGORY 3), H226 ACUTE TOXICITY, INHALATION (CATEGORY 3), H331 SKIN CORROSION (CATEGORY 1A), H314 SERIOUS EYE DAMAGE (CATEGORY 1), H318 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), RESPIRATORY SYSTEM, H335

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

P405





SIGNAL WORD **DANGER**

HAZARD STATEMENT(S)

H226 FLAMMABLE LIQUID AND VAPOUR.

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. H314

H318 CAUSES SERIOUS EYE DAMAGE.

H331 TOXIC IF INHALED.

MAY CAUSE RESPIRATORY IRRITATION. H335

P

PRECAUTIONARY STATEMENT(S)		
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT	
	SURFACES NO SMOKING.	
P233	KEEP CONTAINER TIGHTLY CLOSED.	
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.	
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/	
	LIGHTING/ EQUIPMENT.	
P242	USE ONLY NON-SPARKING TOOLS.	
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC	
	DISCHARGE.	
P261	AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/	
	SPRAY.	
P264	WASH SKIN THOROUGHLY AFTER HANDLING.	
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.	
P280	WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE	
	PROTECTION/ FACE PROTECTION.	
P301 + P330 + P331	IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE	
	VOMITING.	
P303 + P361 + P353	IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY	
	ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/	
	SHOWER.	
P304 + P340 + P310	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP	
	COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A	
	POISON CENTER OR DOCTOR/ PHYSICIAN.	
P305 + P351 + P338 +	IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL	
P310	MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND	
	EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A	
	POISON CENTER/DOCTOR.	
P363	WASH CONTAMINATED CLOTHING BEFORE REUSE.	
P370 + P378	IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR	
	ALCOHOL-RESISTANT FOAM FOR EXTINCTION.	
P403 + P233	STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER	
	TIGHTLY CLOSED.	
P403 + P235	STORE IN A WELL-VENTILATED PLACE. KEEP COOL.	

STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE REACTS VIOLENTLY WITH WATER. LACHRYMATOR.

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: $C_2H_5Cl_3Si$

MW: 163.51

CAS-NO. 1558-33-4

PURITY: \geq 98% (GC)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION	
Dichloro(chloromethyl)methylsilane			
	FLAM. LIQ. 3; ACUTE TOX. 3;	<= 100 %	
	SKIN CORR. 1A; EYE DAM. 1;		
	STOT SE 3; H226, H331, H314,		
	H318, H335		

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING. GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

CONTACT

TAKE OFF CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH OFF WITH SOAP AND PLENTY OF

WATER. TAKE VICTIM IMMEDIATELY TO HOSPITAL.

CONSULT A PHYSICIAN.

IN CASE OF EYE

CONTACT

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A

PHYSICIAN.CONTINUE RINSING EYES DURING

TRANSPORT TO HOSPITAL.

IF SWALLOWED

DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT

SYMPTOMS AND EFFECTS, BOTH ACUTE

AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE

EXTINGUISHING MEDIA

DRY POWDER

SPECIAL HAZARDS ARISING FROM THE

SUBSTANCE OR MIXTURE

CARBON OXIDES, HYDROGEN CHLORIDE GAS,

SILICON OXIDES

ADVICE FOR WEAR SELF-CONTAINED BREATHING APPARATUS FOR

FIREFIGHTERS FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES

WEAR RESPIRATORY PROTECTION. AVOID BREATHING

VAPOURS, MIST OR GAS. ENSURE ADEQUATE

VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN ACCUMULATE IN

LOW AREAS.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND MATERIALS FOR **CONTAINMENT AND CLEANING UP**

CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WETBRUSHING AND PLACE IN CONTAINER FOR

DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). DO NOT FLUSH WITH WATER.

REFERENCE TO OTHER SECTIONS

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

HANDLING

PRECAUTIONS FOR SAFE AVOID CONTACT WITH SKIN AND EYES. AVOID

INHALATION OF VAPOUR OR MIST.

KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING TAKE MEASURES TO PREVENT THE BUILD

UP OF ELECTROSTATIC CHARGE. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT

UPRIGHT TO PREVENT LEAKAGE.

NEVER ALLOW PRODUCT TO GET IN CONTACT WITH

WATER DURING STORAGE.

Store at 2 - 8 °C

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2

NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

EXPOSURE CONTROLS

AVOID CONTACT WITH SKIN, EYES AND CLOTHING. APPROPRIATE WASH HANDS BEFORE BREAKS AND IMMEDIATELY **ENGINEERING**

CONTROLS AFTER HANDLING THE PRODUCT.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

TIGHTLY FITTING SAFETY GOGGLES. FACESHIELD (8-INCH MINIMUM). USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: FLUORINATED RUBBER MINIMUM LAYER THICKNESS: 0.7 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED: VITOJECT (KCL 890, SIZE M)

WATERIAL TESTED. VITOSECT (RCL 690, SIZE WI)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.4 MM

BREAK THROUGH TIME: 30 MIN

MATERIAL TESTED: CAMATRIL (KCL 730, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR

(US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING

CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR

CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Colorless to brown liquid
ODOUR NO DATA AVAILABLE
ODOUR THRESHOLD NO DATA AVAILABLE
PH NO DATA AVAILABLE

MELTING

POINT/FREEZING POINT

INITIAL BOILING POINT 121 - 122 °C

AND BOILING RANGE

FLASH POINT 35 °C

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY 5.65 - (AIR = 1.0)

RELATIVE DENSITY 1.284

WATER SOLUBILITY NO DATA AVAILABLE PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION NO DATA AVAILABLE

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

RELATIVE VAPOUR 5.65 - (AIR = 1.0)

DENSITY

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS

VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

REACTS VIOLENTLY WITH WATER.

CONDITIONS TO AVOID HEAT, FLAMES AND SPARKS. EXPOSURE TO MOISTURE

INCOMPATIBLE MATERIALS

STRONG OXIDIZING AGENTS, WATER, STRONG BASES

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - CARBON OXIDES, HYDROGEN CHLORIDE GAS, SILICON OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA

AVAILABLE

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY NO DATA AVAILABLE

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN

CORROSION/IRRITATION

NO DATA AVAILABLE

SERIOUS EYE

DAMAGE/EYE IRRITATION

NO DATA AVAILABLE

RESPIRATORY OR SKIN

SENSITISATION

NO DATA AVAILABLE

GERM CELL MUTAGENICITY NO DATA AVAILABLE

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR

CONFIRMED HUMAN CARCINOGEN BY IARC.

ACGIH: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL

CARCINOGEN BY ACGIH.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON

OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE

EXPOSURE

MAY CAUSE RESPIRATORY IRRITATION.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EVECTION TO SELECT

EXPOSURE

NO DATA AVAILABLE

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION

RTECS: VV2160000

MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE

OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN. COUGH, SHORTNESS OF BREATH, HEADACHE, NAUSEA

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND PBT/VPVB ASSESSMENT NOT AVAILABLE AS

VPVB ASSESSMENT CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT

METHODS

PRODUCT BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH

AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA

CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE

SOLUTIONS TO A LICENSED DISPOSAL COMPANY.
CONTACT A LICENSED PROFESSIONAL WASTE

DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: TOXIC LIQUIDS, CORROSIVE, ORGANIC, N.O.S.

(Dichloro(chloromethyl)methylsilane)

UN NUMBER: 2927 CLASS: 6.1 (8) PACKING GROUP: II

REPORTABLE QUANTITY

(RQ):

POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: TOXIC LIQUIDS, CORROSIVE, ORGANIC, N.O.S.

(Dichloro(chloromethyl)methylsilane)

UN NUMBER: 2927 CLASS: 6.1 (8) PACKING GROUP: II EMS-NO: F-A, S-B

IATA

PROPER SHIPPING NAME: TOXIC LIOUIDS, CORROSIVE, ORGANIC, N.O.S.

(Dichloro(chloromethyl)methylsilane)

UN NUMBER: 2927

CLASS: 6.1 (8) PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL

COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION

313.

SARA 311/312 HAZARDS FIRE HAZARD, ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Dichloro(chloromethyl)methylsilane 1558-33-4

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Dichloro(chloromethyl)methylsilane 1558-33-4

CALIFORNIA PROP. 65 COMPONENTS

THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H226 FLAMMABLE LIQUID AND VAPOUR.

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

H318 CAUSES SERIOUS EYE DAMAGE.

H331 TOXIC IF INHALED.

H335 MAY CAUSE RESPIRATORY IRRITATION.

MSDS LEGEND

MW: MOLECULAR WEIGHT
MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.1 REVISION DATE: 01/27/2017