Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 36238

NAME: Barium *tert*-butoxide

SYNONYMS: Barium di-t-butoxide

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE SOLIDS (CATEGORY 2), H228 $\,$

SKIN CORROSION (CATEGORY 1B), H314 SERIOUS EYE DAMAGE (CATEGORY 1), H318 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), RESPIRATORY SYSTEM, H335

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H228 FLAMMABLE SOLID.

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

H335 MAY CAUSE RESPIRATORY IRRITATION.

PRECAUTIONARY STATEMENT(S)

P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT

SURFACES. - NO SMOKING.

P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.

P241 USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/

LIGHTING/ EQUIPMENT.

P260 DO NOT BREATHE DUST OR MIST.

P264 WASH SKIN THOROUGHLY AFTER HANDLING.

P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA

P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE

PROTECTION/ FACE PROTECTION.

P301 + P330 + P331 IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE

VOMITING.

P303 + P361 + P353 IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY

ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/

SHOWER.

P304 + P340 + P310 IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP

COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A

POISON CENTER/DOCTOR.

P305 + P351 + P338 + IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

P310 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A

POISON CENTER/DOCTOR.

P363 WASH CONTAMINATED CLOTHING BEFORE REUSE.

P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR

ALCOHOL-RESISTANT FOAM TO EXTINGUISH.

P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER

TIGHTLY CLOSED.

P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT REACTS VIOLENTLY WITH WATER.

OTHERWISE

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: C₈H₁₈BaO₂

MW: 283.55

CAS-NO. 24363-36-8

PURITY: \geq 85% (Gravimetric assay)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Barium tert-butoxide		
	FLAM. SOL. 2; SKIN CORR. 1B; EYE DAM. 1; STOT SE 3; H228, H314, H318, H335	<= 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

CONTACT

TAKE OFF CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH OFF WITH SOAP AND PLENTY OF

WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE

CONTACT

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A

PHYSICIAN.CONTINUE RINSING EYES DURING

TRANSPORT TO HOSPITAL.

DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING IF SWALLOWED

> BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY **IMMEDIATE MEDICAL** ATTENTION AND SPECIAL TREATMENT **NEEDED**

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE SUITABLE EXTINGUISHING MEDIA

EXTINGUISHING MEDIA DRY POWDER DRY SAND

UNSUITABLE EXTINGUISHING MEDIA

DO NOT USE WATER JET.

SPECIAL HAZARDS CARBON OXIDES, BARIUM OXIDE

ARISING FROM THE SUBSTANCE OR MIXTURE

ADVICE FOR WEAR SELF CONTAINED BREATHING APPARATUS FOR

FIRE FIGHTING IF NECESSARY. **FIREFIGHTERS**

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL USE PERSONAL PROTECTIVE EQUIPMENT. AVOID PRECAUTIONS, DUST FORMATION. AVOID BREATHING VAPOURS, MIST **PROTECTIVE** OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE **EQUIPMENT AND** ALL SOURCES OF IGNITION. EVACUATE PERSONNEL **EMERGENCY** TO SAFE AREAS. AVOID BREATHING DUST.

PROCEDURES FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE **PRECAUTIONS** TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND SWEEP UP AND SHOVEL. CONTAIN SPILLAGE, AND MATERIALS FOR THEN COLLECT WITH AN ELECTRICALLY PROTECTED **CONTAINMENT AND** VACUUM CLEANER OR BY WET-BRUSHING AND PLACE **CLEANING UP** IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). DO NOT FLUSH WITH

WATER. KEEP IN SUITABLE, CLOSED CONTAINERS FOR

DISPOSAL.

REFERENCE TO OTHER SECTIONS

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS.FURTHER PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE

ADDITIONAL PROCESSING OCCURS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED.KEEP AWAY FROM

SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF

ELECTROSTATIC CHARGE.

FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND

WELL-VENTILATED PLACE.

NEVER ALLOW PRODUCT TO GET IN CONTACT WITH

WATER DURING STORAGE.

MOISTURE SENSITIVE. AIR SENSITIVE

Store at 2 - 8 °C

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2

NO OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

EXPOSURE CONTROLS

APPROPRIATE HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL ENGINEERING HYGIENE AND SAFETY PRACTICE. WASH HANDS CONTROLS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT

> FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR EN 166(EU).

SKIN PROTECTION HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED

PRIOR TO USE. USE PROPER GLOVE REMOVAL

TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER

SURFACE) TO AVOID SKIN CONTACT WITH THIS

PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY

HANDS.

BODY PROTECTION COMPLETE SUIT PROTECTING AGAINST CHEMICALS.

FLAME RETARDANT ANTISTATIC PROTECTIVE

CLOTHING. THE TYPE OF PROTECTIVE EOUIPMENT

MUST BE SELECTED ACCORDING TO THE

CONCENTRATION AND AMOUNT OF THE DANGEROUS

SUBSTANCE AT THE SPECIFIC WORKPLACE.

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORY PROTECTION

RESPIRATORS ARE APPROPRIATE USE A FULLFACE

PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN

143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE

SOLE MEANS OF PROTECTION. USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL **EXPOSURE**

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Light brown powder ODOUR NO DATA AVAILABLE ODOUR THRESHOLD NO DATA AVAILABLE PH NO DATA AVAILABLE

MELTING > 200 °C

POINT/FREEZING POINT INITIAL BOILING POINT AND BOILING RANGE

FLASH POINT

NO DATA AVAILABLE **EVAPORATION RATE**

FLAMMABILITY (SOLID, THE SUBSTANCE OR MIXTURE IS A FLAMMABLE SOLID

GAS) WITH THE CATEGORY 2.

UPPER/LOWER NO DATA AVAILABLE FLAMMABILITY OR

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY 9.79 - (AIR = 1.0)

RELATIVE DENSITY

EXPLOSIVE LIMITS

WATER SOLUBILITY NO DATA AVAILABLE PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION NO DATA AVAILABLE

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

RELATIVE VAPOUR 9.79 - (AIR = 1.0)

DENSITY

REACTIONS

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF REACTS VIOLENTLY WITH WATER. **HAZARDOUS**

CONDITIONS TO AVOID HEAT, FLAMES AND SPARKS. EXPOSURE TO MOISTURE

INCOMPATIBLE STRONG OXIDIZING AGENTS MATERIALS

HAZARDOUS OTHER DECOMPOSITION PRODUCTS - NO DATA

DECOMPOSITION AVAILABLE

PRODUCTS HAZARDOUS DECOMPOSITION PRODUCTS FORMED

UNDER FIRE CONDITIONS. - CARBON OXIDES, BARIUM

OXIDE

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY NO DATA AVAILABLE

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN NO DATA AVAILABLE

CORROSION/IRRITATION

SERIOUS EYE NO DATA AVAILABLE DAMAGE/EYE IRRITATION

RESPIRATORY OR SKIN NO DATA AVAILABLE

SENSITISATION

MUTAGENICITY

GERM CELL NO DATA AVAILABLE

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA'S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN IN

TOXICITY - SINGLE

EXPOSURE

INHALATION - MAY CAUSE RESPIRATORY

IRRITATION.

SPECIFIC TARGET ORGAN

TOXICITY - REPEATED

EXPOSURE

NO DATA AVAILABLE

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION

RTECS: NOT AVAILABLE

MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN. SPASM, INFLAMMATION AND EDEMA OF THE LARYNX, SPASM, INFLAMMATION AND EDEMA OF THE BRONCHI, PNEUMONITIS, PULMONARY EDEMA, BURNING SENSATION, COUGH, WHEEZING,

LARYNGITIS, SHORTNESS OF BREATH, HEADACHE,

NAUSEA

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

 ${\tt PBT/VPVB} \ {\tt ASSESSMENT} \ {\tt NOT} \ {\tt AVAILABLE} \ {\tt AS}$

CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS

TO A LICENSED DISPOSAL COMPANY. BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND

SCRUBBER.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: ALKALI METAL ALCOHOLATES, SELF-HEATING,

CORROSIVE, N.O.S. (Barium tert-butoxide)

UN NUMBER: 3206 CLASS: 4.2 (8) PACKING GROUP: II

REPORTABLE QUANTITY

(RQ):

POISON INHALATION NO

HAZARD:

IMDG

PROPER SHIPPING NAME: ALKALI METAL ALCOHOLATES, SELF-HEATING,

CORROSIVE, N.O.S. (Barium tert-butoxide)

UN NUMBER: 3206 CLASS: 4.2 (8) PACKING GROUP: II EMS-NO: F-A, S-J

IATA

PROPER SHIPPING NAME: ALKALI METAL ALCOHOLATES, SELF-HEATING,

CORROSIVE, N.O.S. (Barium tert-butoxide)

UN NUMBER: 3206 CLASS: 4.2 (8) PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL

COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS REACTIVITY HAZARD, ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Barium *tert*-butoxide 24363-36-8

NEW JERSEY RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Barium *tert*-butoxide 24363-36-8

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H228 FLAMMABLE SOLID.

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

H335 MAY CAUSE RESPIRATORY IRRITATION.

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL

INDUSTRIAL HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER

OSHA: OCCUPATIONAL SAFETY AND HEALTH

ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.1 REVISION DATE: 01/27/2017