Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 36327

NAME: Chloro-dimethyl-octadecylsilane solution, 70% in toluene

SYNONYMS: Dimethyl-octadecylchlorosilane

Octadecyldimethylchlorosilane

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE LIQUIDS (CATEGORY 2), H225 SKIN CORROSION (CATEGORY 1B), H314

SERIOUS EYE DAMAGE (CATEGORY 1), H318 REPRODUCTIVE TOXICITY (CATEGORY 2), H361 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), RESPIRATORY SYSTEM, CENTRAL NERVOUS SYSTEM, H335, H336 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (CATEGORY 2), CENTRAL NERVOUS SYSTEM, H373 ASPIRATION HAZARD (CATEGORY 1), H304 SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 2), H401 LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 3), H412

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM







SIGNAL WORD **DANGER**

HAZARD STATEMENT(S)

H225	HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H304	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
H314	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H335	MAY CAUSE RESPIRATORY IRRITATION.
H336	MAY CAUSE DROWSINESS OR DIZZINESS.
H361	SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN
	CHILD.
H373	MAY CAUSE DAMAGE TO ORGANS (CENTRAL NERVOUS
	SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE.
H401	TOXIC TO AQUATIC LIFE.
H412	HARMFUL TO AQUATIC LIFE WITH LONG LASTING
	EFFECTS.

PRECAUTIONARY STA	TEMENT(S)
P201	OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.
P202	DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE
	BEEN READ AND UNDERSTOOD.
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT
	SURFACES NO SMOKING.
P233	KEEP CONTAINER TIGHTLY CLOSED.
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/
	LIGHTING/ EQUIPMENT.
P242	USE ONLY NON-SPARKING TOOLS.
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC
	DISCHARGE.
P260	DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/
	SPRAY.
P264	WASH SKIN THOROUGHLY AFTER HANDLING.
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P273	AVOID RELEASE TO THE ENVIRONMENT.
P280	WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE
	PROTECTION/ FACE PROTECTION.

P301 + P310	IF SWALLOWED: IMMEDIATELY CALL A POISON
	CENTER/DOCTOR.
P301 + P330 + P331	IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE
	VOMITING.
P303 + P361 + P353	IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL
	CONTAMINATED CLOTHING. RINSE SKIN WITH
	WATER/SHOWER.
P304 + P340 + P310	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP
	COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A
	POISON CENTER/DOCTOR.
P305 + P351 + P338 +	IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL
P310	MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND
	EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A
	POISON CENTER/DOCTOR.
P308 + P313	IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/
	ATTENTION.
P363	WASH CONTAMINATED CLOTHING BEFORE REUSE.
P370 + P378	IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR
	ALCOHOL-RESISTANT FOAM TO EXTINCTION.
P403 + P233	STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER
	TIGHTLY CLOSED.
P403 + P235	STORE IN A WELL-VENTILATED PLACE. KEEP COOL.
P405	STORE LOCKED UP.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
	WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

NONE

MF: $C_{20}H_{43}ClSi$

MW: 347.09

CAS-NO. 18643-08-8

PURITY: \geq 98%

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION				
CHLORODIMETHYLOCTADECYLSILANE						
	, ,	>= 70 - < 90 %				
	STOT SE 3; H314, H318, H335					
TOLUENE	TOLUENE					
	FLAM. LIQ. 2; SKIN IRRIT. 2;	>= 30 - < 50 %				
	REPR. 2; STOT SE 3; STOT RE 2;					

ASP. TOX. 1; AQUATIC ACUTE 2; AQUATIC CHRONIC 3; H225, H315, H361, H336, H373, H304, H401, H412 CONCENTRATION LIMITS: 20 %: STOT SE 3, H336

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

CONTACT

TAKE OFF CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH OFF WITH SOAP AND PLENTY OF

WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE

CONTACT

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A

PHYSICIAN.CONTINUE RINSING EYES DURING

TRANSPORT TO HOSPITAL.

IF SWALLOWED DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING

BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.

MOST IMPORTANT

SYMPTOMS AND EFFECTS, BOTH ACUTE

AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11

INDICATION OF ANY IMMEDIATE MEDICAL

ATTENTION AND SPECIAL TREATMENT

NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE SUITABLE EXTINGUISHING MEDIA

EXTINGUISHING MEDIA DRY POWDER DRY SAND

UNSUITABLE EXTINGUISHING MEDIA

DO NOT USE WATER JET.

SPECIAL HAZARDS ARISING FROM THE CARBON OXIDES, HYDROGEN CHLORIDE GAS,

SILICON OXIDES

SUBSTANCE OR MIXTURE

ADVICE FOR WEAR SELF CONTAINED BREATHING APPARATUS FOR

FIREFIGHTERS FIRE FIGHTING IF NECESSARY.

FURTHER INFORMATION USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL USE PERSONAL PROTECTIVE EQUIPMENT. AVOID PRECAUTIONS, BREATHING VAPOURS, MIST OR GAS. ENSURE

PROTECTIVE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. **EQUIPMENT AND EMERGENCY** BEWARE OF VAPOURS ACCUMULATING TO FORM **PROCEDURES** EXPLOSIVE CONCENTRATIONS. VAPOURS CAN

ACCUMULATE IN LOW AREAS.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE **PRECAUTIONS**

TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

METHODS AND CONTAIN SPILLAGE, AND THEN COLLECT WITH NON-MATERIALS FOR COMBUSTIBLE ABSORBENT MATERIAL, (E.G. SAND, **CONTAINMENT AND** CLEANING UP

EARTH, DIATOMACEOUS EARTH, VERMICULITE) AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO

LOCAL / NATIONAL REGULATIONS (SEE SECTION 13).

REFERENCE TO OTHER **SECTIONS**

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

HANDLING

PRECAUTIONS FOR SAFE AVOID CONTACT WITH SKIN AND EYES, AVOID

INHALATION OF VAPOUR OR MIST.

USE EXPLOSION-PROOF EQUIPMENT.KEEP AWAY FROM

SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF

ELECTROSTATIC CHARGE.

FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT

UPRIGHT TO PREVENT LEAKAGE.

Store at RT

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2

NO OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS	
			PARAMETERS		
TOLUENE	108-88-3	TWA	100 PPM	USA. OSHA - TABLE Z-1	
			375 MG/M3	LIMITS FOR AIR	
				CONTAMINANTS - 1910.1000	
		STEL	150 PPM	USA. OSHA - TABLE Z-1	
			560 MG/M3	LIMITS FOR AIR	
				CONTAMINANTS - 1910.1000	
		TWA	200 PPM	USA. OCCUPATIONAL	
				EXPOSURE LIMITS (OSHA) -	
				TABLE Z-2	
	REMARKS	SZ37.12-1967			
		CEIL	300 PPM	USA. OCCUPATIONAL	
				EXPOSURE LIMITS (OSHA) -	
				TABLE Z-2	
		Z37.12-1967			
		PEAK	500 PPM	USA. OCCUPATIONAL	
				EXPOSURE LIMITS (OSHA) -	
				TABLE Z-2	
		Z37.12-1967			
		TWA	20 PPM	USA. ACGIH THRESHOLD	
				LIMIT VALUES (TLV)	
		VISUAL IMPAIRMENT			
		FEMALE REPRODUCTIVE			
		PREGNANCY LOSS			
		2018 ADOPTION SUBSTANCES FOR WHICH THERE IS A BIOLOGICAL			
		EXPOSURE INDEX OR INDICES (SEE BEI SECTION)			
		NOT CLASSIFI	Γ CLASSIFIABLE AS A HUMAN CARCINOGEN		

TWA	100 PPM 375 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
ST	150 PPM 560 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS

COMPONENT	CAS-NO.	PARAMETERS	VALUE	BIOLOGICAL	BASIS
				SPECIMEN	
TOLUENE	108-88-3	TOLUENE	0.02 MG/L	IN BLOOD	ACGIH -
					BIOLOGICAL
					EXPOSURE
					INDICES (BEI)
	REMARKS	PRIOR TO LAST	SHIFT OF WO	RKWEEK	
		TOLUENE	0.03 MG/L	URINE	ACGIH -
					BIOLOGICAL
					EXPOSURE
					INDICES (BEI)
		END OF SHIFT ((AS SOON AS I	POSSIBLE AFTI	ER EXPOSURE
		CEASES)			
		O-CRESOL	0.3MG/G	URINE	ACGIH -
			CREATININ E		BIOLOGICAL
					EXPOSURE
					INDICES (BEI)
		END OF SHIFT (AS SOON AS POSSIBLE AFTER EXPOSURE			
		CEASES)			

EXPOSURE CONTROLS

APPROPRIATE HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL ENGINEERING HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION TIGHTLY FITTING SAFETY GOGGLES. FACESHIELD (8-

INCH MINIMUM). USE EQUIPMENT FOR EYE PROTECTION

TESTED AND APPROVED UNDER APPROPRIATE

GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN

166(EU).

SKIN PROTECTION HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED

PRIOR TO USE. USE PROPER GLOVE REMOVAL

TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER

SURFACE) TO AVOID SKIN CONTACT WITH THIS

PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY

HANDS.

BODY PROTECTION COMPLETE SUIT PROTECTING AGAINST CHEMICALS,

FLAME RETARDANT ANTISTATIC PROTECTIVE

CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE

SPECIFIC WORKPLACE.

RESPIRATORY WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING **PROTECTION** RESPIRATORS ARE APPROPRIATE USE A FULLFACE

RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A

BACKUP TO ENGINEERING CONTROLS. IF THE

RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A

FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL

EXPOSURE

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO

DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Colorless liquid

ODOUR NO DATA AVAILABLE
ODOUR THRESHOLD NO DATA AVAILABLE
PH NO DATA AVAILABLE

MELTING 28 - 32 °C

POINT/FREEZING POINT

INITIAL BOILING POINT 145 - 155 °C

AND BOILING RANGE

FLASH POINT 200 °C

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY 0.86

WATER SOLUBILITY INSOLUBLE

PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

AUTO-IGNITION NO DATA AVAILABLE

TEMPERATURE

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

VISCOSITY NO DATA AVAILABLE EXPLOSIVE PROPERTIES NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

CONDITIONS TO AVOID HEAT, FLAMES AND SPARKS.

INCOMPATIBLE MATERIALS

STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - CARBON OXIDES, HYDROGEN CHLORIDE GAS, SILICON OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA

AVAILABLE

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY NO DATA AVAILABLE

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN NO DATA AVAILABLE

CORROSION/IRRITATION

SERIOUS EYE DAMAGE/EYE IRRITATION NO DATA AVAILABLE

RESPIRATORY OR SKIN SENSITISATION

NO DATA AVAILABLE

GERM CELL MUTAGENICITY NO DATA AVAILABLE

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS

IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED

HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA'S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY

NO DATA AVAILABLE

TOXICITI

NO DATA AVAILABLE

ORGAN TOXICITY -SINGLE EXPOSURE

SPECIFIC TARGET

SPECIFIC TARGET ORGAN TOXICITY -REPEATED EXPOSURE NO DATA AVAILABLE

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION

RTECS: NOT AVAILABLE

SPASM, INFLAMMATION AND EDEMA OF THE LARYNX,

SPASM, INFLAMMATION AND EDEMA OF THE BRONCHI, PNEUMONITIS, PULMONARY EDEMA, BURNING SENSATION, COUGH, WHEEZING,

A DANIGITIC GLIODTNEGG OF DDE ATH, HEAD A GU

LARYNGITIS, SHORTNESS OF BREATH, HEADACHE,

NAUSEA, VOMITING

STOMACH - IRREGULARITIES - BASED ON HUMAN

EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE

POTENTIAL

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS AN ENVIRONMENTAL HAZARD CANNOT BE

EXCLUDED IN THE EVENT OF UNPROFESSIONAL

HANDLING OR DISPOSAL. TOXIC TO AQUATIC LIFE.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS

TO A LICENSED DISPOSAL COMPANY. BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS

MATERIAL.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: CHLOROSILANES, FLAMMABLE, CORROSIVE, N.O.S.

UN NUMBER: 2985 CLASS: 3 (8) PACKING GROUP: II

REPORTABLE QUANTITY 3333 LBS

(RQ):

POISON INHALATION N

HAZARD:

NO

IMDG

PROPER SHIPPING NAME: CHLOROSILANES, FLAMMABLE, CORROSIVE, N.O.S.

UN NUMBER: 2985 CLASS: 3 (8) PACKING GROUP: II EMS-NO: F-E, S-C

IATA

PROPER SHIPPING NAME: CHLOROSILANES, FLAMMABLE, CORROSIVE, N.O.S.

UN NUMBER: 2985 CLASS: 3 (8) PACKING GROUP: II

IATA PASSENGER: NOT PERMITTED FOR TRANSPORT

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THE FOLLOWING COMPONENTS ARE SUBJECT TO

REPORTING LEVELS ESTABLISHED BY SARA TITLE III,

SECTION 313:

CAS-NO. REVISION DATE

TOLUENE 108-88-3 07/01/2007

SARA 311/312 HAZARDS FIRE HAZARD, ACUTE HEALTH HAZARD, CHRONIC

HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.

H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

H335 MAY CAUSE RESPIRATORY IRRITATION. H336 MAY CAUSE DROWSINESS OR DIZZINESS.

H361 SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN

CHILD

H373 MAY CAUSE DAMAGE TO ORGANS (CENTRAL NERVOUS

SYSTEM) THROUGH PROLONGED OR REPEATED

EXPOSURE.

H401 TOXIC TO AQUATIC LIFE.

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL

INDUSTRIAL HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION:3.1 REVISION DATE: 01/27/2017