

Chem-Impex International Inc.

Tel: (630) 766-2112

E-mail: sales@chemimpex.com

Shipping and Correspondence:

935 Dillon Drive

Wood Dale, IL 60191 USA

Fax: (630) 766-2218

Web site: www.chemimpex.com

Manufacturing site:

825 Dillon Drive

Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	36650
NAME:	Selenium dioxide
SYNONYMS:	Selenium oxide NSC 56753
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

ACUTE TOXICITY, ORAL (CATEGORY 3), H301

ACUTE TOXICITY, INHALATION (CATEGORY 3), H331

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (CATEGORY 2), H373

SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 1), H400

LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 1), H410

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H301 + H331 TOXIC IF SWALLOWED OR IF INHALED.
H373 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED
OR REPEATED EXPOSURE.
H410 VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING
EFFECTS.

PRECAUTIONARY STATEMENT(S)

P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/
SPRAY.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS
PRODUCT.
P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P273 AVOID RELEASE TO THE ENVIRONMENT.
P301 + P310 + P330 IF SWALLOWED: IMMEDIATELY CALL A POISON
CENTER/DOCTOR. RINSE MOUTH.
P304 + P340 + P311 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT
REST IN A POSITION COMFORTABLE FOR BREATHING. CALL
A POISON CENTER OR DOCTOR/ PHYSICIAN.
P314 GET MEDICAL ADVICE/ ATTENTION IF YOU FEEL UNWELL.
P391 COLLECT SPILLAGE.
P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER
TIGHTLY CLOSED.
P405 STORE LOCKED UP.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
WASTE DISPOSAL PLANT.

**HAZARDS NOT
OTHERWISE
CLASSIFIED (HNOC)
OR NOT COVERED
BY GHS** VESICANT.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: SeO₂

MW: 110.96

CAS-NO. 7446-08-4

PURITY: \geq 98% (Assay)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Selenium dioxide	ACUTE TOX. 3; STOT RE 2; AQUATIC ACUTE 1; AQUATIC CHRONIC 1; H301, H331, H373, H400, H410	\leq 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	WASH OFF WITH SOAP AND PLENTY OF WATER. TAKE VICTIM IMMEDIATELY TO HOSPITAL. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	FLUSH EYES WITH WATER AS A PRECAUTION.
IF SWALLOWED	NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

**SUITABLE
EXTINGUISHING MEDIA** USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY
CHEMICAL OR CARBON DIOXIDE.

**SPECIAL HAZARDS
ARISING FROM THE
SUBSTANCE OR MIXTURE** SELENIUM/SELENIUM OXIDES

**ADVICE FOR
FIREFIGHTERS** WEAR SELF-CONTAINED BREATHING APPARATUS FOR
FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES** WEAR RESPIRATORY PROTECTION. AVOID DUST
FORMATION. AVOID BREATHING VAPOURS, MIST OR
GAS. ENSURE ADEQUATE VENTILATION. EVACUATE
PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST.
FOR PERSONAL PROTECTION SEE SECTION 8.

**ENVIRONMENTAL
PRECAUTIONS** PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO
DO SO. DO NOT LET PRODUCT ENTER DRAINS.
DISCHARGE INTO THE ENVIRONMENT MUST BE
AVOIDED.

**METHODS AND
MATERIALS FOR
CONTAINMENT AND
CLEANING UP** PICK UP AND ARRANGE DISPOSAL WITHOUT CREATING
DUST. SWEEP UP AND SHOVEL. KEEP IN SUITABLE,
CLOSED CONTAINERS FOR DISPOSAL.

**REFERENCE TO OTHER
SECTIONS** FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE
HANDLING** AVOID CONTACT WITH SKIN AND EYES. AVOID
FORMATION OF DUST AND AEROSOLS. FURTHER
PROCESSING OF SOLID MATERIALS MAY RESULT IN
THE FORMATION OF COMBUSTIBLE DUSTS. THE
POTENTIAL FOR COMBUSTIBLE DUST FORMATION

SHOULD BE TAKEN INTO CONSIDERATION BEFORE ADDITIONAL PROCESSING OCCURS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE.

HYGROSCOPIC KEEP IN A DRY PLACE.

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
Selenium dioxide	7446-08-4	TWA	0.2 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		TWA	0.2 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
	REMARKS	UPPER RESPIRATORY TRACT IRRITATION EYE IRRITATION		
		TWA	0.2 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		PEL	0.2 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH HANDS BEFORE BREAKS AND IMMEDIATELY AFTER HANDLING THE PRODUCT.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION	FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).
SKIN PROTECTION	<p>HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.</p> <p>FULL CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)</p> <p>SPLASH CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)</p> <p>IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.</p>
BODY PROTECTION	COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.
RESPIRATORY PROTECTION	WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE PARTICLE RESPIRATOR TYPE N99 (US) OR TYPE P2 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).
CONTROL OF ENVIRONMENTAL EXPOSURE	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	White to off-white powder
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	315 °C (subl.)
INITIAL BOILING POINT AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	1 HPA AT 157 C
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	AVOID MOISTURE.

**INCOMPATIBLE
MATERIALS**

ORGANIC MATERIALS, STRONG ACIDS, AMMONIA

**HAZARDOUS
DECOMPOSITION
PRODUCTS**

HAZARDOUS DECOMPOSITION PRODUCTS FORMED
UNDER FIRE CONDITIONS. - SELENIUM/SELENIUM
OXIDES
OTHER DECOMPOSITION PRODUCTS - NO DATA
AVAILABLE
IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY

LD50 ORAL - RAT - 68.1 MG/KG
REMARKS: BEHAVIORAL: SOMNOLENCE (GENERAL
DEPRESSED ACTIVITY). BEHAVIORAL: CONVULSIONS
OR EFFECT ON SEIZURE THRESHOLD.

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

**SKIN
CORROSION/IRRITATION**

NO DATA AVAILABLE

**SERIOUS EYE
DAMAGE/EYE IRRITATION**

NO DATA AVAILABLE

**RESPIRATORY OR SKIN
SENSITISATION**

NO DATA AVAILABLE

**GERM CELL
MUTAGENICITY**

NO DATA AVAILABLE

CARCINOGENICITY

IARC:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED
HUMAN CARCINOGEN BY IARC.

NTP:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS A KNOWN OR ANTICIPATED
CARCINOGEN BY NTP.

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON
OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: VS8575000 MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN., COUGH, SHORTNESS OF BREATH, HEADACHE, NAUSEA STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY TO FISH	LC50 - PIMEPHALES PROMELAS (FATHEAD MINNOW) - 2.9 MG/L - 96.0 H
TOXICITY TO ALGAE	GROWTH INHIBITION EC50 - SCENEDESMUS ACUTUS - 0.1 MG/L - 3 D GROWTH INHIBITION LOEC - PSEUDOKIRCHNERIELLA SUBCAPITATA - 24.63 MG/L - 6 D
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL HANDLING OR DISPOSAL. VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER.

CONTAMINATED PACKAGING DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: SELENIUM COMPOUND, SOLID, N.O.S. (Selenium dioxide)
UN NUMBER: 3283
CLASS: 6.1
PACKING GROUP: III
REPORTABLE QUANTITY (RQ): 10 LBS
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: SELENIUM COMPOUND, SOLID, N.O.S. (Selenium dioxide)
UN NUMBER: 3283
CLASS: 6.1
PACKING GROUP: III
EMS-NO: F-A, S-A

IATA

PROPER SHIPPING NAME: SELENIUM COMPOUND, SOLID, N.O.S. (Selenium dioxide)
UN NUMBER: 3283
CLASS: 6.1
PACKING GROUP: III

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS	NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.	
SARA 313 COMPONENTS	THE FOLLOWING COMPONENTS ARE SUBJECT TO REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:	
	CAS-NO.	REVISION DATE
Selenium dioxide	7446-08-4	02/16/1993
SARA 311/312 HAZARDS	ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD	
MASSACHUSETTS RIGHT TO KNOW COMPONENTS		
	CAS-NO.	REVISION DATE
Selenium dioxide	7446-08-4	02/16/1993
PENNSYLVANIA RIGHT TO KNOW COMPONENTS		
	CAS-NO.	REVISION DATE
Selenium dioxide	7446-08-4	02/16/1993
NEW JERSEY RIGHT TO KNOW COMPONENTS		
	CAS-NO.	REVISION DATE
Selenium dioxide	7446-08-4	02/16/1993

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H301 + H331	TOXIC IF SWALLOWED OR IF INHALED.
H373	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.
H410	VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CIH** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES,*

*HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION:3.1

REVISION DATE: 01/27/2017