Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 37008

NAME: Manganese sulfate monohydrate, USP, EP, Powder, Low

heavy metals (As: <= 1 ppm, Cd: <= 1 ppm, Pb: <= 1 ppm &

 $Hg: \le 0.1 \text{ ppm}$

SYNONYMS: Manganese sulfate monohydrate, USP, EP, Powder, Low

heavy metals (As: <= 1 ppm, Cd: <= 1 ppm, Pb: <= 1 ppm &

 $Hg: \le 0.1 \text{ ppm}$

Manganese (II) sulfate monohydrate

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER (630) 766-2112 SERVICE:

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

SERIOUS EYE DAMAGE (CATEGORY 1), H318 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE, INHALATION (CATEGORY 2), BRAIN, H373 SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 3), H402 LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 2), H411

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM

SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H318 CAUSES SERIOUS EYE DAMAGE.

H373 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED

OR REPEATED EXPOSURE.

H402 HARMFUL TO AQUATIC LIFE

H411 TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

PRECAUTIONARY STATEMENT(S)

P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/

SPRAY.

P273 AVOID RELEASE TO THE ENVIRONMENT.

P280 WEAR EYE PROTECTION/ FACE PROTECTION

P305 + P351 + P338 + IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

P310 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A

POISON CENTER/DOCTOR.

P314 GET MEDICAL ADVICE/ ATTENTION IF YOU FEEL UNWELL.

P391 COLLECT SPILLAGE.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT NONE

OTHERWISE

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: $MnSO_4 \cdot H_2O$

MW: 169.01

CAS-NO. 10034-96-5

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION				
Manganese sulfate monohydrate, USP, EP, Powder, Low heavy metals (As: <= 1 ppm, Cd: <=						
1 ppm, Pb: <= 1 ppm & Hg: <= 0.1 ppm)						
	EYE DAM. 1; STOT RE 2;	<= 100%				
	AQUATIC ACUTE 3; AQUATIC					
	CHRONIC 2; H318, H373, H402,					
	H411					

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DECODIDETON	OF FIDOR AID	BATE A CITIZEN
DESCRIPTION	OR BIRST AID	MIRASIIRES
DESCIMITION	OI IIIOI AID	MEADURED

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA
	SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN WASH OFF WITH SOAP AND PLENTY OF WATER.

CONTACT CONSULT A PHYSICIAN.

IN CASE OF EYE RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

CONTACT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

IF SWALLOWED NEVER GIVE ANYTHING BY MOUTH TO AN

UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER.

CONSULT A PHYSICIAN.

MOST IMPORTANT SYMPTOMS AND

EFFECTS, BOTH ACUTE

AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

NEEDED

NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY **SUITABLE**

EXTINGUISHING MEDIA CHEMICAL OR CARBON DIOXIDE.

SPECIAL HAZARDS SULPHUR OXIDES, MANGANESE/MANGANESE OXIDES

ARISING FROM THE

SUBSTANCE OR MIXTURE

ADVICE FOR WEAR SELF-CONTAINED BREATHING APPARATUS FOR

FIREFIGHTERS FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL USE PERSONAL PROTECTIVE EQUIPMENT. AVOID PRECAUTIONS, DUST FORMATION. AVOID BREATHING VAPOURS, MIST

PROTECTIVE OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID **EQUIPMENT AND**

EMERGENCY BREATHING DUST.

FOR PERSONAL PROTECTION SEE SECTION 8. **PROCEDURES**

ENVIRONMENTAL PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE **PRECAUTIONS** TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

PICK UP AND ARRANGE DISPOSAL WITHOUT **METHODS AND** CREATING DUST. SWEEP UP AND SHOVEL. KEEP IN **MATERIALS FOR**

CONTAINMENT AND SUITABLE, CLOSED CONTAINERS FOR DISPOSAL. **CLEANING UP**

REFERENCE TO OTHER FOR DISPOSAL SEE SECTION 13.

SECTIONS

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE AVOID FORMATION OF DUST AND AEROSOLS.FURTHER HANDLING PROCESSING OF SOLID MATERIALS MAY RESULT IN

THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE

ADDITIONAL PROCESSING OCCURS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT

PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND

WELL-VENTILATED PLACE.

ANY INCOMPATIBILITIES HYGROSCOPIC

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2

NO OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS	
			PARAMETERS		
Manganese sulfate	10034-96-5	С	5 MG/M3	USA. OCCUPATIONAL	
monohydrate, USP,				EXPOSURE LIMITS (OSHA) -	
EP, Powder, Low				TABLE Z-1 LIMITS FOR AIR	
heavy metals (As: <=				CONTAMINANTS	
1 ppm, Cd: <= 1					
ppm, Pb: <= 1 ppm					
& Hg: $\leq 0.1 \text{ ppm}$)					
	REMARKS	CEILING LIMIT IS TO BE DETERMINED FROM			
		BREATHING-ZONE AIR SAMPLES.			
		TWA	0.1 MG/M3	USA. ACGIH THRESHOLD	
				LIMIT VALUES (TLV)	
		CENTRAL NERVOUS SYSTEM IMPAIRMENT			
		NOT CLASSIFIABLE AS A HUMAN CARCINOGEN			
		VARIES			
		TWA	0.02 MG/M3	USA. ACGIH THRESHOLD	
				LIMIT VALUES (TLV)	
		CENTRA	CENTRAL NERVOUS SYSTEM IMPAIRMENT		
		NOT CLA	OT CLASSIFIABLE AS A HUMAN CARCINOGEN		
		VARIES			
		TWA	1 MG/M3	USA. NIOSH	
				RECOMMENDED EXPOSURE	
				LIMITS	
		ST	3 MG/M3	USA. NIOSH	
				RECOMMENDED EXPOSURE	
				LIMITS	
		PEL	0.2 MG/M3	CALIFORNIA PERMISSIBLE	
				EXPOSURE LIMITS FOR	
				CHEMICAL CONTAMINANTS	

EXPOSURE CONTROLS

APPROPRIATE HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL **ENGINEERING** HYGIENE AND SAFETY PRACTICE. WASH HANDS **CONTROLS**

BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION FACE SHIELD AND SAFETY GLASSES USE EOUIPMENT

> FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR EN 166(EU).

SKIN PROTECTION HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED

PRIOR TO USE. USE PROPER GLOVE REMOVAL

TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER

SURFACE) TO AVOID SKIN CONTACT WITH THIS

PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY

HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER

SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER

FAMILIAR WITH THE SPECIFIC SITUATION OF

ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR

ANY SPECIFIC USE SCENARIO.

BODY PROTECTION COMPLETE SUIT PROTECTING AGAINST CHEMICALS,

> THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE

SPECIFIC WORKPLACE.

RESPIRATORY WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING **PROTECTION** RESPIRATORS ARE APPROPRIATE USE A FULLFACE

RESPIRATORS ARE APPROPRIATE USE A FULLFACE

PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO

ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR CEN (EU).

CONTROL OF PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO

ENVIRONMENTAL DO SO. DO NOT LET PRODUCT ENTER DRAINS. **EXPOSURE** DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Pale pink fine powder

ODOUR ODOURLESS

ODOUR THRESHOLD NO DATA AVAILABLE PH 3.0 - 3.5 AT 50 G/L AT 20 C

MELTING

POINT/FREEZING POINT INITIAL BOILING POINT AND BOILING RANGE

FLASH POINT

EVAPORATION RATE NO DATA AVAILABLE FLAMMABILITY (SOLID, NO DATA AVAILABLE

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

VAPOUR PRESSURE NO DATA AVAILABLE VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY

WATER SOLUBILITY 762 G/L AT 20 C

PARTITION COEFFICIENT: NOT APPLICABLE FOR INORGANIC SUBSTANCES

N- OCTANOL/WATER

AUTO-IGNITION NO DATA AVAILABLE

TEMPERATURE

DECOMPOSITION 400 - 450 C - ELIMINATION OF WATER OF

TEMPERATURE CRYSTALLISATION

850 C - (ANHYDROUS SUBSTANCE)

VISCOSITY

NO DATA AVAILABLE
EXPLOSIVE PROPERTIES

NO DATA AVAILABLE
OXIDIZING PROPERTIES

NO DATA AVAILABLE

OTHER SAFETY INFORMATION

BULK DENSITY CA.1,000 - 1,200 KG/M3

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS

NO DATA AVAILABLE

CONDITIONS TO AVOID AVOID MOISTURE.

INCOMPATIBLE MATERIALS

NO DATA AVAILABLE

HAZARDOUS DECOMPOSITION PRODUCTS HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - SULPHUR OXIDES,

MANGANESE/MANGANESE OXIDES

OTHER DECOMPOSITION PRODUCTS - NO DATA

AVAILABLE

IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY LD50 ORAL - RAT - MALE AND FEMALE - 2,150 MG/KG

REMARKS: (ANHYDROUS SUBSTANCE) (ECHA)

LC50 INHALATION - RAT - MALE AND FEMALE - 4 H ->

4.45 MG/L

(OECD TEST GUIDELINE 403)

REMARKS: (ANHYDROUS SUBSTANCE)

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN - RABBIT

CORROSION/IRRITATION RESULT: NO SKIN IRRITATION - 4 H

(OECD TEST GUIDELINE 404)

REMARKS: (ANHYDROUS SUBSTANCE)

SERIOUS EYE EYES - RABBIT

DAMAGE/EYE IRRITATION RESULT: IRREVERSIBLE EFFECTS ON THE EYE

(OECD TEST GUIDELINE 405)

REMARKS: (ANHYDROUS SUBSTANCE)

RESPIRATORY OR SKIN

SENSITISATION

NO DATA AVAILABLE

GERM CELL AMES TEST

MUTAGENICITY RESULT: NEGATIVE

(NATIONAL TOXICOLOGY PROGRAM)

CARCINOGENICITY

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EOUAL TO 0.1% IS

IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED

HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

TOXICITY - SINGLE

EXPOSURE

ACUTE ORAL TOXICITY - AFTER UPTAKE OF LARGE OUANTITIES:. NAUSEA. VOMITING. DIARRHOEA.

GASTRIC PAIN, IRRITATIONS OF MUCOUS

MEMBRANES IN THE MOUTH, PHARYNX,

OESOPHAGUS AND GASTROINTESTINAL TRACT. ACUTE INHALATION TOXICITY - POSSIBLE DAMAGES:, MUCOSAL IRRITATIONS, TISSUE

DAMAGE, PNEUMONIA

SPECIFIC TARGET ORGAN

TOXICITY - REPEATED

EXPOSURE

INHALATION - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. -

BRAIN

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION

RTECS: OP0893500

MEN EXPOSED TO MANGANESE DUSTS SHOWED A DECREASE IN FERTILITY. CHRONIC MANGANESE POISONING PRIMARILY INVOLVES THE CENTRAL NERVOUS SYSTEM. EARLY SYMPTOMS INCLUDE LANGUOR, SLEEPINESS AND WEAKNESS IN THE LEGS. A STOLID MASK-LIKE APPEARANCE OF THE FACE, EMOTIONAL DISTURBANCES SUCH AS UNCONTROLLABLE LAUGHTER AND A SPASTIC GAIT WITH TENDENCY TO FALL IN WALKING ARE FINDINGS IN MORE ADVANCED CASES. HIGH INCIDENCE OF PNEUMONIA HAS BEEN FOUND IN WORKERS EXPOSED TO THE DUST OR FUME OF SOME MANGANESE COMPOUNDS. PROLONGED OR REPEATED INHALATION MAY CAUSE: PNEUMONIA

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

MANGANESE COMPOUNDS ARE GENERALLY ONLY VERY SLIGHTLY ABSORBABLE VIA THE GASTROINTESTINAL TRACT.
OTHER DANGEROUS PROPERTIES CAN NOT BE EXCLUDED.
HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE.

STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY

TOXICITY TO ALGAE

STATIC TEST NOEC - DESMODESMUS SUBSPICATUS

(GREEN ALGAE) - 1 MG/L - 72 H (OECD TEST GUIDELINE 201)

STATIC TEST ERC50 - DESMODESMUS SUBSPICATUS

(GREEN ALGAE) - 61 MG/L - 72 H (OECD TEST GUIDELINE 201)

PERSISTENCE AND DEGRADABILITY

THE METHODS FOR DETERMINING THE BIOLOGICAL

DEGRADABILITY ARE NOT APPLICABLE TO

INORGANIC SUBSTANCES.

BIOACCUMULATIVE POTENTIAL NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT ANDPBT/VPVB ASSESSMENT NOT AVAILABLE AS **VPVB ASSESSMENT**CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS AN ENVIRONMENTAL HAZARD CANNOT BE

EXCLUDED IN THE EVENT OF UNPROFESSIONAL

HANDLING OR DISPOSAL.

TOXIC TO AQUATIC LIFE WITH LONG LASTING

EFFECTS.

DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS

TO A LICENSED DISPOSAL COMPANY.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US) NOT DANGEROUS GOODS

IMDG

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S. (Manganese sulfate monohydrate, USP, EP, Powder, Low heavy metals (As: <= 1 ppm, Cd: <= 1 ppm, Pb:

 $\leq 1 \text{ ppm & Hg: } \leq 0.1 \text{ ppm)}$

UN NUMBER: 3077
CLASS: 9
PACKING GROUP: III
EMS-NO: F-A, S-F

MARINE POLLUTANT: YES

IATA

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S. (Manganese sulfate monohydrate, USP, EP, Powder, Low heavy metals (As: <= 1 ppm, Cd: <= 1 ppm, Pb:

<= 1 ppm & Hg: <= 0.1 ppm))

UN NUMBER: 3077 CLASS: 9 PACKING GROUP: III

FURTHER INFORMATION

EHS-MARK REQUIRED (ADR 2.2.9.1.10, IMDG CODE 2.10.3) FOR SINGLE PACKAGINGS AND COMBINATION PACKAGINGS CONTAINING INNER PACKAGINGS WITH DANGEROUS GOODS > 5L FOR LIQUIDS OR > 5KG FOR SOLIDS.

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO

THE REPORTING REQUIREMENTS OF SARA TITLE III,

SECTION 302.

SARA 313 COMPONENTS THE FOLLOWING COMPONENTS ARE SUBJECT TO

REPORTING LEVELS ESTABLISHED BY SARA TITLE III,

SECTION 313:

CAS-NO. REVISION DATE

10034-96-5 07-08-2015

Manganese sulfate monohydrate, USP, EP, Powder, Low heavy metals (As: <= 1 ppm, Cd: <= 1 ppm, Pb: <= 1 ppm & Hg: <= 0.1 ppm)

SARA 311/312 HAZARDS CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

CAS-NO. REVISION DATE

Manganese sulfate 10034-96-5 07-08-2015

monohydrate, USP, EP, Powder, Low heavy metals (As: <= 1 ppm, Cd: <= 1 ppm, Pb: <= 1 ppm & Hg: <= 0.1 ppm)

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H318 CAUSES SERIOUS EYE DAMAGE.

H373 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED

OR REPEATED EXPOSURE.

H402 HARMFUL TO AQUATIC LIFE.

H411 TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

HYGINISTS

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA) TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.1. REVISION DATE: 01/27/2017