

# *Chem-Impex International Inc.*

---

Tel: (630) 766-2112

E-mail: [sales@chemimpex.com](mailto:sales@chemimpex.com)

Shipping and Correspondence:

935 Dillon Drive

Wood Dale, IL 60191 USA

Fax: (630) 766-2218

Web site: [www.chemimpex.com](http://www.chemimpex.com)

Manufacturing site:

825 Dillon Drive

Wood Dale, IL 60191 USA

## SAFETY DATA SHEET

---

### SECTION 1. CHEMICAL IDENTIFICATION

---

CATALOG #:	37851
NAME:	Ebselen
SYNONYMS:	2-Phenyl-1,2-benzoisoselenazol-3(2H)-one
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

### SECTION 2. HAZARDS IDENTIFICATION

---

#### CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

#### GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

ACUTE TOXICITY, ORAL (CATEGORY 3), H301

ACUTE TOXICITY, INHALATION (CATEGORY 3), H331

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (CATEGORY 2), H373

SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 1), H400

LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 1), H410

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS  
PICTOGRAM**



SIGNAL WORD DANGER

**HAZARD STATEMENT(S)**

H301 + H331 TOXIC IF SWALLOWED OR IF INHALED.  
H373 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED  
OR REPEATED EXPOSURE.  
H410 VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING  
EFFECTS.

**PRECAUTIONARY STATEMENT(S)**

P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/  
SPRAY.  
P264 WASH SKIN THOROUGHLY AFTER HANDLING.  
P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS  
PRODUCT.  
P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.  
P273 AVOID RELEASE TO THE ENVIRONMENT.  
P301 + P310 + P330 IF SWALLOWED: IMMEDIATELY CALL A POISON  
CENTER/DOCTOR. RINSE MOUTH.  
P304 + P340 + P311 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT  
REST IN A POSITION COMFORTABLE FOR BREATHING. CALL  
A POISON CENTER OR DOCTOR/ PHYSICIAN.  
P314 GET MEDICAL ADVICE/ ATTENTION IF YOU FEEL UNWELL.  
P391 COLLECT SPILLAGE.  
P403 + P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER  
TIGHTLY CLOSED.  
P405 STORE LOCKED UP.  
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED  
WASTE DISPOSAL PLANT.

**HAZARDS NOT  
OTHERWISE  
CLASSIFIED (HNOC)  
OR NOT COVERED  
BY GHS** NONE

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

MF:  $C_{13}H_9NOSe$   
MW: 274.18  
CAS-NO. 60940-34-3

PURITY:  $\geq 98\%$  (GC)

**HAZARDOUS COMPONENTS**

COMPONENT	CLASSIFICATION	CONCENTRATION
Ebselen	ACUTE TOX. 3; STOT RE 2; AQUATIC ACUTE 1; AQUATIC CHRONIC 1; H301, H331, H373, H400, H410	$\leq 100\%$

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

---

**SECTION 4. FIRST-AID MEASURES**

---

**DESCRIPTION OF FIRST AID MEASURES**

<b>GENERAL ADVICE</b>	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT OF DANGEROUS AREA.
<b>IF INHALED</b>	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
<b>IN CASE OF SKIN CONTACT</b>	WASH OFF WITH SOAP AND PLENTY OF WATER. TAKE VICTIM IMMEDIATELY TO HOSPITAL. CONSULT A PHYSICIAN.
<b>IN CASE OF EYE CONTACT</b>	FLUSH EYES WITH WATER AS A PRECAUTION.
<b>IF SWALLOWED</b>	NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
<b>MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED</b>	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
<b>INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED</b>	NO DATA AVAILABLE

---

**SECTION 5. FIRE AND EXPLOSION DATA**

---

**EXTINGUISHING MEDIA**

**SUITABLE EXTINGUISHING MEDIA** USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

**SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE** CARBON OXIDES, NITROGEN OXIDES (NOX), SELENIUM/SELENIUM OXIDES COMBUSTIBLE.

**ADVICE FOR FIREFIGHTERS** WEAR SELF-CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.

**FURTHER INFORMATION** NO DATA AVAILABLE

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

---

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES** WEAR RESPIRATORY PROTECTION. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST. FOR PERSONAL PROTECTION SEE SECTION 8.

**ENVIRONMENTAL PRECAUTIONS** PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP** PICK UP AND ARRANGE DISPOSAL WITHOUT CREATING DUST. SWEEP UP AND SHOVEL. KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.

**REFERENCE TO OTHER SECTIONS** FOR DISPOSAL SEE SECTION 13.

---

**SECTION 7. HANDLING AND STORAGE**

---

**PRECAUTIONS FOR SAFE HANDLING** AVOID CONTACT WITH SKIN AND EYES. AVOID FORMATION OF DUST AND AEROSOLS. FURTHER PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION

SHOULD BE TAKEN INTO CONSIDERATION BEFORE ADDITIONAL PROCESSING OCCURS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2.

**CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES** KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE.  
Store at 2 - 8 °C

**SPECIFIC END USE(S)** APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### CONTROL PARAMETERS

#### COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
Ebselen	60940-34-3	TWA	0.2 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		TWA	0.2 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
	REMARKS	UPPER RESPIRATORY TRACT IRRITATION EYE IRRITATION		
		TWA	0.2 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		PEL	0.2 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS

### EXPOSURE CONTROLS

**APPROPRIATE ENGINEERING CONTROLS** AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH HANDS BEFORE BREAKS AND IMMEDIATELY AFTER HANDLING THE PRODUCT.

### PERSONAL PROTECTIVE EQUIPMENT

**EYE/FACE PROTECTION** FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

**SKIN PROTECTION** HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

**FULL CONTACT**

MATERIAL: NITRILE RUBBER  
MINIMUM LAYER THICKNESS: 0.11 MM  
BREAK THROUGH TIME: 480 MIN  
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

**SPLASH CONTACT**

MATERIAL: NITRILE RUBBER  
MINIMUM LAYER THICKNESS: 0.11 MM  
BREAK THROUGH TIME: 480 MIN  
MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

**BODY PROTECTION** COMPLETE SUIT PROTECTING AGAINST CHEMICALS, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

**RESPIRATORY PROTECTION** WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE PARTICLE RESPIRATOR TYPE N99 (US) OR TYPE P2 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

**CONTROL OF ENVIRONMENTAL EXPOSURE** PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

---

**INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE Light orange to yellow to green powder to crystal

ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING	181 - 185 °C
POINT/FREEZING POINT	
INITIAL BOILING POINT	
AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER	NO DATA AVAILABLE
FLAMMABILITY OR	
EXPLOSIVE LIMITS	
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	LOG POW: 3.126 - BIOACCUMULATION IS NOT EXPECTED
AUTO-IGNITION	NO DATA AVAILABLE
TEMPERATURE	
DECOMPOSITION	NO DATA AVAILABLE
TEMPERATURE	
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

**OTHER SAFETY INFORMATION**

NO DATA AVAILABLE

---

**SECTION 10. STABILITY AND REACTIVITY**

---

<b>REACTIVITY</b>	NO DATA AVAILABLE
<b>CHEMICAL STABILITY</b>	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
<b>POSSIBILITY OF HAZARDOUS REACTIONS</b>	NO DATA AVAILABLE
<b>CONDITIONS TO AVOID</b>	NO DATA AVAILABLE
<b>INCOMPATIBLE MATERIALS</b>	NO DATA AVAILABLE

**HAZARDOUS  
DECOMPOSITION  
PRODUCTS**

HAZARDOUS DECOMPOSITION PRODUCTS FORMED  
UNDER FIRE CONDITIONS. - CARBON OXIDES,  
NITROGEN OXIDES (NOX), SELENIUM/SELENIUM OXIDES  
OTHER DECOMPOSITION PRODUCTS - NO DATA  
AVAILABLE  
IN THE EVENT OF FIRE: SEE SECTION 5

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

---

**INFORMATION ON TOXICOLOGICAL EFFECTS**

**ACUTE TOXICITY**

NO DATA AVAILABLE

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

**SKIN  
CORROSION/IRRITATION**

NO DATA AVAILABLE

**SERIOUS EYE  
DAMAGE/EYE IRRITATION**

NO DATA AVAILABLE

**RESPIRATORY OR SKIN  
SENSITISATION**

NO DATA AVAILABLE

**GERM CELL  
MUTAGENICITY**

NO DATA AVAILABLE

**CARCINOGENICITY**

IARC:

NO COMPONENT OF THIS PRODUCT PRESENT AT  
LEVELS GREATER THAN OR EQUAL TO 0.1% IS  
IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED  
HUMAN CARCINOGEN BY IARC.

NTP:

NO COMPONENT OF THIS PRODUCT PRESENT AT  
LEVELS GREATER THAN OR EQUAL TO 0.1% IS  
IDENTIFIED AS A KNOWN OR ANTICIPATED  
CARCINOGEN BY NTP.

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT  
LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON  
OSHA S LIST OF REGULATED CARCINOGENS.

**REPRODUCTIVE TOXICITY**

NO DATA AVAILABLE

**SPECIFIC TARGET ORGAN  
TOXICITY - SINGLE  
EXPOSURE**

NO DATA AVAILABLE



<b>SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE</b>	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.
<b>ASPIRATION HAZARD</b>	NO DATA AVAILABLE
<b>ADDITIONAL INFORMATION</b>	RTECS: NOT AVAILABLE  ACUTE SELENIUM POISONING PRODUCES CENTRAL NERVOUS SYSTEM EFFECTS, WHICH INCLUDE NERVOUSNESS, CONVULSIONS, AND DROWSINESS. OTHER SIGNS OF INTOXICATION CAN INCLUDE SKIN ERUPTIONS, LASSITUDE, GASTROINTESTINAL DISTRESS, TEETH THAT ARE DISCOLORED OR DECAYED, ODOROUS ("GARLIC") BREATH, AND PARTIAL LOSS OF HAIR AND NAILS. CHRONIC EXPOSURE BY INHALATION CAN PRODUCE SYMPTOMS THAT INCLUDE PALLOR, COATING OF THE TONGUE, ANEMIA, IRRITATION OF THE MUCOSA, LUMBAR PAIN, LIVER AND SPLEEN DAMAGE, AS WELL AS ANY OF THE OTHER PREVIOUSLY MENTIONED SYMPTOMS. CHRONIC CONTACT WITH SELENIUM COMPOUNDS MAY CAUSE GARLIC ODOR OF BREATH AND SWEAT, DERMATITIS, AND MODERATE EMOTIONAL INSTABILITY.  TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.  STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

---

**SECTION 12. ECOLOGICAL INFORMATION**

---

<b>TOXICITY</b>	NO DATA AVAILABLE
<b>PERSISTENCE AND DEGRADABILITY</b>	NO DATA AVAILABLE
<b>BIOACCUMULATIVE POTENTIAL</b>	NO DATA AVAILABLE
<b>MOBILITY IN SOIL</b>	NO DATA AVAILABLE
<b>RESULTS OF PBT AND VPVB ASSESSMENT</b>	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED

**OTHER ADVERSE EFFECTS** AN ENVIRONMENTAL HAZARD CANNOT BE EXCLUDED IN THE EVENT OF UNPROFESSIONAL HANDLING OR DISPOSAL. VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

---

**WASTE TREATMENT METHODS**

**PRODUCT** OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER.

**CONTAMINATED PACKAGING** DISPOSE OF AS UNUSED PRODUCT.

---

**SECTION 14. TRANSPORT INFORMATION**

---

**DOT (US)**

PROPER SHIPPING NAME: SELENIUM COMPOUND, SOLID, N.O.S. (Ebselen)  
UN NUMBER: 3283  
CLASS: 6.1  
PACKING GROUP: III  
REPORTABLE QUANTITY (RQ):  
POISON INHALATION HAZARD: NO

**IMDG**

PROPER SHIPPING NAME: SELENIUM COMPOUND, SOLID, N.O.S. (Ebselen)  
UN NUMBER: 3283  
CLASS: 6.1  
PACKING GROUP: III  
EMS-NO: F-A, S-A  
MARINE POLLUTANT : YES

**IATA**

PROPER SHIPPING NAME: SELENIUM COMPOUND, SOLID, N.O.S. (Ebselen)  
UN NUMBER: 3283  
CLASS: 6.1  
PACKING GROUP: III

---

**SECTION 15. REGULATORY INFORMATION**

---

**SARA 302 COMPONENTS** THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 302 EHS TPQ.

**SARA 313 COMPONENTS** THE FOLLOWING COMPONENTS ARE SUBJECT TO REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:

	CAS-NO.	REVISION DATE
Ebselen	60940-34-3	07-08-2015

**SARA 311/312 HAZARDS** ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

**MASSACHUSETTS RIGHT TO KNOW COMPONENTS**

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

**PENNSYLVANIA RIGHT TO KNOW COMPONENTS**

	CAS-NO.	REVISION DATE
Ebselen	60940-34-3	07-08-2015

**NEW JERSEY RIGHT TO KNOW COMPONENTS**

	CAS-NO.	REVISION DATE
Ebselen	60940-34-3	07-08-2015

---

**SECTION 16. OTHER INFORMATION**

---

**FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.**

H301 + H331	TOXIC IF SWALLOWED OR IF INHALED.
H373	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.
H410	VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

**MSDS LEGEND**

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

**IMPORTANT:**

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO*

*SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

*VERSION: 3.2.*

*REVISION DATE: 07/01/2020*