

# *Chem-Impex International Inc.*

---

Tel: (630) 766-2112  
E-mail: [sales@chemimpex.com](mailto:sales@chemimpex.com)  
**Shipping and Correspondence:**  
935 Dillon Drive  
Wood Dale, IL 60191 USA

Fax: (630) 766-2218  
Web site: [www.chemimpex.com](http://www.chemimpex.com)  
**Manufacturing site:**  
825 Dillon Drive  
Wood Dale, IL 60191 USA

## SAFETY DATA SHEET

---

### SECTION 1. CHEMICAL IDENTIFICATION

---

CATALOG #:	40538
NAME:	Hexamethyldisiloxane
SYNONYMS:	HMDSO
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

### SECTION 2. HAZARDS IDENTIFICATION

---

#### CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

**GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)**  
FLAMMABLE LIQUIDS (CATEGORY 2), H225  
SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 1), H400  
LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 1), H410

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS  
PICTOGRAM**



SIGNAL WORD DANGER

**HAZARD STATEMENT(S)**

H225 HIGHLY FLAMMABLE LIQUID AND VAPOR.  
H410 VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

**PRECAUTIONARY STATEMENT(S)**

P210 KEEP AWAY FROM HEAT/ SPARKS/ OPEN FLAMES/ HOT SURFACES. NO SMOKING.  
P233 KEEP CONTAINER TIGHTLY CLOSED.  
P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.  
P241 USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/ LIGHTING/ EQUIPMENT.  
P242 USE ONLY NON-SPARKING TOOLS.  
P243 TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.  
P273 AVOID RELEASE TO THE ENVIRONMENT.  
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.  
P303 + P361 + P353 IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER.  
P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM TO EXTINGUISH.  
P391 COLLECT SPILLAGE.  
P403 + P235 STORE IN A WELL-VENTILATED PLACE. KEEP COOL.  
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

**HAZARDS NOT  
OTHERWISE  
CLASSIFIED (HNOC)  
OR NOT COVERED  
BY GHS** NONE

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

MF:  $C_6H_{18}OSi_2$   
MW: 162.38  
CAS-NO. 107-46-0

PURITY:  $\geq 99\%$  (GC)

#### HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Hexamethyldisiloxane	FLAM. LIQ. 2; AQUATIC ACUTE 1; AQUATIC CHRONIC 1; H225, H400, H410 M-FACTOR - AQUATIC ACUTE: 1 - AQUATIC CHRONIC: 1	$\leq 100\%$

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

---

## SECTION 4. FIRST-AID MEASURES

---

### DESCRIPTION OF FIRST AID MEASURES

<b>GENERAL ADVICE</b>	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
<b>IF INHALED</b>	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
<b>IN CASE OF SKIN CONTACT</b>	WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.
<b>IN CASE OF EYE CONTACT</b>	FLUSH EYES WITH WATER AS A PRECAUTION.
<b>IF SWALLOWED</b>	DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
<b>MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED</b>	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11.
<b>INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED</b>	NO DATA AVAILABLE

---

## **SECTION 5. FIRE AND EXPLOSION DATA**

---

### **EXTINGUISHING MEDIA**

#### **SUITABLE EXTINGUISHING MEDIA**

SUITABLE EXTINGUISHING MEDIA  
DRY POWDER DRY SAND

UNSUITABLE EXTINGUISHING MEDIA  
DO NOT USE WATER JET.

#### **SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE**

CARBON OXIDES, SILICON OXIDES

#### **ADVICE FOR FIREFIGHTERS**

WEAR SELF-CONTAINED BREATHING APPARATUS FOR  
FIREFIGHTING IF NECESSARY.

#### **FURTHER INFORMATION**

USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

---

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

---

#### **PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES**

AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE  
ADEQUATE VENTILATION. REMOVE ALL SOURCES OF  
IGNITION. EVACUATE PERSONNEL TO SAFE AREAS.  
BEWARE OF VAPOURS ACCUMULATING TO FORM  
EXPLOSIVE CONCENTRATIONS. VAPOURS CAN  
ACCUMULATE IN LOW AREAS.  
FOR PERSONAL PROTECTION SEE SECTION 8.

#### **ENVIRONMENTAL PRECAUTIONS**

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE  
TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.  
DISCHARGE INTO THE ENVIRONMENT MUST BE  
AVOIDED.

#### **METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP**

CONTAIN SPILLAGE, AND THEN COLLECT WITH NON-  
COMBUSTIBLE ABSORBENT MATERIAL, (E.G. SAND,  
EARTH, DIATOMACEOUS EARTH, VERMICULITE) AND  
PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO  
LOCAL / NATIONAL REGULATIONS (SEE SECTION 13).

#### **REFERENCE TO OTHER SECTIONS**

FOR DISPOSAL SEE SECTION 13.

---

## **SECTION 7. HANDLING AND STORAGE**

---

<b>PRECAUTIONS FOR SAFE HANDLING</b>	AVOID INHALATION OF VAPOUR OR MIST. USE EXPLOSION-PROOF EQUIPMENT.KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE. FOR PRECAUTIONS SEE SECTION 2.2.
<b>CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES</b>	KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. STORE UNDER INERT GAS. HYGROSCOPIC  Store at RT
<b>SPECIFIC END USE(S)</b>	APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED.

---

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

### **CONTROL PARAMETERS**

#### **COMPONENTS WITH WORKPLACE CONTROL PARAMETERS**

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL EXPOSURE LIMIT VALUES.

### **EXPOSURE CONTROLS**

#### **APPROPRIATE ENGINEERING CONTROLS**

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

### **PERSONAL PROTECTIVE EQUIPMENT**

#### **EYE/FACE PROTECTION**

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

**SKIN PROTECTION**

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

**FULL CONTACT**

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

**SPLASH CONTACT**

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

**BODY PROTECTION**

IMPERVIOUS CLOTHING, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

**RESPIRATORY PROTECTION**

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULLFACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

**CONTROL OF ENVIRONMENTAL EXPOSURE**

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

---

**INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Colorless clear liquid
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	-59 °C (Lit.)
INITIAL BOILING POINT AND BOILING RANGE	100 °C (Lit.)
FLASH POINT	-2 °C
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	UPPER EXPLOSION LIMIT: 21.8 %(V) LOWER EXPLOSION LIMIT: 0.5 %(V)
VAPOUR PRESSURE	44 HPA AT 20 C
VAPOUR DENSITY	5.61 - (AIR = 1.0)
RELATIVE DENSITY	0.77 g/mL
WATER SOLUBILITY	0.00093 G/L AT 23 C - SLIGHTLY SOLUBLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	LOG POW: > 4 AT 25 C
AUTO-IGNITION TEMPERATURE	340 C AT 1,013 HPA
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

**OTHER SAFETY INFORMATION**

RELATIVE VAPOUR DENSITY	5.61 - (AIR = 1.0)
-------------------------	--------------------

---

**SECTION 10. STABILITY AND REACTIVITY**

---

<b>REACTIVITY</b>	NO DATA AVAILABLE
<b>CHEMICAL STABILITY</b>	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
<b>POSSIBILITY OF HAZARDOUS REACTIONS</b>	VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

<b>CONDITIONS TO AVOID</b>	HEAT, FLAMES AND SPARKS.
<b>INCOMPATIBLE MATERIALS</b>	STRONG ACIDS, STRONG BASES, STRONG OXIDIZING AGENTS, OXYGEN
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b>	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - CARBON OXIDES, SILICON OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

---

## SECTION 11. TOXICOLOGICAL INFORMATION

---

### INFORMATION ON TOXICOLOGICAL EFFECTS

<b>ACUTE TOXICITY</b>	LD50 ORAL - RAT - > 5,000 MG/KG  LC50 INHALATION - RAT - 4 H - 15956 PPM (OECD TEST GUIDELINE 403)  LD50 DERMAL - RABBIT - > 2,000 MG/KG (OECD TEST GUIDELINE 402)  NOAEL ORAL - RAT - 160 MG/KG
<b>SKIN CORROSION/IRRITATION</b>	SKIN - RABBIT RESULT: NO SKIN IRRITATION (OECD TEST GUIDELINE 404)
<b>SERIOUS EYE DAMAGE/EYE IRRITATION</b>	EYES - RABBIT RESULT: NO EYE IRRITATION
<b>RESPIRATORY OR SKIN SENSITISATION</b>	NO DATA AVAILABLE
<b>GERM CELL MUTAGENICITY</b>	CHROMOSOME ABERRATION TEST IN VITRO CHINESE HAMSTER LUNG CELLS RESULT: NEGATIVE OECD TEST GUIDELINE 475 RAT - BONE MARROW RESULT: NEGATIVE
<b>CARCINOGENICITY IARC:</b>	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.



NTP:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.
OSHA:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.
<b>REPRODUCTIVE TOXICITY</b>	NO TOXICITY TO REPRODUCTION
<b>SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE</b>	NO DATA AVAILABLE
<b>SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE</b>	NO DATA AVAILABLE
<b>ASPIRATION HAZARD</b>	NO DATA AVAILABLE
<b>ADDITIONAL INFORMATION</b>	RTECS: JM9237000  PROLONGED OR REPEATED EXPOSURE TO SKIN CAUSES DEFATTING AND DERMATITIS., DIZZINESS, TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

---

## SECTION 12. ECOLOGICAL INFORMATION

---

### TOXICITY

TOXICITY TO FISH	FLOW-THROUGH TEST LC50 - ONCORHYNCHUS MYKISS (RAINBOW TROUT) - CA. 0.46 MG/L - 96 H
TOXICITY TO ALGAE	EC50 - PSEUDOKIRCHNERIELLA SUBCAPITATA (GREEN ALGAE) - 0.22 MG/L - 95 H (OECD TEST GUIDELINE 201)

### PERSISTENCE AND DEGRADABILITY

BIODEGRADABILITY	AEROBIC - EXPOSURE TIME 28 D RESULT: 2 % - NOT BIODEGRADABLE (OECD TEST GUIDELINE 301C)
------------------	--

### BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION	CYPRINUS CARPIO (CARP) - 70 D AT 25 C  BIOCONCENTRATION FACTOR (BCF): 1,100 - 2,400 (OECD TEST GUIDELINE 305C)
-----------------	--

<b>MOBILITY IN SOIL</b>	NO DATA AVAILABLE
-------------------------	-------------------

**RESULTS OF PBT AND  
VPVB ASSESSMENT**

PBT/VPVB ASSESSMENT NOT AVAILABLE AS  
CHEMICAL SAFETY ASSESSMENT NOT  
REQUIRED/NOT CONDUCTED

**OTHER ADVERSE EFFECTS**

AN ENVIRONMENTAL HAZARD CANNOT BE  
EXCLUDED IN THE EVENT OF UNPROFESSIONAL  
HANDLING OR DISPOSAL.  
VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING  
EFFECTS.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

---

**WASTE TREATMENT METHODS**

**PRODUCT**

OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS  
TO A LICENSED DISPOSAL COMPANY. BURN IN A  
CHEMICAL INCINERATOR EQUIPPED WITH AN  
AFTERBURNER AND SCRUBBER BUT EXERT EXTRA  
CARE IN IGNITING AS THIS MATERIAL IS HIGHLY  
FLAMMABLE. CONTACT A LICENSED PROFESSIONAL  
WASTE DISPOSAL SERVICE TO DISPOSE OF THIS  
MATERIAL.

**CONTAMINATED  
PACKAGING**

DISPOSE OF AS UNUSED PRODUCT.

---

**SECTION 14. TRANSPORT INFORMATION**

---

**DOT (US)**

PROPER SHIPPING NAME: FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)  
UN NUMBER: 1993  
CLASS: 3  
PACKING GROUP: II  
REPORTABLE QUANTITY  
(RQ):  
POISON INHALATION HAZARD: NO

**IMDG**

PROPER SHIPPING NAME: FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)  
UN NUMBER: 1993  
CLASS: 3  
PACKING GROUP: II  
EMS-NO: F-E, S-E  
MARINE POLLUTANT : YES

**IATA**

PROPER SHIPPING NAME: FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)  
UN NUMBER: 1993  
CLASS: 3  
PACKING GROUP: II

---

**SECTION 15. REGULATORY INFORMATION**

---

**SARA 302 COMPONENTS** THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 302 EHS TPQ.

**SARA 313 COMPONENTS** THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

**SARA 311/312 HAZARDS** FIRE HAZARD

**MASSACHUSETTS RIGHT TO KNOW COMPONENTS**

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

**PENNSYLVANIA RIGHT TO KNOW COMPONENTS**

	CAS- NO.	REVISION DATE
Hexamethyldisiloxane	107-46-0	

---

**SECTION 16. OTHER INFORMATION**

---

**FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.**

H225	HIGHLY FLAMMABLE LIQUID AND VAPOR.
H410	VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

**MSDS LEGEND**

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

**IMPORTANT:**

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF*

*MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

*VERSION: 3.2.*

*REVISION DATE: 07/01/2020*