Chem-Impex International Inc.

Tel: (630) 766-2112 E-mail: <u>sales@chemimpex.com</u> Shipping and Correspondence: 935 Dillon Drive Wood Dale, IL 60191 USA Fax: (630) 766-2218 Web site: <u>www.chemimpex.com</u> Manufacturing site: 825 Dillon Drive Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	41300
NAME:	Zirconium(IV) butoxide (ca. 80% in 1-Butanol)
SYNONYMS:	Zirconium(IV) tetrabutoxide (ca. 80% in 1-Butanol)
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) FLAMMABLE LIQUIDS (CATEGORY 3), H226 SKIN CORROSION (CATEGORY 1B), H314 SERIOUS EYE DAMAGE (CATEGORY 1), H318 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3), RESPIRATORY SYSTEM, CENTRAL NERVOUS SYSTEM, H335, H336 FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM



SIGNAL WORD

DANGER

HAZARD STATEMENT(S)

H226	FLAMMABLE LIQUID AND VAPOUR.
H314	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H335	MAY CAUSE RESPIRATORY IRRITATION.
H336	MAY CAUSE DROWSINESS OR DIZZINESS.

PRECAUTIONARY STATEMENT(S)

PRECAUTIONARY STA	
P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT
	SURFACES NO SMOKING.
P233	KEEP CONTAINER TIGHTLY CLOSED.
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/
	LIGHTING/ EQUIPMENT.
P242	USE ONLY NON-SPARKING TOOLS.
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC
	DISCHARGE.
P261	AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/
	SPRAY.
P264	WASH SKIN THOROUGHLY AFTER HANDLING.
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA
P280	WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE
	PROTECTION.
P301 + P330 + P331	IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE
	VOMITING.
P303 + P361 + P353	IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY
	ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/
	SHOWER.
P304 + P340 + P310	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP
	COMFORTABLE FOR BREATHING. IMMEDIATELY CALL A
	POISON CENTER/DOCTOR.
P305 + P351 + P338 +	IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL
P310	MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND
	EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A
	POISON CENTER/DOCTOR.
P363	WASH CONTAMINATED CLOTHING BEFORE REUSE.
P370 + P378	IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR
	ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P403 + P233	STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER
	TIGHTLY CLOSED.
P403 + P235	STORE IN A WELL-VENTILATED PLACE. KEEP COOL.
P405	STORE LOCKED UP.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED
	WASTE DISPOSAL PLANT.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:	$\mathrm{C_{16}H_{36}O_4Zr}$
MW:	383.68
CAS-NO.	1071-76-7

PURITY: 27 - 28% (Assay)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION			
ZIRCONIUM TETRA	ZIRCONIUM TETRABUTANOLATE				
	FLAM. LIQ. 3; SKIN CORR. 1B;	>= 70 - < 90 %			
	EYE DAM. 1; H226, H314, H318				
N-BUTANOL					
	FLAM. LIQ. 3; ACUTE TOX. 4;	>= 20 - < 30 %			
	SKIN IRRIT. 2; EYE DAM. 1;				
	STOT SE 3; H226, H302, H315,				
	H318, H335, H336				
	CONCENTRATION LIMITS: >=				
	20 %: STOT SE 3, H335; >= 20 %:				
	STOT SE 3, H336;				

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	TAKE OFF CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH OFF WITH SOAP AND PLENTY OF

WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE CONTACT	RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.CONTINUE RINSING EYES DURING TRANSPORT TO HOSPITAL.
IF SWALLOWED	DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	SUITABLE EXTINGUISHING MEDIA DRY POWDER DRY SAND
	UNSUITABLE EXTINGUISHING MEDIA DO NOT USE WATER JET.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	CARBON OXIDES, ZIRCONIUM OXIDES
ADVICE FOR FIREFIGHTERS	WEAR SELF CONTAINED BREATHING APPARATUS FOR FIRE FIGHTING IF NECESSARY.
FURTHER INFORMATION	USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL	USE PERSONAL PROTECTIVE EQUIPMENT. AVOID
PRECAUTIONS,	BREATHING VAPOURS, MIST OR GAS. ENSURE
PROTECTIVE	ADEQUATE VENTILATION. REMOVE ALL SOURCES OF
EQUIPMENT AND	IGNITION. EVACUATE PERSONNEL TO SAFE AREAS.

EMERGENCY	BEWARE OF VAPOURS ACCUMULATING TO FORM
PROCEDURES	EXPLOSIVE CONCENTRATIONS. VAPOURS CAN
	ACCUMULATE IN LOW AREAS.
	FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE
PRECAUTIONS	TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.
METHODS AND	CONTAIN SPILLAGE, AND THEN COLLECT WITH NON-
MATERIALS FOR	COMBUSTIBLE ABSORBENT MATERIAL, (E.G. SAND,
CONTAINMENT AND	EARTH, DIATOMACEOUS EARTH, VERMICULITE) AND
CLEANING UP	PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO
	LOCAL / NATIONAL REGULATIONS (SEE SECTION 13).
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	AVOID CONTACT WITH SKIN AND EYES. AVOID INHALATION OF VAPOUR OR MIST. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE. FOR PRECAUTIONS SEE SECTION 2.2.
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. MOISTURE SENSITIVE.
SPECIFIC END USE(S)	Store at RT APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS	
			PARAMETERS		
Zirconium(IV)	1071-76-7	TWA	5 MG/M3	USA. OCCUPATIONAL	
butoxide (ca. 80%				EXPOSURE LIMITS (OSHA) -	
in 1-Butanol)				TABLE Z-1 LIMITS FOR AIR	
				CONTAMINANTS	
		TWA	5 MG/M3	USA. ACGIH THRESHOLD	
				LIMIT VALUES (TLV)	
	REMARKS		ORY IRRITATION		
			SIFIABLE AS A HUM		
		STEL	10 MG/M3	USA. ACGIH THRESHOLD	
				LIMIT VALUES (TLV)	
		RESPIRATORY IRRITATION			
			SIFIABLE AS A HUM	•	
		TWA	5 MG/M3	USA. NIOSH	
				RECOMMENDED EXPOSURE	
				LIMITS	
		ST	10 MG/M3	USA. NIOSH	
				RECOMMENDED EXPOSURE	
		DEI		LIMITS	
		PEL	5 MG/M3	CALIFORNIA PERMISSIBLE	
				EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS	
		STEL	10 MG/M3	CALIFORNIA PERMISSIBLE	
		SIEL	10 1010/1015	EXPOSURE LIMITS FOR	
				CHEMICAL CONTAMINANTS	
N-BUTANOL	71-36-3	TWA	20 PPM	USA. ACGIH THRESHOLD	
N-DO IANOL	/1-50-5	1 11/1	2011111	LIMIT VALUES (TLV)	
		UPPER RES	PIRATORY TRACT I		
		EYE IRRITATION			
		C	50 PPM	USA. NIOSH	
		C	150 MG/M3	RECOMMENDED EXPOSURE	
				LIMITS	
		POTENTIAI	L FOR DERMAL ABS		
		TWA	100 PPM	USA. OCCUPATIONAL	
			300 MG/M3	EXPOSURE LIMITS (OSHA) -	
				TABLE Z-1 LIMITS FOR AIR	
				CONTAMINANTS	
		THE VALUE IN MG/M3 IS APPROXIMATE.			
		С	50 PPM	CALIFORNIA PERMISSIBLE	
			150 MG/M3	EXPOSURE LIMITS FOR	
				CHEMICAL CONTAMINANTS	
	1	1		1	

EXPOSURE CONTROLS

APPROPRIATE	HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL
ENGINEERING CONTROLS	HYGIENE AND SAFETY PRACTICE. WASH HANDS
	BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION	TIGHTLY FITTING SAFETY GOGGLES. FACESHIELD (8-
	INCH MINIMUM). USE EQUIPMENT FOR EYE
	PROTECTION TESTED AND APPROVED UNDER
	APPROPRIATE GOVERNMENT STANDARDS SUCH AS
	NIOSH (US) OR EN 166(EU).

SKIN PROTECTIONHANDLE WITH GLOVES. GLOVES MUST BE INSPECTED
PRIOR TO USE. USE PROPER GLOVE REMOVAL
TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER
SURFACE) TO AVOID SKIN CONTACT WITH THIS
PRODUCT. DISPOSE OF CONTAMINATED GLOVES
AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS
AND GOOD LABORATORY PRACTICES. WASH AND DRY
HANDS.

FULL CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT MATERIAL: NITRILE RUBBER MINIMUM LAYER THICKNESS: 0.11 MM BREAK THROUGH TIME: 480 MIN MATERIAL TESTED:DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTIONCOMPLETE SUIT PROTECTING AGAINST CHEMICALS,
FLAME RETARDANT ANTISTATIC PROTECTIVE
CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT
MUST BE SELECTED ACCORDING TO THE
CONCENTRATION AND AMOUNT OF THE DANGEROUS
SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION	WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTIPURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).
CONTROL OF ENVIRONMENTAL EXPOSURE	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	White to yellow to green clear liquid
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING	
POINT/FREEZING POINT	
INITIAL BOILING POINT	
AND BOILING RANGE	
FLASH POINT	38 °C
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID,	NO DATA AVAILABLE
GAS)	
UPPER/LOWER	UPPER EXPLOSION LIMIT: 11.2 %(V)
FLAMMABILITY OR	LOWER EXPLOSION LIMIT: 1.4 %(V)
EXPLOSIVE LIMITS	
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	1.06 g/mL
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT:	NO DATA AVAILABLE
N- OCTANOL/WATER	
AUTO-IGNITION	NO DATA AVAILABLE
TEMPERATURE	
DECOMPOSITION	NO DATA AVAILABLE
TEMPERATURE	
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	HEAT, FLAMES AND SPARKS
INCOMPATIBLE MATERIALS	BASES, OXIDIZING AGENTS, ALKALI METALS, STRONG OXIDIZING AGENTS, STRONG ACIDS, HALOGENS
HAZARDOUS DECOMPOSITION PRODUCTS	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS CARBON OXIDES, ZIRCONIUM OXIDES IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS		
ACUTE TOXICITY	NO DATA AVAILABLE	
	INHALATION: NO DATA AVAILABLE	
	DERMAL: NO DATA AVAILABLE	
	NO DATA AVAILABLE	
SKIN CORROSION/IRRITATION	NO DATA AVAILABLE	
SERIOUS EYE DAMAGE/EYE IRRITATION	NO DATA AVAILABLE	
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE	
GERM CELL MUTAGENICITY	NO DATA AVAILABLE	
CARCINOGENICITY		

IARC:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS
	IDENTIFIED AS PROBABLE, POSSIBLE OR
	CONFIRMED HUMAN CARCINOGEN BY IARC.
NTP:	NO COMPONENT OF THIS PRODUCT PRESENT AT
	LEVELS GREATER THAN OR EQUAL TO 0.1% IS
	IDENTIFIED AS A KNOWN OR ANTICIPATED
	CARCINOGEN BY NTP.
OSHA:	NO COMPONENT OF THIS PRODUCT PRESENT AT
	LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON
	OSHA S LIST OF REGULATED CARCINOGENS.
REPRODUCTIVE TOXICITY	NO DATA AVAILABLE
SDECIEIC TADCET ODCAN	ΝΟ ΠΑΤΑ ΑΥΑΠ ΑΒΙ Ε

SPECIFIC TARGET ORGAN NO DATA AVAILABLE TOXICITY - SINGLE EXPOSURE

SPECIFIC TARGET ORGAN NO DATA AVAILABLE **TOXICITY - REPEATED EXPOSURE**

ASPIRATION HAZARD NO DATA AVAILABLE

ADDITIONAL INFORMATION RTECS: NOT AVAILABLE

CENTRAL NERVOUS SYSTEM DEPRESSION, GASTROINTESTINAL DISTURBANCE, DRYING, CRACKING OF THE SKIN, SKIN IRRITATION

STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	NO DATA AVAILABLE
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCTOFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS
TO A LICENSED DISPOSAL COMPANY. BURN IN A
CHEMICAL INCINERATOR EQUIPPED WITH AN
AFTERBURNER AND SCRUBBER BUT EXERT EXTRA
CARE IN IGNITING AS THIS MATERIAL IS HIGHLY
FLAMMABLE. CONTACT A LICENSED PROFESSIONAL
WASTE DISPOSAL SERVICE TO DISPOSE OF THIS
MATERIAL.CONTAMINATEDDISPOSE OF AS UNUSED PRODUCT

CONTAMINATEDDISPOSE OF AS UNUSED PRODUCT.PACKAGING

SECTION 14. TRANSPORT INFORMATION

DOT (US) PROPER SHIPPING NAME:	FLAMMABLE LIQUID, N.O.S. (Zirconium(IV) butoxide (ca. 80% in 1-Butanol))
UN NUMBER:	1993
CLASS:	3
PACKING GROUP:	III
REPORTABLE QUANTITY (RQ):	100 LBS
POISON INHALATION HAZARD:	NO
IMDG	
PROPER SHIPPING NAME:	FLAMMABLE LIQUID, N.O.S. (Zirconium(IV) butoxide (ca. 80% in 1-Butanol))
UN NUMBER:	1993
CLASS:	3
PACKING GROUP:	III
EMS-NO:	F-E, S-E
IATA	
PROPER SHIPPING NAME:	FLAMMABLE LIQUID, N.O.S. (Zirconium(IV) butoxide (ca. 80% in 1-Butanol))
UN NUMBER:	1993
CLASS:	3
PACKING GROUP:	III

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS

THE FOLLOWING COMPONENTS ARE SUBJECT TO REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:

CAS-NO.REVISION DATEZirconium(IV) butoxide (ca.1071-76-707-01-200780% in 1-Butanol)07-01-200707-01-2007

SARA 311/312 HAZARDS FIRE HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

Zirconium(IV) butoxide (ca.	CAS-NO.	REVISION DATE
80% in 1-Butanol)	1071-76-7	02-16-1993
N-BUTANOL	71-36-3	07-01-2007

SECTION 16. OTHER INFORMATION

FULL TEXT OF H	I-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.
H226	FLAMMABLE LIQUID AND VAPOUR.
H314	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
H335	MAY CAUSE RESPIRATORY IRRITATION.
H336	MAY CAUSE DROWSINESS OR DIZZINESS.

MSDS LEGEND	
MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENENTAL
	INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH
	ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)
IMPORTANT:	
THE INFORMATION ABOVE IS B	ELIEVED TO BE ACCURATE AND REPRESENTS THE

BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO

WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.2.

REVISION DATE: 07/01/2020